

Wrecker CH8T-INT 05272020





SETTING STANDARDS IN HAULING™





CH8-Ton Wrecker: CH8T-INT

www.dancoproducts.com

MADE IN THE USA 💝 • GREENCASTLE, PA

1.814.37 kg



- Aluminum Modular Sides
- Rigid Steel Rear Bumper



- 4,000 lb (1,814.37 kg) Underlift
- Rear Safety Chain Storage Pockets

OPTIONS

- Clutch Pump or PTO/Pump
- Wrecker Special Light Bar
- Tow Dollies & Brackets Safety Chains
- Wheel Lift Straps
- Custom Paint
- Front Push Bumper
- Rear View Camera
- Tunnel Tool Box Option
- Wheel Simulators
- Magnetic Tow Lights
- Additional LED Lighting

RECOVERY BOOM

| Boom Rating at Boom Swivel | 16,000 lb | 7,257.48 kg |
|---|------------|-------------|
| Maximum Angle | 35 Degrees | |
| Lift Height from Ground to Hook at Max. Elevation | 96 in | 243.84 cm |

<u>UNDERLIFT</u>

Lift Capacity at Full Extension

SPECIFICATIONS

| Range of Tilt | Up | 71 Degrees | |
|--------------------------------|------------------|------------|-------------|
| | Down | 22 Degrees | |
| Distance from Bumper to Center | Line of Lift Arm | | |
| | Retracted | 51 in | 129.54 cm |
| | Extended | 80-5/8 in | 204.79 cm |
| Tow Rating | | 7,500 lb | 3,401.94 kg |

4.000 lb

WINCH & CARLES

| WINCH & CADELS | | |
|--|----------------|-------------------|
| Winch Rating: 1st Layer of Each Drum/Winch | 8,000 lb | 3,628.74 kg |
| Cable Diameter and Length Each Drum | 3/8 in x 75 ft | 0.95 cm x 22.86 m |

CHASSIS RECOMMENDATIONS

| Cab to Axle | 60 in | 152.40 cm |
|--|---------------|--------------|
| Cab to Axle: 24" (60.96 cm) Tunnel Box | 84 in | 213.36 cm |
| Minimum GVWR | 15,000 lb | 6,803.89 kg |
| Maximum GVWR | 26,000 lb | 11,793.40 kg |
| Minimum Frame RBM | 280 000 in-lh | |

STANDARD FEATURES

- Integrated Boom & Underlift System
- Dual Boom Tilt Cylinders
- Power Fold Underlift
- Fold Cylinder Inspection Panel
- Pilot Operated Holding Valves
- Self Centering Crossbar
- Wheel Grids and Lift Arms • 60" (152.40 cm) Aluminum Body
- 88" (223.52 cm) Body Width
- Right & Left Side Tool Compartments
- Contour Fender Design
- Rotary Style Latches
- Chrome Finished Flush Mount Hinges
- Right & Left Side Manual Controls Contol Rod Linkages (Not Cables)
- Ramsey High Speed Worm Gear Winch
- Cable Tensioner
- Winch Free Spool Handle
- Hydraulic Reservoir w/ Filter
- Weather Resistant Electrical System
- LED STT & Marker Lights
- Junction Box & Wiring Harness
- Back-Up LED Light w/ Alarm • Low Mount Chain Anchors

• 1 Pr Low Mount LED Work Lights

- Trailer Hitch Receiver Adapter
- Rear Receptacle for Tow Lights
- Lift Arm Storage Pockets
- Safety Chain Storage Pockets
- Full Height Enclosed Pylon
- Federal Standard #108 Lighting
- Lubrication Fitting at Pivot Points

IMPORTANT: Gross vehicle rating limitation must be considered. Ratings are based on structural factors only, not chassis capacity. Danco specifications shown are approximations and may vary depending on chassis selected. Prices and product specifications are subject to change without notice. Optional equipment may be shown in photographs and may not be part of the standard package. Optional upgrade prices not included in standard pricing. See dancoproducts.com for a more complete list of specifications. * Optional upgrade prices not included in standard pricing.

All prices are installed, Freight on Board Greencastle, PA

DANCO PRODUCTS

411 South Cedar Lane Greencastle, PA 17225 Telephone: 717-597-7185 Toll-free in US 1-800-453-2626 www.dancoproducts.com