

# Above Ground Tanks - small-medium - water & waste

### Vertical - Baffled - Rectangular - 800-1000 Litres All Applications including WRAS

Volume (Litres)	Volume (Gallons)	Stock Code	Length (mm)	Height (mm)	Depth (mm)	Standard Outlet	Lid Quantity	Lid Diameter	Dry Weight (kg)	Standard Colour	PRICE £
800	176	PS-171508	1,250	1,155	700	1.5"	1	255mm VENTED	55	BLACK	see website
1,000	220	PS-171510	1,650	1,305	600	1.5"	1	255mm VENTED	70	BLACK	see website



Vertical use, rectangular, slimline tank manufactured from a WRAS-approved medium density polyethylene (MDPE). Complete with a single, vented lid and multiple slots for securing with ratchet/cargo straps and/or a metal frame, this tank has moulded-in baffles to prevent sloshing and increase stability when on the move.

**Multiple applications**: potable drinking water, rainwater harvesting, liquid transport, grey and black toilet waste collection for glamping huts, constructions sites, catering stands and event industry accommodation.

## Flat - Baffled - Rectangular - 800-1000 Litres

### All Applications including WRAS

Volume (Litres)	Volume (Gallons)	Stock Code	Length (mm)	Depth (mm)	Height (mm)	Standard Outlet	Lid Quantity	Lid Diameter	Dry Weight (kg)	Standard Colour	PRICE £
800	176	PS-171708	1,250	1,100	755	1.5"	1	255mm VENTED	55	BLACK	see website
1,000	220	PS-171710	1,650	1,250	655	1.5"	1	255mm VENTED	70	BLACK	see website



Flat use, rectangular, slimline tank manufactured from a WRAS-approved medium density polyethylene (MDPE). Complete with a single, vented lid and multiple slots for securing with ratchet/cargo straps and/or a metal frame, this tank has moulded-in baffles to prevent sloshing and increase stability when on the move.

**Multiple applications**: potable drinking water, rainwater harvesting, liquid transport, grey and black toilet waste collection for glamping huts, constructions sites, catering stands and event industry accommodation.

### **Vertical**<sup>(1)</sup>/ **Horizontal**<sup>(2)</sup>- **Baffled** - 450 Litres

#### **All Applications including WRAS**

	Volume (Litres)	Volume (Gallons)	Stock Code	Length (mm)	Height (mm)	Depth (mm)	Standard Outlet	Lid Quantity	Lid Diameter	Dry Weight (kg)	Standard Colour	PRICE £
(1) -	450	99	PS-450V3	1,250	1,100	460	1" BSP	1	210mm VENTED	35	BLACK	see website
(2) -	450	99	PS-450H3	1,250	460	1,100	1" BSP	1	210mm VENTED	35	BLACK	see website



Vertical and horizontal use, rectangular, slimline tank manufactured from a WRAS-approved medium density polyethylene (MDPE). Complete with an 8" vented lid and a 1" brass insert, this tank has two moulded-in baffles to restrict sloshing and increase stability when transporting liquids.

**Multiple applications**: potable drinking water, rainwater harvesting, liquid transport, grey and black toilet waste collection for glamping huts, constructions sites, catering stands and event industry accommodation.



**Please note:** tank sizes quoted are subject to a +/-3% variation. We reserve the right to amend the technical specification to improve the product without prior notification. Standard **product warranty** on manufacturing process and materials is 12 months: upgrade to a 10 year warranty by returning the Extended Warranty Form within 21 days of purchase. Warranty excludes damage due to misuse.

UK Freephone: 0800 999 6010




## Above Ground Tanks - small-medium - water & waste

# **Options** Rainwater Havesting Kits, Outlets and Linking Kits

Name	Contents	Application	Image
Small Outlet Fittings WRAS-approved	0.5" / 0.75" / 1" / 1.25" / 1.5" Hansen Fittings	Allows connection to a range of fittings. Taps, valves, water pump, etc.	
Medium Outlet Fittings WRAS-approved	2" / 3" / 4" Hansen Fittings	Allows connection to a range of fittings. Taps, valves, water pump, etc.	-4989-
Simple Link Kits	Suitable for water or waste.	2 x tank connectors, 2 x hose barbs, 2 x pipe clips & 1m long flexible hose.	1. 1
(without ball valves)	Link tanks together, 1m apart to increase capacity.	available in 1" 2" 3" or 4" sizes.	
Link Kits	Suitable for water or waste. Link tanks together, 1m apart	2 x tank connectors, 2 x hose barbs, 2 x pipe clips, 2 x ball valves & 1m long flexible hose.	
(with isolating ball valves)	to increase capacity. Facility to isolate tanks from each other.	available in 1" 2" 3" or 4" sizes.	H= -=
Simple Rainwater Kit	Filter collector with 1m link kit. Fits all UK downpipes from 65mm-110mm (round or square). Filter cartridge easily cleaned.	90m <sup>2</sup> roof  Use with small tanks and water butts.  Will need regular maintenance to clear debris from filter.	+
Rainwater Harvesting Kit A	Filter, dirt collection basket, siphon overflow c/w skimming inlet, siphon overflow to fit a 130mm hole	$\frac{200m^2\ roof}{\text{Use when there is only 1 capture tank.}}$ Will need regular maintenance to clear debris from filter.	Tord
Rainwater Harvesting Kit B	in storage tank wall, calmed inlet to prevent incoming water disturbing tank sediment. Use with large tanks.	$\begin{tabular}{ll} 450m^2\ roof \\ Use when surplus water can be siphoned off to mains drainage. \\ Maintain every 3 months to remove debris. \\ \end{tabular}$	



A "catch-all" 1½" **Hansen** fitting is supplied loose with 800 and 1000 litre tanks. Complete with male and female threads, once the tank is in the correct place you can drill the tank and connect this fitting exactly where you want it. The male / female option allows you to connect pipework, ball valves etc. Alternative sizes are available (see above).



Email: sales@glampsan.com Website: www.glampsan.com