

# ACOUSTICAL PANEL LIMITATIONS

## Moisture

Cardinal Acoustic interior panels are not intended for use where they will come in direct contact with water or condensation. However, they can be used for indoor pools, protected open shelters and breezeways.

5/8" and 1" panels should not be used in areas where RH is over 85%. 1 1/2" panels do not have RH restrictions.

## Tolerances

Cardinal interior panels have a tolerance of plus or minus 3/16" in both width and length. Thickness tolerance is +/- 1/8". Beveled edges are recommended where panel edges meet.

## Color Variations

The color and tone of raw unpainted panels is derived from the natural poplar fibers used in the manufacturing process. Please refer to our panel finish bulletin at [www.cardinalacoustics.com](http://www.cardinalacoustics.com) for more information.

## Limited Lifetime Warranty

Cardinal Acoustics, Inc. extends a lifetime warranty against breakage from the date of final acceptance for its products and systems when installed in accordance with the company's published recommendations at the time of purchase as well as CISCA recommendations. Liability is limited to a refund of the purchase price or replacement of material. No responsibility will be assumed for other applications not referred to in this literature.



**CARDINAL**  
ACOUSTICS®

AN ACOUSTICAL WOOD FIBER COMPANY

For more information, visit [cardinalacoustics.com](http://cardinalacoustics.com)  
or call us at 614.721.3001

Email: [info@cardinalacoustics.com](mailto:info@cardinalacoustics.com)

**OFFICE HEADQUARTERS**

2941 Donnylane Blvd.  
Columbus, OH 43235

**MANUFACTURING & FABRICATION PLANT**

2000 S. Yellow Springs St.  
Springfield, OH 45506