

EFFORTLESS PERFORMANCE

Lay-in wood fiber ceiling panels provide durability and noise reduction for high-traffic and high-abuse areas. These easy-to-install wood fiber panels maintain their finish, performance, and quality. We recommend using our Cardinal Clips to keep the panels in place where frequent contact is likely.

- Classrooms
- Gymnasiums
- Corporate offices
- Parking garages

FEATURES

- Compatible with standard 15/16" Intermediate **Acoustical Suspension** System
- Abuse-resistant
- Easy install

For more information, visit cardinal acoustics.com or call us at 614.721.3001

Email: info@cardinalacoustics.com

OFFICE HEADOUARTERS

2941 Donnylane Blvd. Columbus, OH 43235

MANUFACTURING & FABRICATION PLANT

2000 S. Yellow Springs St. Springfield, OH 45506







CARDINAL LAY-IN CEILING SPECIFICATION DETAILS:

EDGE DETAIL	NRC	MOUNTING	THICKNESS*	WIDTH	LENGTH	WEIGHT P/SF
Square	.60	E-400	5/8"	23 ¾"	23 ¾" or 47 ¾"	1.55
	.70	E-400	1"			2.20



FINISH OPTIONS

Cardinal Direct Attached Panels are available in painted natural, painted white, and can be customized to match colors of all paint manufacturers.

Maintains NRC rating and Class A fire resistance rating when factory or field painted

For more information, visit cardinal acoustics.com or call us at 614.721.3001

Email: info@cardinalacoustics.com



Columbus, OH 43235

OFFICE HEADOUARTERS MANUFACTURING & FABRICATION PLANT

2000 S. Yellow Springs St. Springfield, OH 45506



