

ECOsmarte's Rainwater, Cistern or Grey Water System

Recirculation Model 30,000 Gallon Holding Capacity

Retail Price - \$12,995

PLANET FRIENDLY

Est. 1994

1 ECOsmarte DC Voltage Control Box

- WQA GOLD SEAL listed component.
- A DC voltage controller that energizes only when water is flowing by communicating to the Pentair Water Valve and the ECOsmarte Anode Chamber.



• 1 ECOsmarte Copper/Oxygen Anode Chambers (Sch40)

- One pair of self-sacrificing copper plates to generate low level .1ppm to .2ppm copper to travel in the water from point-of-entry to point-of-use.
- One pair of titanium/platinum anodes to generate 02 oxygen. The oxygen makes heavy metals and inorganic chemicals easier to filter.



- Glass Pack® Filter Media
- Top Mount Multiport Backwash Valve w/ Gauge

• 1 Pentair 2850 SXT Programmable and Metered Water Valve

- WQA GOLD SEAL listed component.
- The Pentair Digital SXT Metered Water Valve and Media Tank communicate directly with the ECOsmarte Valve and Meter.
- The system rinses every 500 to 1500 gallons with no brine or chloride discharge and is compliant with current and proposed County and State bans on chloride discharge.













In-Line &
River or Lake Strain Models
Available in different
configurations.