

Tecpel DSL-336A Calibrator



DSL 336A Specifications:

Specifications for DSL 336A CE Approved

Output Sound Pressure Levels 114dB and 94dB re 20 uPa under reference conditions.

Output Frequency 1000Hz 4%

Reference Conditions TEMPERATURE -->23°C(73°F)

ATMOSPHERIC PRESSURE -->1013 mbar (760mm of Hg)

RELATIVE HUMIDITY -->65%

Accuracy of Sound Pressure Level Under stated reference environment conditions 0.5dB

Power One 9V battery 006P or IEC 6F22 or NEDA 1604.

Battery Test Internal circuitry checks condition of battery continuously.

Calibrator will operate at all if battery voltage falls below acceptable range.

Battery life About 50 hours

Dimensions 103(L) x 63(W) x 54(H)mm

Weight approx. 200g (include batteries)

Operating temperature 0 - 50°C(32 - 122°F)

Operating humidity 0 - 90%RH

Accessories 9V battery, Carrying case, Instruction manual. 1" and 1/2"

Microphone Adaptor

Features:

Specifications:

Output Sound Pressure Levels:

114dB and 94dB re 20uPa under reference Conditions

Output Frequency: 1000Hz±2%

Total Harmonic Distortion:

Reference Condition:

Temperature 23°C(73°F)

Static press 103hpa

Relative humidity 50%

Accuracy of sound pressure level:

Understated reference environment conditions ±0.5dB

Battery test:

Operate: Green LED indicator

Low battery: Red LED indicator

Battery: 9V battery

Dimensions: 113x63x44 mm

Weight: Approx.170gStandard Accessories:

Battery, Operation Manual, soft Carrying bag, 1/2 inch Microphone adapter