

Flapper Investigation Tool

Avoid costly and unnecessary fishing operations by confirming safety valve flapper position



Features

- ▶ Fail-safe close feature
- ▶ Suitable for various safety valve sizes/types

Benefits

- ▶ Quickly and cost effectively establish a safety valve is safe to run wireline operations through.
- ▶ Simple to run
- ▶ No need for specialist personnel

Impact Selector's Flapper Investigation Tool (FIT)

is designed to determine the status of the flapper in a safety valve. The modular design allows the length and nipple profile to be changed to suit alternative safety valves with little effort.

The FIT is deployed on wireline and landed against the safety valve nipple no-go. The tool is then slowly lifted. If an overpull is achieved, this verifies that the flapper is not housed as it should be and could lead to a potential fishing event should the tool string be deployed below this point.

If no overpull is achieved, this verifies the flow tube is fully stroked, the flapper is contained as designed, and intervention can safely take place.

After determining flapper status, the FIT must be activated by downward jarring against the nipple no-go which closes the catch area, providing a continuous flush OD and allowing retrieval to surface.

A brass impression plate on the bottom sub of the tool collects extra information about an open flapper.

FIT Configurations

Nominal Size (inches)	4.50				5.50			
Nipple Size* (inches)	3.813	4.312		4.313	4.562	4.579	4.685	5.000
Nipple Profile*	X, AF, EOF, QN				AF, QN, DB, RQ			
No-Go to Flapper Recess Length (inches)	46, 66, 108, 114, 122, 130, 189				55, 82, 105, 156			

*Nipple Profiles and Lengths available upon request.



IMPACT SELECTOR®
Intelligent Conveyance® Technologies



1-800-238-9239



impact@impactselector.com



www.impactselector.com

ISO 9001-2015 / ISO 45001-2018

Heath, TX-USA and Aberdeen, Scotland-UK

©Impact Selector – All rights reserved. November 2022