

# XRVAP PRO

# PureBlue

Wenn Reinigung begeistert

PROFESSIONAL LINE  
XRVAP PRO



Steam cleaner - 10 bar with continuous flow and digital display.

| Technical features               | Data   |
|----------------------------------|--|
| Colour:                          | Black/transparent blue/woodline/chrome   |
| Steam production:                | continuous flow with automatic filling system                                  |
| Boiler Steam temperature:        | 180 ° C  |
| Heating time:                    | 4 minutes  |
| Pressure (bar):                  | 10   |
| Boiler Power Consumption (W):    | 3200   |
| Boiler volume (l):               | 2  |
| Steam EV1 (gr/min):              | 76 gr/min  |
| Steam EV2 (gr/min):              | 84 gr/min  |
| Steam EV1+EV2 (gr/min):          | 102 gr/min   |
| Boiler material:                 | stainless steel AISI 304   |
| Steam regulation on steam hose:  | activation on the pistol grip with indication in digital display frontal panel |
| Total Power Consumption (W):     | 3200   |
| Iron Power Consumption (W):      | 800  |
| Voltage:                         | 230 V AC / 50 Hz   |
| Tank capacity (l):               | 1,3  |
| Water level alarm:               | visual (digital display) and acoustic  |
| Pressure indicator:              | visual (digital display)   |
| Water pump power:                | 48W 220-240V AC/50Hz   |
| Low tension voltage on handgrip: | 9V DC  |
| Power cable:                     | 7 m  |
| Net weight (only machine) (kg):  | 7,80   |
| Machine Dimensions (DxH):        | 450x390 mm   |
| Certification Reached:           | CE   |



# XRVAP PRO

## PROFESSIONAL LINE 3000/3000D Medical



## PureBlue

Wenn Reinigung begeistert



Steam cleaner with continuous flow, vacuum function (water filter) available with detergent function. This model has reached an important certification: CE Medical which gives to the machine an additional value and the possibility to be used in hospitals. The trolley (optional) is light and versatile.

| Technical features               | Data  |
|----------------------------------|---|
| Colour:                          | White   |
| Steam production:                | continuous flow with automatic filling system                         |
| Boiler Steam temperature:        | 161 °C  |
| Heating time:                    | 5 minutes   |
| Pressure (bar):                  | 6,5   |
| Boiler Power Consumption (W):    | 2200  |
| Boiler volume (l):               | 2   |
| Steam EV1 (gr/min)               | 48 gr/min   |
| Steam EV2 (gr/min):              | 56 gr/min   |
| Steam EV1+EV2 (gr/min):          | 64 gr/min   |
| Detergent injection quantity:    | 10 cc/min   |
| Boiler material:                 | Stainless Steel AISI 304  |
| Vac Motor suction power (Kpa):   | 19  |
| Vac Motor Power Consumption (W): | 1000  |
| Total Power Consumption (W)      | 3200  |
| Voltage:                         | 230 V AC / 50 Hz  |
| Tank capacity (l):               | 2,2   |
| Waste tank capacity (l)          | 1   |
| Water level alarm:               | visual and acoustic   |
| Pressure indicator:              | visual  |
| Detergent Tank capacity (l):     | 1l  |
| Detergent tank - level alarm:    | visual and acoustic   |
| Steam activation:                | activation on the pistol grip - with indication in led frontal pannel |
| Vaacum activation:               | activation on the pistol grip - with indication in led frontal pannel |
| Detergent activation:            | activation on the pistol grip - with indication in led frontal pannel |
| Water pump power:                | 48W 220-240V AC / 50Hz  |
| Low tension voltage on handgrip: | 9 V   |
| Power cable:                     | 7 mt  |
| Detergent pump power:            | 21W 220-240V AC / 50Hz  |
| Net weight (only machine) (kg):  | 14,5  |
| Dimensions (LxWXH):              | 530x400xH.400   |
| Certification Reached:           | CE MEDICAL  |



# XRVAP PRO

## PureBlue

Wenn Reinigung begeistert

### PROFESSIONAL LINE Inox 6000



Stainless steel steam cleaner with continuous flow - 10 bar, vacuum function (water filter), detergent or hot water injection.

| Technical features                    | Data  |
|---------------------------------------|---|
| Colour:                               | steel grey  |
| Steam production:                     | continuous flow with automatic filling system                                     |
| Boiler Steam temperature:             | 180°C   |
| Heating time:                         | 4 minutes   |
| Pressure (bar):                       | 10  |
| Boiler Power Consumption (W):         | 3200  |
| Boiler volume (l):                    | 2   |
| Steam EV1 (gr/min):                   | 73 gr/min   |
| Steam EV2 (gr/min):                   | 84 gr/min   |
| Steam EV1+EV2 (gr/min):               | 100 gr/min  |
| Detergent injection quantity:         | 10 cc/min   |
| Boiler material:                      | Stainless steel AISI 304  |
| Steam regulation on steam hose:       | activation on the pistol grip-with indication in digital display on frontal panel |
| Vac Motor suction power (Kpa):        | 21,5  |
| Vac Motor Power Consumption (W):      | 1200  |
| Total Power Consumption (W):          | 3400  |
| Voltage: 2                            | 30 V AC / 50 Hz   |
| Tank capacity (l):                    | 5   |
| Waste tank capacity (l) :             | 6,5   |
| Water level alarm:                    | visual and acoustic   |
| Pressure indicator:                   | visual  |
| Detergent Tank capacity (l):          | 5 L   |
| Detergent tank - level alarm:         | visual and acoustic   |
| Hot Water Injection + Steam (gr/min): | 364 gr/min.   |
| Water pump power:                     | 48W 220-240V AC/50Hz  |
| Low tension voltage on handgrip:      | 9 V DC  |
| Power cable:                          | 7 m   |
| Net weight (only machine) (kg):       | 35  |
| Dimensions (LxWXH):                   | 440x465x705 mm  |
| Certification Reached:                | CE  |

# XRVAP PRO

## PROFESSIONAL LINE INOX 8000



# PureBlue

Wenn Reinigung begeistert



Professional stainless steel steam cleaner (10bar) with automatic refili, hot water jet and detergent function .

| Technical features                    | Data  |
|---------------------------------------|---|
| Colour:                               | Stainless steel grey  |
| Steam production:                     | Continuous flow with automatic filler system  |
| Boiler Steam temperature:             | 180 °C  |
| Heating time:                         | 4 minutes   |
| Pressure (bar):                       | 10  |
| Boiler Power Consumption (W):         | 3200  |
| Boiler volume (l):                    | 2   |
| Steam EV1 (gr/min)                    | 73 gr/min   |
| Steam EV2 (gr/min):                   | 84 gr/min   |
| Steam EV1+EV2 (gr/min):               | 100 gr/min  |
| Detergent injection quantity:         | 10 cc / min   |
| Boiler material:                      | Stainless steel 304   |
| Steam regulation on steam hose:       | Activation on the handle τ with printed board indications.<br>Lights upon the front panel |
| Total Power Consumption (W):          | 3200  |
| Voltage:                              | 230 V AC / 50 Hz  |
| Tank capacity (l):                    | 5   |
| Water level alarm:                    | Visual and acoustic   |
| Pressure indicator:                   | Visual  |
| Detergent Tank capacity (l):          | 3 l   |
| Detergent tank - level alarm:         | Visual and acoustic   |
| Hot Water Injection + Steam (gr/min): | 364 gr/min  |
| Water pump power:                     | 48W 220 - 240V AC / 50Hz  |
| Low tension voltage on handgrip:      | 9V DC   |
| Power cable:                          | 7 mt  |
| Net weight (only machine) (kg):       | 17  |
| Dimensions (LxWXH)                    | 320x400x320 mm  |
| Certification Reached:                | CE  |





# PureBlue

Wenn Reinigung begeistert

## PROFESSIONAL LINE Odonto-Steam



Stainless steel steam cleaner with continuous flow suitable for dentist labs and jewelry

| Technical features                    | Data  |
|---------------------------------------|---|
| Colour:                               | stainless steel   |
| Steam production:                     | continuous flow   |
| Boiler Steam temperature:             | 171°C   |
| Heating time:                         | 5 minutes   |
| Pressure (bar):                       | 10 bar  |
| Boiler Power Consumption (W):         | 3200  |
| Boiler volume (l):                    | 2   |
| Steam EV1 (gr/min):                   | 36 gr/min minimum regulation - 76 gr/min maximum regulation   |
| Boiler material:                      | Stainless Steel AISI 304                                      |
| Steam regulation on steam hose :      | no  |
| Total Power Consumption (W):          | 3200  |
| Voltage:                              | 230 V 50 Hz   |
| Tank capacity (l):                    | 5   |
| Water level alarm:                    | visual and acoustic   |
| Pressure indicator:                   | visual  |
| Hot Water Injection + Steam (gr/min): | 173 gr/min minimum regulation - 224 gr/min maximum regulation |
| Water pump power:                     | 48W   |
| Low tension voltage on handgrip:      | 9 V   |
| Power cable:                          | 7 m   |
| Net weight (only machine) (kg):       | 8,8   |
| Dimensions (LxWXH):                   | 322x365x330 mm  |
| Certification Reached:                | CE  |