



LED Flood Light

Model: SZ-FL600W



Advantage:

- UL&DLC certificate
- 3030 Chip, high CRI
- Input voltage 100-277VAC
- No UV or IR in the beam
- Easy to install and operate
- Energy saving, long lifespan
- Light is soft and uniform, safe to eyes
- Instant start, NO flickering, NO humming
- Green and eco-friendly without mercury.



Application:

Factory floor, libraries, square, park;
Supermarkets, railway stations;
Advertising lighting, etc.



Product Specifications

Product Name	LED Flood Light
Light Type	SZ-FL300WCT3*2 module

Technical Characteristic

Color temperature	5000K/5700K
CRI	>70
Lumen	78000 LM
Lumen Efficacy	130mLM/W
Input Power	600W
Viewing Anle	60° / 90°
Input Voltage	100-277V 50/60Hz
Driver model	SOSEN
PF	>0.9
Waterproof Rating	IP65

Materials

LED Type	3030/1.5W
LED QTY	384*2, 768PCS
Housing	Aluminum(ADC12) +PC
Housing color	Black
Operating Temperature	-40℃ TO 45℃
Operating Humidity	10%-90% RH
Storage Temperature	-40℃ TO 80℃

Other

Storage Humidity	10%-95%
Application	Outdoor
Safety Certification	UL&DLC
Warranty Time	5 Years
Parking Info	N.W:20kg 1PCS /Carton