



LED Parking Lot Light

Model: SZ-PK600W-SL3-S[1, 2, 3]-5700K


Advantage:

- UL&DLC certificate
- 3030 Chip, high CRI
- Input voltage 100-277VAC
- No UV or IR in the beam
- Easy to install and operate
- Energy saving, long lifespan
- Light is soft and uniform, safe to eyes
- Instant start, NO flickering, NO humming
- Green and eco-friendly without mercury.


Application:

Outdoor basketball court, tennis court.
Badminton court, the football field.
The school playground, stadium.
Community leisure entertainment plaza,
road lamp etc.


Unit: mm




AM



DM



FM



Product Specifications

Product Name	LED parking lot light
Model	SZ-PK600W-SL3-S[1, 2, 3]-5700K
Dimension	950*380*190mm

Technical Characteristic

Color temperature	5000K/5700K
CRI	>70
Lumen	81000LM
Lumen Efficacy	135LM/W
Input Power	600W
Viewing Angle	Type III, TypeIV, Type V, (Optional)
Input Voltage	100-277V 50/60Hz
Driver model	Mean Well Driver (1-10Vdc Dimmer / Surge protector)
Optional Accessory	Photocell / Surge protector
Mounting Option	Slip Fitter / Direct / Flood Mount (Optional)
PF	>0.9
Waterproof Rating	IP65

Materials



LED Type	SEOUL (SSC) SMD3030
LED QTY	672PCS
Housing	Aluminum(ADC12) +PC
Housing color	Brown
Operating Temperature	-40℃ TO 45℃
Operating Humidity	10%-90% RH
Storage Temperature	-40℃ TO 80℃

Other

Storage Humidity	10%-95%
Application	Outdoor
Safety Certification	UL&DLC
Warranty Time	5 Years

Light Distribution Testing Parameters

DATA OF LAMP			PHOTOMETRIC DATA			EFF:127 lm/W
MODEL				24632	S/MH (C0/180)	1.63
NOMINAL POWER (W)	600		LOR (%)	100.0	S/MH (C90/270)	0.74
RATED VOLTAGE (V)	120		TOTAL FLUX (LM)	81045	η UP, DN (C0-180)	0.1, 67.3
NOMINAL FLUX (LM)	81045		CIE CLASS	DIRECT	η UP, DN (C180-360)	0.1, 32.5
LAMPS INSIDE	1		η up (%)	0.2	CIBSE SHR NOM	1.25
TEST VOLTAGE (V)	120.0		η down (%)	99.8	CIBSE SHR MAX	1.35



Package

Model	Net Weight	Carton Size	Qty / Carton	Gross Weight
SZ-PK600W-SL3-S[1, 2, 3]-5700K AM	16.2KG	1025*455*210mm	1 PC	17.7KG

