## **EVERFLOOR**



Summary Datasheet



#### Part 1: Dimensions

Width	125	mm
Length	1850	mm
Thickness	14.3	mm
Boards Per Box	6	planks
Box Size	1.3875	sqm

### Part 2: General Data

Surface Lacquer	EverGuard™ Protection, developed with Teknos Treffert Parquet Lacquer, each board with 10 - 11 Coats, utilising 6 types of lacquer:  • UV PU Insulation Base Coat • UV Transparent Sealer Base Coat • UV Anti Scratch Sealer Base Coat • UV Sealer Low Gloss Base Coat OR Semi-Gloss Base Coat • UV Super Matt Top Coat OR Semi-Gloss Top Coat	
Edging	Micro-Bevelled Edging	
Finish	Depending on product selection:      Semi-Gloss Smooth      Matte Brushed	
Installation Method	Floating Click Installation (Recommended) Trowel Glue Installation	
Box Weight	19.3kg	
Installation Areas	Residential and Commercial	

# **EVERFLOOR**

### Part 4: Installation

Floated on Underlay	Yes Suitable with all EverQuiet® Hard Floor Underlay. Please confirm suitability with other underlays with your installer or retailer.
Trowel Glue	Yes (4 - 6mm trowel)  Note: Floating is the recommended approach of installation, however, adhesive fixed installations are also suitable in some circumstances when the moisture of the environment is well controlled.
Nailed	No

### Part 3: Warranty

General Residential (Structural)	25	years
Light Commercial (Structural)	5	years