

APOLLO 2

130mm Downlight

Apollo 2 is the second generation of our hugely popular Apollo range. Perfect for retrofitting and new builds alike. The refined design will sit smartly in your ceiling and provide a beautifully balanced ambiance and lighting profile.

LEVEL 2
STD


General Specifications

Delivered Lumens ²	900lm @ 3000K
Classification	IC-F
Driver	Phoenix Series Insulation Coverable
IP Rating ⁴	IP65
Power	11W (System)
Warranty ¹	7-Years
Beam Angle	120°
Colour Rendering	~83CRI (Typical)
Dimmable ³	Yes - Leading + Trailing
CCT Options	3000K
Colour/s	White
Material	Aluminum Powder Coated
Clearances	SCB = 0 HCB = 0
Size	Cutout: 100-122mm Depth: 38.9mm Trim: 130mm

Key Facts


Retrofit or New Build

Highly versatile trim design for a discrete new build or retrofit.


Low Profile Design

Fits under building elements and fully insulation coverable.


Long Life by Design

Boasting a 50,000hr L70 rated lifespan for long term ownership.


Assembled in Christchurch

Supporting extremely high quality standards and a local workforce.

80+
CRI11
WATT900
LM

IC-F

LOW
PROFILE

120°

Product Options

SKU Example: A130-DW3K (Dimmable / White Trim / 3000K)

SKU	Driver	Trim	CCT	Optics	Technology
A130	(D) Dimmable	(W) White	(3K) 3000K	(_)120° Optic	N/A

(1.) Warranty for residential use. 5 Year warranty for commercial use. (2.) Subject to a +-5% light production tolerance. (3.) Processor ability. Not applicable to all dimmer mechanisms. Specifications are provided on an 'as is' basis and are subject to change without notice. (4) Refers to the front of the lamp. Rear of lamp is IP40.

