



## ALUMINUM THERMO ALU75 PANORAMICVIEW™

Thermo Alu75 PanoramicView delivers the same high performance of Thermo Alu75, but with an extra slim, 3" frame that provides a consistent widths for fixed and operable units, establishing uniform glass lines for your design. Available in double or triple pane glass.

### PERFORMANCE

Frame Depth = 75mm (2.95")

CE Values:

$U_f = 1.92 \text{ W/(m}^2\text{K)}$

$U_g = 0.53 \text{ W/(m}^2\text{K)}$

$U_w = 0.9 \text{ W/(m}^2\text{K)}$

$\Psi = 0.050 \text{ W/mK}$

STC / OITC Values:

STC upto 31

OITC upto 23

### FINISH OPTIONS

Interior and Exterior: RAL powder coated, Tactile Series, and Anodized options.

### CONFIGURATIONS AVAILABLE

Fixed

Tilt-turn, Tilt-only, Turn-only, Tilt-first

Fixed/Operable combinations

French window opening

### HARDWARE

European multi-point locking system with upto eight locking points on windows and four points on entry doors. Concealed hinges standard.



All performance data based on typical assemblies. Discuss specific performance values with a Zola Project Manager

Questions? Contact us for assistance at 303.578.0001