



# Tilting Mini COUPLERS

All the  
options for  
simple, versatile  
and efficient operation



The **tenX Tilt Coupler for Minis** has all of the renowned & patented safety and easy-install features of the Wedgeloock tenX coupler range for large excavators.




Designed to minimize cost and to maintain ease of use, the **Draw Pin Tilt Coupler** enables operators to change attachments by simply pulling one bucket pin.



A tough and robust coupler, requiring minimal installation and maintenance, the **Mechanical Tilt Coupler** is simple to operate. Use the supplied ratchet to operate the unique screw thread system.



wedgeloock



Enjoy the  
versatility of  
**180  
DEGREES**

The entire range  
of **Wedglock Tilt  
Couplers** for mini  
excavators tilt **90  
degrees both sides**  
to give the operator  
total control over  
delicate operations



## tenX® Tilt Coupler

Supplied with two bucket pins

Weight Class	PART #	DESCRIPTION	EST. WEIGHT [kgs]	TILT ANGLE [degrees]
022	CT-022-K	HYDRAULIC TILT COUPLER	40	180
028	CT-028-K	HYDRAULIC TILT COUPLER	80	180
037	CT-037-K	HYDRAULIC TILT COUPLER	96	180
055	CT-055-K	HYDRAULIC TILT COUPLER	145	180
070	CT-070-K	HYDRAULIC TILT COUPLER	185	180

## Mechanical Tilt Coupler

Supplied with operating ratchet & two bucket pins

Weight Class	PART #	DESCRIPTION	EST. WEIGHT [kgs]	TILT ANGLE [degrees]
022	HMT-022-K	MECHANICAL TILT COUPLER	34	180

## Draw Pin Tilt Coupler

Supplied with draw pin & one bucket pin

Weight Class	PART #	DESCRIPTION	EST. WEIGHT [kgs]	TILT ANGLE [degrees]
022	CDT-022-K	DRAW PIN TILT COUPLER	34	180
028	CDT-028-K	DRAW PIN TILT COUPLER	65	180