




SAFE: COMPLIANT SIMPLE: RELIABLE

The coupler that ticks **ALL** the boxes




#### **LIFTING EYE**

Increased working load limits allow lifting capability of the carrier machines to be maximised



# **INSTANT**SAFETY KNUCKLE

Coupler is locked to attachment and safe as soon as the first pin is engaged



# **INSTANT**RESET TRIGGER

Coupler is ready for reattachment immediately after disengagement



# WEDGE and SAFETY ARM

Safety Arm maintains pin-to-Wedge relationship in the event of loss of engagement force



### MULTI-MODEL DESIGN

Easily fits almost all attachments in the weight class

### tenX® Twin-Ram Tilt Coupler

Supplied with two bucket pins

Weight Class	PART #	DESCRIPTION	EST. WEIGHT (kgs)	TILT ANGLE (degrees)
055	CTX-055-K	TWIN-RAM TILT COUPLER	90	145
070	CTX-070-K	TWIN-RAM TILT COUPLER	90	185
130	CTX-130-K	TWIN-RAM TILT COUPLER	90	360
170	CTX-170-K	TWIN-RAM TILT COUPLER	90	520
210	CTX-210-K	TWIN-RAM TILT COUPLER	90	635
270	CTX-270-K	TWIN-RAM TILT COUPLER	90	755
320	CTX-320-K	TWIN-RAM TILT COUPLER	90	1065
450	CTX-450-K	TWIN-RAM TILT COUPLER	90	1750

Complies with the following standards/position papers: ISO 13031, AS4772–2008, EN474, NSW Quick Coupler position paper, NZ WorkSafe Best Practices. Specifications are subject to change without notice. All images used are representative only and may differ from actual product.

