



**ECO Lighting Technology and Solutions**



## Specification

<b>Model No.</b>	<b>CW-200RGB-20</b>
Color	Red, Green, Blue and Yellow
Material	PVC
Diameter	2.2±0.1mm
Qty	200Feet/roll
Conductor stranding	26*0.15
Tolerance mm	±0.002
Resistance Ω/km	41.19
Conductor elongation %	10
Insulation thickness mm	0.38
Insulation thinnest mm	0.33
Nominal Voltage V	300V
Standard	UL1007

## Aging Test

performance			Insulation	Jacket
Aging test	elongation %	Before aging	100%	/
	Expend intension MPA		10	/
	elongation %		change ± 20%	/
	Expend intension MPA	70±2°C×7 70±2°C×7 after aging	change ± 20%	/
Hi-Pot Test	AC V	2000V 5min no strike out		
spark testing		3KV		

## LED Accessories

**Model No. CW-200RGB-20**



**UL Certificate: E137395**

**Please visit [jsledpower.com](http://jsledpower.com) for more information**

**For support please call toll free number 1-800-909-5188**

### Headquarter Office

1318 Maine Ave.,  
Baldwin Park, CA 91706  
Tel: (626) 338 - 8291  
Fax: (626) 338 - 8391

### Texas Branch

2307 Shaver St.,  
Pasadena, TX 77502  
Tel: (832) 270 - 1556

### New Jersey Branch

600 Deer Rd., Suite #3  
Cherry Hill, NJ 08034  
Tel: (646) 287 - 5979

### Florida Branch

4333 Silver Star Rd., Suite #170  
Orlando, FL 32808  
Tel: (407) 808 - 9768