



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

SDS # : 39334

RUBIA TIR 9900 FE 5W-30

Date of the previous version: 2017-10-31

Revision Date: 2018-04-23

Version 4.04

Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name	RUBIA TIR 9900 FE 5W-30
Number	1YW
Substance/mixture	Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Motor oil.
------------------------	------------

1.3. Details of the supplier of the safety data sheet

Supplier	<p style="color: red;">A - TOTAL UK LIMITED 183 Eversholt St, Kings Cross London, NW1 1BU UNITED KINGDOM Tel: +44 (0)20 7339 8000 Fax: +44 (0)20 7339 8033</p> <p style="color: red;">B - TOTAL LUBRIFIANTS 562 Avenue du Parc de L'île 92029 Nanterre Cedex FRANCE Tél: +33 (0)1 41 35 40 00 Fax: +33 (0)1 41 35 84 71***</p>
-----------------	--

For further information, please contact:

Contact Point	A - HSE
E-mail Address	B - HSE*** A - rm.gb-msds@total.co.uk B - rm.msds-lubs@total.com ***

1.4. Emergency telephone number

Emergency telephone: +44 1235 239670

UK: National Poisons Information Service (NPIS): NHS on 111 or a doctor

Section 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Version EUUK



SDS # : 39334

RUBIA TIR 9900 FE 5W-30

Revision Date: 2018-04-23

Version 4.04

REGULATION (EC) No 1272/2008 ***

*For the full text of the H-Statements mentioned in this Section, see Section 2.2. ****

Classification

The product is not classified as dangerous according to Regulation (EC) No. 1272/2008***

2.2. Label elements

Labelled according to REGULATION (EC) No 1272/2008***

Signal word

None***

Hazard Statements ***

None***

Precautionary statements

None***

Supplemental Hazard Statements

EUH210 - Safety data sheet available on request***

EUH208 - Contains C14-16-18 Alkyl phenol. May produce an allergic reaction***

2.3. Other hazards

Physical-Chemical Properties Contaminated surfaces will be extremely slippery.***

Environmental properties The product may form an oil film on the water surface that may stop the oxygen exchange.***

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixture***

Chemical nature

The product is made from refined mineral base oils and synthetic oils.***

Hazardous components

Chemical Name	EC-No	REACH Registration Number	CAS-No	Weight %	Classification (Reg. 1272/2008)
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based***	276-738-4***	01-2119474889-13	72623-87-1	50-<60	Asp. Tox. 1 (H304)
Distillates (petroleum), solvent-dewaxed heavy paraffinic***	265-169-7***	01-2119471299-27	64742-65-0	3-<5	Asp. Tox. 1 (H304)
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based***	276-737-9***	01-2119474878-16	72623-86-0	3-<5	Asp. Tox. 1 (H304)

Version EUUK

SDS # : 39334

RUBIA TIR 9900 FE 5W-30

Revision Date: 2018-04-23

Version 4.04

Reaction products of 1-decene, 1-dodecene and 1-octene, hydrogenated***	605-315-2***	01-2119543695-30** *	163149-28-8	3-<5	Asp. Tox. 1 (H304) ***
Reaction products of 1-decene, hydrogenated***	-	01-2119527646-33	68649-12-7	3-<5	Asp.Tox. 1 (H304)
10-ethyl-12-heptyl-11,13-dimethyltricosane; 8-ethyl-9,11-dimethyl-10-nonylnonadecane ***	604-767-8***	01-2119523580-47** *	151006-60-9	3-<5	Asp. Tox. 1 (H304) ***
Distillates (petroleum), hydrotreated heavy paraffinic***	265-157-1***	01-2119484627-25	64742-54-7	3-<5	Asp. Tox. 1 (H304)
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-trans-butyl-4-hydroxyphenyl)propionate***	406-040-9***	01-0000015551-76	125643-61-0	1-<2.5	Aquatic Chronic 4 (H413)
bis(nonylphenyl)amine***	253-249-4***	01-2119488911-28	36878-20-3	1-<2.5	Aquatic Chronic 4 (H413)
zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)***	298-577-9***	01-2119543726-33	93819-94-4	1-<2.5	Skin Irrit. 2 (H315) Eye Dam. 1 (H318) Aquatic Chronic 2 (H411)
C14-16-18 Alkyl phenol***	931-468-2***	01-2119498288-19	^	0.1-<1	STOT RE 2 (H373) Skin Sens. 1B (H317)

Additional information

Product containing mineral oil with less than 3% DMSO extract as measured by IP 346.***

For the full text of the H-Statements mentioned in this Section, see Section 16.

Section 4: FIRST AID MEASURES

4.1. Description of first aid measures

General advice

IN CASE OF SERIOUS OR PERSISTENT CONDITIONS, CALL A DOCTOR OR EMERGENCY MEDICAL CARE.***

Eye contact

Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing.***

Skin contact

Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Wash contaminated clothing before reuse.***

Inhalation

Remove casualty to fresh air and keep at rest in a position comfortable for breathing. If not breathing, give artificial respiration.***

Ingestion

Clean mouth with water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or poison control centre immediately.***

Protection of first-aiders

First aider needs to protect himself. See Section 8 for more detail. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.***

4.2. Most important symptoms and effects, both acute and delayed

Version EUUK



SDS # : 39334

RUBIA TIR 9900 FE 5W-30

Revision Date: 2018-04-23

Version 4.04

Eye contact	Not classified based on available data. The supplier of some components contained within this formulation has indicated that the classification as irritant is not required.***
Skin contact	Not classified based on available data. May produce an allergic reaction.***
Inhalation	Not classified based on available data. Inhalation of vapours in high concentration may cause irritation of respiratory system.***
Ingestion	Not classified based on available data. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.***

4.3. Indication of any immediate medical attention and special treatment needed

Notes to physician Treat symptomatically.***

Section 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media Carbon dioxide (CO₂). ABC powder. Foam. Water spray or fog.***

Unsuitable Extinguishing Media Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

Special hazard Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. These may be highly dangerous if inhaled in confined spaces or at high concentration. Combustion products include sulphur oxides (SO₂ and SO₃) and Hydrogen sulphide H₂S. Mercaptans. Zinc oxides. Phosphorous oxides. Nitrogen oxides (NOx).***

5.3. Precautions for fire-fighters

Special protective equipment for fire-fighters Wear self-contained breathing apparatus and protective suit.

Other information Cool containers / tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Section 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

General Information Do not touch or walk through spilled material. Contaminated surfaces will be extremely slippery. Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition.***

6.2. Environmental precautions

General Information Do not allow material to contaminate ground water system. Prevent entry into waterways, sewers, basements or confined areas. Local authorities should be advised if significant

Version EUUK



SDS # : 39334

RUBIA TIR 9900 FE 5W-30

Revision Date: 2018-04-23

Version 4.04

spillages cannot be contained.***

6.3. Methods and material for containment and cleaning up

Methods for containment	Dike to collect large liquid spills. If necessary dike the product with dry earth, sand or similar non-combustible materials.***
Methods for cleaning up	Dispose of contents/container in accordance with local regulation. In case of soil contamination, remove contaminated soil for remediation or disposal, in accordance with local regulations.***

6.4. Reference to other sections

Personal protective equipment	See Section 8 for more detail.
Waste treatment	See section 13.

Section 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Advice on safe handling	For personal protection see section 8. Use only in well-ventilated areas. Do not breathe vapours or spray mist. Avoid contact with skin, eyes and clothing.***
Prevention of fire and explosion	Take precautionary measures against static discharges.***
Hygiene measures	Ensure the application of strict rules of hygiene by the personnel exposed to the risk of contact with the product. When using, do not eat, drink or smoke. Wash hands before breaks and immediately after handling the product. Regular cleaning of equipment, work area and clothing is recommended. Do not use abrasives, solvents or fuels. Do not dry hands with rags that have been contaminated with product. Do not put product contaminated rags into workwear pockets.***

7.2. Conditions for safe storage, including any incompatibilities

Technical measures/Storage conditions	Keep away from food, drink and animal feedingstuffs. Keep in a bunded area. Keep container tightly closed. Preferably keep in the original container. Otherwise, reproduce all the statutory information from the labels onto the new container. Do not remove the hazard labels of the containers (even if they are empty). Design the installations in order to avoid accidental emissions of product (due to seal breakage, for example) onto hot casings or electrical contacts. Keep at a temperature not exceeding 60 °C. Protect from moisture.***
Materials to avoid	Strong oxidising agents.***

7.3. Specific use(s)

Specific use(s)	Please refer to Technical Data Sheet for further information.***
------------------------	--

Section 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1. Control parametres

Version EUUK



SDS # : 39334

RUBIA TIR 9900 FE 5W-30

Revision Date: 2018-04-23

Version 4.04

Exposure limits

Mineral oil mist:
 USA: OSHA (PEL) TWA 5 mg/m³, NIOSH (REL) TWA 5 mg/m³, STEL 10 mg/m³, ACGIH (TLV) TWA 5 mg/m³ (highly refined)

Legend

See section 16

Derived No Effect Level (DNEL) *****DNEL Worker (Industrial/Professional)*****

Chemical Name	Short term, systemic effects	Short term, local effects	Long term, systemic effects	Long term, local effects
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based*** 72623-87-1				5.4 mg/m ³ /8h (aerosol - inhalation)
Distillates (petroleum), solvent-dewaxed heavy paraffinic*** 64742-65-0				5.4 mg/m ³ /8h (aerosol - inhalation)
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based*** 72623-86-0				5.4 mg/m ³ /8h (aerosol - inhalation)
Distillates (petroleum), hydrotreated heavy paraffinic*** 64742-54-7				5.4 mg/m ³ /8h (aerosol - inhalation)
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-trans-butyl-4-hydroxyphenyl)propionate** * 125643-61-0	20 mg/kg Dermal	1 mg/cm ² Dermal	0.22 mg/kg Dermal	0.006 mg/cm ² Dermal
bis(nonylphenyl)amine*** 36878-20-3			0.62 mg/kg bw/day Dermal 4.37 mg/m ³ Inhalation	
zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)*** 93819-94-4			0.58 mg/kg Dermal 8.31 mg/m ³ Inhalation	
C14-16-18 Alkyl phenol*** ^			1.17 mg/m ³ (inhalation) 0.30 mg/kg bw/day (dermal)	

DNEL Consumer***

Chemical Name	Short term, systemic effects	Short term, local effects	Long term, systemic effects	Long term, local effects
Lubricating oils (petroleum), C20-50,				1.2 mg/m ³ /24h (aerosol - inhalation)

Version EUUK

SDS # : 39334

RUBIA TIR 9900 FE 5W-30

Revision Date: 2018-04-23

Version 4.04

hydrotreated neutral oil-based*** 72623-87-1				
Distillates (petroleum), solvent-dewaxed heavy paraffinic*** 64742-65-0				1.2 mg/m ³ /24h (aerosol - inhalation)
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based*** 72623-86-0				1.2 mg/m ³ /24h (inhalation -aerosol)
Distillates (petroleum), hydrotreated heavy paraffinic*** 64742-54-7				1.2 mg/m ³ /24h (aerosol - inhalation)
bis(nonylphenyl)amine*** 36878-20-3			0.31 mg/kg bw/day Dermal 1.09 mg/m ³ Inhalation 0.31 mg/kg bw/day Oral	
zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)*** 93819-94-4			0.29 mg/kg Dermal 2.11 mg/m ³ Inhalation 0.24 mg/kg Oral	

Predicted No Effect Concentration (PNEC) ***

Chemical Name	Water	Sediment	Soil	Air	STP	Oral
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based*** 72623-87-1						9.33 mg/kg food
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-trans-butyl-4-hydroxyphenyl)propionate*** 125643-61-0	0.0043 mg/l fw 0.00043 mg/l mw	233 mg/kg fw dw 23.3 mg/kg mw dw	189 mg/kg			
bis(nonylphenyl)amine*** 36878-20-3	0.1 mg/l fw 0.01 mg/l mw 1 mg/l or	132000 mg/kg dw fw 13200 mg/kg dw mw	263000 mg/kg dw		1 mg/l	
zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)*** 93819-94-4	0.004 mg/l fw 0.0046 mg/l mw 0.021 mg/l or	0.0116 mg/kg dw fw 0.00116 mg/kg dw mw	0.00528 mg/kg soil dw		100 mg/l	10.67 mg/kg food

Version EUUK



SDS # : 39334

RUBIA TIR 9900 FE 5W-30

Revision Date: 2018-04-23

Version 4.04

C14-16-18 Alkyl phenol*** ^	0.100 mg/l (fw) 0.010 mg/l (mw) 1 mg/ (or)	4266.16 mg/kg sediment dw (fw) 426.62 mg/kg sediment dw (mw)	852.58 mg/kg soil dw		100 mg/l	
--------------------------------	--	---	----------------------	--	----------	--

8.2. Exposure controls**Occupational Exposure Controls****Engineering measures**

Apply technical measures to comply with the occupational exposure limits. Ensure adequate ventilation, especially in confined areas. When working in confined spaces (tanks, containers, etc.), ensure that there is a supply of air suitable for breathing and wear the recommended equipment.***

Personal protective equipment**General Information**

Protective engineering solutions should be implemented and in use before personal protective equipment is considered. The personal protective equipment (PPE) recommendations apply to the product AS DELIVERED. In case of mixtures or formulations, it is suggested that you contact the relevant PPE suppliers.***

Respiratory protection

None under normal use conditions. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Respirator with combination filter for vapour/particulate (EN 14387). Type A/P1. Warning ! filters have a limited use duration. The use of breathing apparatus must comply strictly with the manufacturer's instructions and the regulations governing their choices and uses.***

Eye protection

If splashes are likely to occur, wear: Safety glasses with side-shields. EN 166.***

Skin and body protection

Wear suitable protective clothing. Protective shoes or boots. Long sleeved clothing. Type 4/6.***

Hand protection

Hydrocarbon-proof gloves. Fluorinated rubber. Nitrile rubber. In case of prolonged contact with the product, it is recommended to wear gloves complying with EN 420 and EN 374 standards, protecting at least for 480 minutes and having a thickness of 0,38 mm at least. These values are indicative only. The level of protection is provided by the material of the glove, its technical characteristics, its resistance to the chemicals to be handled, the appropriateness of its use and its replacement frequency. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.***

Environmental exposure controls**General Information**

The product should not be allowed to enter drains, water courses or the soil.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES9.1. Information on basic physical and chemical properties

Version EUUK



SDS # : 39334

RUBIA TIR 9900 FE 5W-30

Revision Date: 2018-04-23

Version 4.04

Appearance		Clear***	
Colour		brown***	
Physical state @20°C		liquid***	
Odour		characteristic***	
Odour Threshold		No information available***	
Property	Values	Remarks	Method
pH		Not applicable***	
Melting point/range		No information available	
Boiling point/boiling range		No information available***	
Flash point	223*** °C*** 433*** °F***	***	ASTM D 92*** ASTM D 92***
Evaporation rate		No information available***	
Flammability Limits in Air		***	
Upper ***		No information available***	***
Lower ***		No information available***	***
Vapour pressure		No information available***	
Vapour density		No information available***	
Relative density	0.848*** -*** 0.868***	@ 15 °C***	ASTM D 1298***
Density	848*** - *** 868*** kg/m ³ ***	@ 15 °C***	ASTM D 1298***
Water solubility		Insoluble***	
Solubility in other solvents		No information available***	
logPow		No information available***	
Autoignition temperature		No information available***	
Decomposition temperature		No information available	
Viscosity, kinematic	72.5*** mm ² /s***	@ 40 °C***	ASTM D 445***
Explosive properties	Not explosive***		
Oxidising properties	Not applicable***		
Possibility of hazardous reactions	None under normal processing***		

9.2. Other information

Freezing point No information available

Section 10: STABILITY AND REACTIVITY10.1. Reactivity

General Information None under normal processing.***

10.2. Chemical stability

Stability Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions No dangerous reaction known under conditions of normal use.***

Version EUUK



SDS # : 39334

RUBIA TIR 9900 FE 5W-30

Revision Date: 2018-04-23

Version 4.04

10.4. Conditions to avoid

Conditions to avoid Keep away from open flames, hot surfaces and sources of ignition. Keep away from heat and sparks.***

10.5. Incompatible materials

Materials to avoid Strong oxidising agents.***

10.6. Hazardous Decomposition Products

Hazardous Decomposition Products Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. Phosphorous oxides. Nitrogen oxides (NOx). Mercaptans. Combustion products include sulphur oxides (SO₂ and SO₃) and Hydrogen sulphide H₂S. Zinc oxides.***

Section 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effectsAcute toxicity Local effects Product Information

Skin contact	. Not classified based on available data. May produce an allergic reaction.***
Eye contact	. Not classified based on available data. The supplier of some components contained within this formulation has indicated that the classification as irritant is not required.***
Inhalation	. Not classified based on available data. Inhalation of vapours in high concentration may cause irritation of respiratory system.***
Ingestion	. Not classified based on available data. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.***
ATEmix (oral)	79,952.00*** mg/kg***
ATEmix (dermal)	84,805.00*** mg/kg***
ATEmix (inhalation-dust/mist)	7.00*** mg/l***

Acute toxicity - Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based***	LD50 > 5000 mg/kg bw (rat - OECD 401)	LD50 > 5000 mg/kg bw (rabbit - OECD 402)	LC50 (4h) > 5 mg/l (aerosol) (rat - OECD 403)
Distillates (petroleum), solvent-dewaxed heavy paraffinic***	LD50 > 5000 mg/kg bw (rat - OECD 420)	LD50 > 5000 mg/kg bw (rabbit - OECD 402)	LC50 (4h) > 5.53 mg/l (aerosol) (rat - OECD 403)
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based***	LD50 > 5000 mg/kg bw (Rat - OECD TG 401)	LD50 > 2000 mg/kg (Rabbit - OECD 402)	LD50 (4h) > 5.53 mg/l (Rat - OECD 403)
Reaction products of 1-decene, 1-dodecene and 1-octene, hydrogenated***	LD50 5000 mg/kg bw (rat - OECD 403)***	LD50 2000 mg/kg bw (rat - OECD 402)***	
Reaction products of 1-decene,	LD50 > 5000 mg/kg (Rat - OECD	LD50 > 2000 mg/kg (Rabbit -	LC50 (4h) > 5000 mg/m ³ (Rat -

Version EUUK

SDS # : 39334

RUBIA TIR 9900 FE 5W-30

Revision Date: 2018-04-23

Version 4.04

hydrogenated***	401)	OECD 402)	Aerosol - OECD 403)
10-ethyl-12-heptyl-11,13-dimethyltricosane; 8-ethyl-9,11-dimethyl-10-nonylnonadecane ***	LD50 5000 mg/kg bw (rat) ***	LD50 2000 mg/kg bw (rat - OECD 402)***	LC50(4h) 5mg/L (rat - OECD 403)***
Distillates (petroleum), hydrotreated heavy paraffinic***	LD50 > 5000 mg/kg bw (rat - OECD 420)	LD50 > 5000 mg/kg bw (rabbit - OECD 402)	LC50 (4h) > 5 mg/l (aerosol) (rat - OECD 403)
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-trans-butyl-4-hydroxyphenyl)propi onate***	LD50 > 2000 mg/kg (Rat - OECD 401)	LD50 > 2000 mg/kg (Rat - OECD 402)	
bis(nonylphenyl)amine***	LD50 > 5000 mg/kg (Rat - OECD 401)	LD50 > 2000 mg/kg (Rat - OECD 402)	
zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)***	LD50 2600 mg/kg (Rat)	LD50 > 3160 mg/kg (Rabbit - OECD 402)	LC50(1h) > 2 mg/l (Rat - OECD Test Guideline 403)***
C14-16-18 Alkyl phenol***	LD50 2000 mg/kg bw (rat)	LD50 2000 mg/kg bw (rat)	

Sensitisation

Sensitisation

Not classified based on available data. Contains sensitizer(s). May produce an allergic reaction.***

Specific effects

Carcinogenicity

Not classified based on available data. During use in engines, contamination of oil with low levels of combustion products occurs. Used motor oils have been shown to cause skin cancer in mice following repeated application and continuous exposure. Brief or intermittent skin contact with used motor oil is not expected to have serious effects in humans if the oil is thoroughly removed by washing with soap and water.***

Mutagenicity

Germ cell mutagenicity

Not classified based on available data.***

Reproductive toxicity

Not classified based on available data.***

Repeated Dose Toxicity

Target Organ Effects (STOT)

Specific target organ systemic toxicity (single exposure)

Not classified based on available data.***

Specific target organ toxicity - repeated exposure

Not classified based on available data.***

Aspiration toxicity

Not classified based on available data.***

Other information

Other adverse effects

Characteristic skin lesions (oil blisters) may develop following prolonged and repeated exposures (contact with contaminated clothing).***

Section 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Not classified based on available data.***

SDS # : 39334

RUBIA TIR 9900 FE 5W-30

Revision Date: 2018-04-23

Version 4.04

Acute aquatic toxicity - Product Information***

No information available.***

Acute aquatic toxicity - Component Information

Chemical Name	Toxicity to algae	Toxicity to daphnia and other aquatic invertebrates.	Toxicity to fish	Toxicity to microorganisms
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based*** 72623-87-1	EL50 (48h) > 100 mg (Pseudokirchnerella subcapitata - OECD 201)	EL50 (48h) > 10000 mg/l (Daphnia magna - OECD 202) LL50 (24h) > 10000 mg/l (Gammarus pulex - OECD 202) LL50 (48h) > 10000 mg/l (Gammarus pulex - OECD 202) LL50 (72h) > 10000 mg/l (Gammarus pulex - OECD 202) LL50 (96h) > 10000 mg/l (Gammarus pulex - OECD 202)	LL50 (96h) > 100 mg/l (Oncorhynchus mykiss - OECD 203)	
Distillates (petroleum), solvent-dewaxed heavy paraffinic*** 64742-65-0		EL50 (48h) > 10000 mg/l (Daphnia magna - OECD 202)	LL50 (96h) > 100 mg/l (Oncorhynchus mykiss - OECD 203)	
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based*** 72623-86-0		EL50(48h) >1000 mg/l (OECD TG 202)	LL50 (96h) > 100 mg/l (OECD TG 203)	
Reaction products of 1-decene, hydrogenated*** 68649-12-7	EL50 (72h) > 1000 mg/l (WAF - Scenedesmus capricornutum - static - OECD 201)	EL50 (48h) > 1000 mg/l (WAF - Daphnia magna - static - OECD 202)	LC50 (96h) > 1000 mg/l (WAF - Oncorhynchus mykiss - semi static)	
10-ethyl-12-heptyl-11,13-dimethyltricosane; 8-ethyl-9,11-dimethyl-10-nonylnonadecane *** 151006-60-9				EC50(16h) 10000 mg/L***
Distillates (petroleum), hydrotreated heavy paraffinic*** 64742-54-7	EL50 (48h) > 100 mg/l (Pseudokirchnerella subcapitata - OECD 201)	EL50 (48h) > 10000 mg/l (Daphnia magna - OECD 202)	LL50 (96h) > 100 mg/l (Oncorhynchus mykiss - OECD 203)	
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-trans-butyl-4-hydroxyphenyl)propionate*** 125643-61-0	EC50 (72h) > 3 mg/l (Scenedesmus sp. - OECD 201)	EC50(24h) > 100 mg/l (Daphnia magan - OECD 202)	LC50 (96h) > 74 mg/l (Brachydanio rerio - semi static - OECD 203)	
bis(nonylphenyl)amine*** 36878-20-3	EC50 (72h) > 100 mg/l (Desmodesmus subspicatus - OECD 201)	EC50 (48h) > 100 mg/l (Daphnia magna - OECD 202)	LC50 (96h) > 100 mg/l (Brachydanio rerio - OECD 203)	
zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)*** 93819-94-4	EbC50 (96h) 2.1 mg/l Selenastrum capricornutum (OECD 201)	EL50 (48h) 5.4 mg/l Daphnia magna (OECD 202)	LC50 (96h) 4.5 mg/l Oncorhynchus mykiss (OECD 203)	
C14-16-18 Alkyl phenol***		EC50(48h) > 100 mg/l		

Version EUUK



SDS # : 39334

RUBIA TIR 9900 FE 5W-30

Revision Date: 2018-04-23

Version 4.04

^	(Daphnia magna - static - OECD202)
---	------------------------------------

Chronic aquatic toxicity - Product Information

No information available.***

Chronic aquatic toxicity - Component Information

Chemical Name	Toxicity to algae	Toxicity to daphnia and other aquatic invertebrates.	Toxicity to fish	Toxicity to microorganisms
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based*** 72623-87-1	NOEL (72h) >= 100 mg/l (Pseudokirchnerella subcapitata - OECD 201)	NOEL (21d) 10 mg/l (Daphnia magna - OECD 211)	NOEL (14/28d) > 1000 mg/l (Oncorhynchus mykiss - QSAR Petrotox) NOEL (96h) > 100 mg/l (Pimephales promelas - OECD 203)	
Distillates (petroleum), solvent-dewaxed heavy paraffinic*** 64742-65-0		NOEL (21d) 10 mg/l (Daphnia magna - OECD 211)	NOEL (14/28d) > 1000 mg/l (Oncorhynchus mykiss - QSAR Petrotox)	
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based*** 72623-86-0		NOEL (21d) = 10 mg/l (OECD TG 202)	NOELR (14d) > 1000 mg/l (QSAR modelled data)	
Reaction products of 1-decene, hydrogenated*** 68649-12-7		NOELr(21d) 125 mg/l (Daphnia magna)		
Distillates (petroleum), hydrotreated heavy paraffinic*** 64742-54-7		NOEL (21d) 10 mg/l (Daphnia magna - QSAR Petrotox)	NOEL (14/28d) > 1000 mg/l (Oncorhynchus mykiss - QSAR Petrotox)	

Effects on terrestrial organisms

No information available.***

12.2. Persistence and Degradability**General Information**

No information available.

12.3. Bioaccumulative potential**Product Information**

No information available.***

logPow

No information available***

Component Information

Chemical Name	log Pow
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based*** - 72623-87-1	4.1
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based*** - 72623-86-0	6.1
Reaction products of 1-decene, hydrogenated*** - 68649-12-7	5

Version EUUK



SDS # : 39334

RUBIA TIR 9900 FE 5W-30

Revision Date: 2018-04-23

Version 4.04

Distillates (petroleum), hydrotreated heavy paraffinic*** - 64742-54-7	-
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-trans-butyl-4-hydroxyphenyl)propionate*** - 125643-61-0	9.2
bis(nonylphenyl)amine*** - 36878-20-3	7.7
zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)*** - 93819-94-4	0.9

12.4. Mobility in soil

Soil	Given its physical and chemical characteristics, the product generally shows low soil mobility.***
Air	Loss by evaporation is limited.***
Water	The product is insoluble and floats on water.***

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment No information available.***

12.6. Other adverse effects

General Information No information available.***

Section 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from residues / unused products	Should not be released into the environment. Do not empty into drains. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations. Where possible recycling is preferred to disposal or incineration.***
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal.***
EWC Waste Disposal No	According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user based on the application for which the product was used. The following Waste Codes are only suggestions: 13 02 05.***
Other information	Refer to section 8 for safety and protective measures for disposal personnel.***

Section 14: TRANSPORT INFORMATION

<u>ADR/RID</u>	not regulated
<u>IMDG/IMO</u>	not regulated
<u>ICAO/IATA</u>	not regulated

Version EUUK



SDS # : 39334

RUBIA TIR 9900 FE 5W-30

Revision Date: 2018-04-23

Version 4.04

ADN not regulated

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Further information

No information available***

15.2. Chemical Safety Assessment

Chemical Safety Assessment No information available***

15.3. National regulatory information

The United Kingdom

- Avoid exceeding occupational exposure limits (see section 8).

Ireland

- Avoid exceeding occupational exposure limits (see section 8).

Section 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H304 - May be fatal if swallowed and enters airways

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H318 - Causes serious eye damage

H373 - May cause damage to organs through prolonged or repeated exposure

H411 - Toxic to aquatic life with long lasting effects

H413 - May cause long lasting harmful effects to aquatic life***

Abbreviations, acronyms

ACGIH = American Conference of Governmental Industrial Hygienists

bw = body weight

bw/day = body weight/day

EC x = Effect Concentration associated with x% response

GLP = Good Laboratory Practice

IARC = International Agency for Research of Cancer

Version EUUK



SDS # : 39334

RUBIA TIR 9900 FE 5W-30

Revision Date: 2018-04-23

Version 4.04

LC50 = 50% Lethal concentration - Concentration of a chemical in air or a chemical in water which causes the death of 50% (one half) of a group of test animals

LD50 = 50% Lethal Dose - Chemical amount, given at once, which causes the death of 50% (one half) of a group of test animals

LL = Lethal Loading

NIOSH = National Institute of Occupational Safety and Health

NOAEL = No Observed Adverse Effect Level

NOEC = No Observed Effect Concentration

NOEL = No Observed Effect Level

OECD = Organization for Economic Co-operation and Development

OSHA = Occupational Safety and Health Administration

UVCB = Substance of unknown or Variable composition, Complex reaction products or Biological material

DNEL = Derived No Effect Level

PNEC = Predicted No Effect Concentration

dw = dry weight

fw = fresh water

mw = marine water

or = occasional release

Legend Section 8

TWA: Time Weight Average

STEL: Short Time Exposure Limit

+	Sensitiser	*	Skin designation
**	Hazard Designation	C:	Carcinogen
M:	Mutagen	R:	Toxic to reproduction

Revision Date: 2018-04-23

Revision Note *** Indicates updated section.

This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

This safety data sheet serves to complete but not to replace the technical product sheets. The information contained herein is given in good faith and is accurate to the best of knowledge at the date indicated above. It is understood by the user that any use of the product for purposes other than those for which it was designed entails potential risk. The information given herein in no way dispenses the user from knowing and applying all provisions regulating his activity. The user bears sole liability for the precautions required when using the product. The regulatory texts indicated herein are intended to aid the user to fulfil his obligations. This list is not to be considered complete and exhaustive. It is the user's responsibility to ensure that he is subject to no other obligations than those mentioned.

End of Safety Data Sheet

Version EUUK