

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

SDS #: 33025 **FINAVESTAN A 360 B**

Date of the previous version: 2017-12-19 Revision Date: 2018-01-16 Version 2.06

Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE

COMPANY/UNDERTAKING

1.1. Product identifier

Product name FINAVESTAN A 360 B
REACH Registration Number 01-2119487078-27

REACH Registration Number 01-21194870 Number J93

Substance/mixture Substance

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses White mineral oil, food industry, Cosmetic additive.

1.3. Details of the supplier of the safety data sheet

Supplier A - TOTAL UK LIMITED

183 Eversholt St, Kings Cross

London, NW1 1BU UNITED KINGDOM Tel: +44 (0)20 7339 8000 Fax: +44 (0)20 7339 8033

B - TOTAL LUBRIFIANTS 562 Avenue du Parc de L'ile 92029 Nanterre Cedex

FRANCE

Tél: +33 (0)1 41 35 40 00 Fax: +33 (0)1 41 35 84 71

For further information, please contact:

Contact Point A - HSE

B - HSE

E-mail Address A - rm.gb-msds@total.co.uk

B - rm.msds-lubs@total.com

1.4. Emergency telephone number

Emergency telephone: +44 1235 239670

UK: National Poisons Information Service (NPIS): NHS on 111 or a doctor

Section 2: HAZARDS IDENTIFICATION



FINAVESTAN A 360 B

Revision Date: 2018-01-16 Version 2.06

2.1. Classification of the substance or mixture

REGULATION (EC) No 1272/2008

For the full text of the H-Statements mentioned in this Section, see Section 2.2.

Classification

The product is not classified as dangerous according to Regulation (EC) No. 1272/2008

2.2. Label elements

Labelled according to REGULATION (EC) No 1272/2008

EC-No 232-455-8

Signal word

None

Hazard Statements

None

Precautionary statements

None

2.3. Other hazards

Physical-Chemical Properties Contaminated surfaces will be extremely slippery.

Environmental propertiesThe product may form an oil film on the water surface that may stop the oxygen exchange.

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substance

Additional information

Chemical nature Mineral oil of petroleum origin.

Chemical Name	EC-No	REACH Registration Number	CAS-No	Weight %	Classification (Reg. 1272/2008)
White mineral oil (petroleum)	232-455-8	01-2119487078-27	8042-47-5	100	-

Product containing mineral oil with less than 3% DMSO extract as measured by IP 346.

For the full text of the H-Statements mentioned in this Section, see Section 16.

Section 4: FIRST AID MEASURES

4.1. Description of first aid measures



Revision Date: 2018-01-16 Version 2.06

General advice IN CASE OF SERIOUS OR PERSISTENT CONDITIONS, CALL A DOCTOR OR

EMERGENCY MEDICAL CARE.

Eye contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses and

continue flushing for at least 15 minutes. Keep eye wide open while rinsing.

Skin contact Wash off immediately with soap and plenty of water while removing all contaminated

clothes and shoes. Wash contaminated clothing before reuse.

Inhalation Remove casualty to fresh air and keep at rest in a position comfortable for breathing. If not

breathing, give artificial respiration.

Ingestion Clean mouth with water. Do NOT induce vomiting. Never give anything by mouth to an

unconscious person. Call a physician or poison control centre immediately.

Protection of first-aiders First aider needs to protect himself. See Section 8 for more detail. Do not use

mouth-to-mouth method if victim ingested or inhaled the substance; induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper

respiratory medical device.

4.2. Most important symptoms and effects, both acute and delayed

Eye contact Not classified based on available data.

Skin contact Not classified based on available data.

Inhalation Not classified based on available data. Inhalation of vapours in high concentration may

cause irritation of respiratory system.

Ingestion Not classified based on available data. Ingestion may cause gastrointestinal irritation,

nausea, vomiting and diarrhoea.

4.3. Indication of any immediate medical attention and special treatment needed

Notes to physician Treat symptomatically.

Section 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media Carbon dioxide (CO₂). ABC powder. Foam. Water spray or fog.

Unsuitable Extinguishing Media Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

Special hazard Incomplete combustion and thermolysis may produce gases of varying toxicity such as

carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. These may

be highly dangerous if inhaled in confined spaces or at high concentration.

5.3. Precautions for fire-fighters



FINAVESTAN A 360 B

Revision Date: 2018-01-16 Version 2.06

Special protective equipment for

fire-fighters

Wear self-contained breathing apparatus and protective suit.

Other information Cool containers / tanks with water spray. Fire residues and contaminated fire extinguishing

water must be disposed of in accordance with local regulations.

Section 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

General Information Do not touch or walk through spilled material. Contaminated surfaces will be extremely

slippery. Use personal protective equipment. Ensure adequate ventilation. Remove all

sources of ignition.

6.2. Environmental precautions

General Information Do not allow material to contaminate ground water system. Prevent entry into waterways,

sewers, basements or confined areas. Local authorities should be advised if significant

spillages cannot be contained.

6.3. Methods and material for containment and cleaning up

Methods for containment Dike to collect large liquid spills. If necessary dike the product with dry earth, sand or similar

non-combustible materials.

Methods for cleaning up Dispose of contents/container in accordance with local regulation. In case of soil

contamination, remove contaminated soil for remediation or disposal, in accordance with

local regulations.

6.4. Reference to other sections

Personal protective equipment See Section 8 for more detail.

Waste treatment See section 13.

Section 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Advice on safe handling For personal protection see section 8. Use only in well-ventilated areas. Do not breathe

vapours or spray mist. Avoid contact with skin, eyes and clothing.

Hygiene measures Ensure the application of strict rules of hygiene by the personnel exposed to the risk of

contact with the product. When using, do not eat, drink or smoke. Wash hands before breaks and immediately after handling the product. Provide regular cleaning of equipment, work area and clothing. Do not use abrasives, solvents or fuels. Do not dry hands with rags that have been contaminated with product. Do not put product contaminated rags into

workwear pockets.



Revision Date: 2018-01-16 Version 2.06

7.2. Conditions for safe storage, including any incompatibilities

Technical measures/Storage

conditions

Keep away from food, drink and animal feedingstuffs. Keep in a bunded area. Keep container tightly closed. Preferably keep in the original container. Otherwise, reproduce all the statutory information from the labels onto the new container. Do not remove the hazard labels of the containers (even if they are empty). Design the installations in order to avoid accidental emissions of product (due to seal breakage, for example) onto hot casings or electrical contacts. Store at room temperature. Protect from moisture.

Materials to avoid Strong oxidising agents.

7.3. Specific use(s)

Specific use(s) No information available.

Section 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1. Control parametres

Exposure limits Mineral oil mist:

USA: OSHA (PEL) TWA 5 mg/m3, NIOSH (REL) TWA 5 mg/m3, STEL 10 mg/m3, ACGIH

(TLV) TWA 5 mg/m³ (highly refined)

Legend See section 16

DNEL Worker (Industrial/Professional)

Chemical Name	Short term, systemic effects	Short term, local effects	Long term, systemic effects	Long term, local effects
White mineral oil (petroleum) 8042-47-5			220 mg/kg/8h (dermal) 160 mg/m ³ /8h (aerosol - inhalation)	

DNEL Consumer

Chemical Name	Short term, systemic effects	Short term, local effects	Long term, systemic effects	Long term, local effects
White mineral oil (petroleum) 8042-47-5			92 mg/kg/8h (dermal) 35 mg/m³/8h (aerosol -	
0042-47-5			inhalation) 40 mg/kg/24h (oral)	

8.2. Exposure controls

Occupational Exposure Controls

Engineering measures Apply technical measures to comply with the occupational exposure limits. Ensure

adequate ventilation, especially in confined areas. When working in confined spaces (tanks, containers, etc.), ensure that there is a supply of air suitable for breathing and wear the

recommended equipment.

Personal protective equipment



> **Revision Date: 2018-01-16** Version 2.06

General Information Protective engineering solutions should be implemented and in use before personal

protective equipment is considered. The personal protective equipment (PPE) recommendations apply to the product AS DELIVERED. In case of mixtures or

formulations, it is suggested that you contact the relevant PPE suppliers.

None under normal use conditions. When workers are facing concentrations above the Respiratory protection

exposure limit they must use appropriate certified respirators. Respirator with combination filter for vapour/particulate (EN 14387). Type A/P1. Warning! filters have a limited use duration. The use of breathing apparatus must comply strictly with the manufacturer's

instructions and the regulations governing their choices and uses.

If splashes are likely to occur, wear:. Safety glasses with side-shields. EN 166. Eye protection

Skin and body protection Wear suitable protective clothing. Protective shoes or boots. Long sleeved clothing. Type

4/6.

Hydrocarbon-proof gloves: Fluorinated rubber. Nitrile rubber. In case of prolonged contact Hand protection

with the product, it is recommended to wear gloves complying with EN 420 and EN 374 standards, protecting at least for 480 minutes and having a thickness of 0,38 mm at least. These values are indicative only. The level of protection is provided by the material of the glove, its technical characteristics, its resistance to the chemicals to be handled, the appropriateness of its use and its replacement frequency. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is

used, such as the danger of cuts, abrasion, and the contact time.

Environmental exposure controls

General Information The product should not be allowed to enter drains, water courses or the soil.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Clear **Appearance** Colour colourless Physical state @20°C liquid characteristic Odour

Odour Threshold No information available

Property Values Remarks Method

Not applicable Melting point/range

No information available

Boiling point/boiling range No information available

ASTM D 92 > 240 °C Flash point > 464 °F ASTM D 92

No information available **Evapouration rate**



> **Revision Date: 2018-01-16** Version 2.06

> > ISO 3104

Flammability Limits in Air

No information available Upper Lower No information available No information available Vapour pressure Vapour density No information available

0.870 @ 15 °C Relative density @ 15 °C 870 kg/m³ Density Insoluble Water solubility

No information available Solubility in other solvents logPow No information available

Autoignition temperature > 250 °C

> 482 °F

Decomposition temperature

No information available Viscosity, kinematic 68 mm2/s @ 40 °C

Explosive properties Not explosive **Oxidising properties** Not applicable

Possibility of hazardous reactions None under normal processing

9.2. Other information

Freezing point No information available

Section 10: STABILITY AND REACTIVITY

10.1. Reactivity

General Information None under normal processing.

10.2. Chemical stability

Stability Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid

Conditions to avoid Keep away from open flames, hot surfaces and sources of ignition. Keep away from heat

and sparks.

10.5. Incompatible materials

Materials to avoid Strong oxidising agents.

10.6. Hazardous Decomposition Products

Hazardous Decomposition Products Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. Other



FINAVESTAN A 360 B

Revision Date: 2018-01-16 Version 2.06

decomposition products.

Section 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Acute toxicity Local effects Product Information

Skin contact . Not classified based on available data.

Eye contact . Not classified based on available data.

Inhalation . Not classified based on available data. Inhalation of vapours in high concentration may

cause irritation of respiratory system.

Ingestion . Not classified based on available data. Ingestion may cause gastrointestinal irritation,

nausea, vomiting and diarrhoea.

Acute toxicity - Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
White mineral oil (petroleum)	LD50 > 5000 mg/kg bw (rat)	LD50 > 2000 mg/kg bw (rabbit)	LC50 (4h) > 5000 mg/m ³ air
			(aerosol) (rat)

Sensitisation

Sensitisation Not classified based on available data.

Specific effects

CarcinogenicityNot classified based on available data.MutagenicityNot classified based on available data.Germ cell mutagenicityNot classified based on available data.

Reproductive toxicity Not classified based on available data.

Repeated dose toxicity

Target Organ Effects (STOT)

Specific target organ systemic toxicity (single exposure)

Not classified based on available data.

Specific target organ toxicity - repeated exposure

Not classified based on available data.

Aspiration toxicity Not classified based on available data.

Other information

Other adverse effects Characteristic skin lesions (oil blisters) may develop following prolonged and repeated

exposures (contact with contaminated clothing).



FINAVESTAN A 360 B

Revision Date: 2018-01-16 Version 2.06

Section 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Not classified based on available data.

Acute aquatic toxicity - Product Information

No information available.

Acute aquatic toxicity - Component Information

Chemical Name	Toxicity to algae	Toxicity to daphnia and other aquatic invertebrates.	Toxicity to fish	Toxicity to microorganisms
White mineral oil (petroleum)	EL50 (48h) > 100 mg	EL50 (48h) > 100 mg/l	LL50 (96h) > 100 mg/l	
8042-47-5	(Pseudokirchnerella	(Daphnia magna - OECD	(Oncorhynchus mykiss -	
	subcapitata - OECD 201)	202)	OECD 203)	

Chronic aquatic toxicity - Product Information

No information available.

Chronic aquatic toxicity - Component Information

Chemical Name	Toxicity to algae	Toxicity to daphnia and other aquatic invertebrates.	Toxicity to fish	Toxicity to microorganisms
White mineral oil (petroleum)		NOEL (21d) 10 mg/l	NOEL (14/21d) > 1000 mg/l	
8042-47-5		(Daphnia magna - OECD	(Oncorhynchus mykiss -	
		211)	QSAR Petrotox)	

Effects on terrestrial organisms

No information available.

12.2. Persistence and Degradability

General Information

No information available.

12.3. Bioaccumulative potential

Product Information No information available.

logPowNo information availableComponent InformationNo information available.

Chemical Name	log Pow
White mineral oil (petroleum) - 8042-47-5	ē

12.4. Mobility in soil



Revision Date: 2018-01-16 Version 2.06

Soil Given its physical and chemical characteristics, the product generally shows low soil

mobility.

Air Loss by evaporation is limited.

Water The product is insoluble and floats on water.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessmentNo information available.

12.6. Other adverse effects

General Information No information available.

Section 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from residues / unused

products

Should not be released into the environment. Do not empty into drains. Dispose of in accordance with the European Directives on waste and hazardous waste. Where possible recycling is preferred to disposal or incineration. After use, this oil must be sent to a licensed waste oil facility. Incorrect disposal of used oil poses a risk to the environment. Mixture with other waste types such as solvents, brake- and cooling liquids is forbidden.

Contaminated packageing Empty containers should be taken to an approved waste handling site for recycling or

disposal.

EWC Waste Disposal NoAccording to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user based on the application

for which the product was used. The following Waste Codes are only suggestions:. 13 02

05.

Other information Refer to section 8 for safety and protective measures for disposal personnel.

Section 14: TRANSPORT INFORMATION

ADR/RID not regulated

IMDG/IMO not regulated

ICAO/IATA not regulated

ADN not regulated

Section 15: REGULATORY INFORMATION



FINAVESTAN A 360 B

Revision Date: 2018-01-16 Version 2.06

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

International Inventories Australia (AICS)

China (IECSC)
Japan (ENCS)
Korea (KECL)
New Zealand (NZIoC)
Philippines (PICCS)***

Further information

No information available

15.2. Chemical Safety Assessment

Chemical Safety Assessment No information available

15.3. National regulatory information

The United Kingdom

• Avoid exceeding occupational exposure limits (see section 8).

<u>Ireland</u>

• Avoid exceeding occupational exposure limits (see section 8).

Section 16: OTHER INFORMATION

Abbreviations, acronyms

ACGIH = American Conference of Governmental Industrial Hygienists

bw = body weight

bw/day = body weight/day

EC x = Effect Concentration associated with x% response

GLP = Good Laboratory Practice

IARC = International Agency for Research of Cancer

LC50 = 50% Lethal concentration - Concentration of a chemical in air or a chemical in water which causes the death of 50% (one half) of a group of test animals

LD50 = 50% Lethal Dose - Chemical amount, given at once, which causes the death of 50% (one half) of a group of test animals LL = Lethal Loading

NIOSH = National Institute of Occupational Safety and Health

NOAEL = No Observed Adverse Effect Level

NOEC = No Observed Effect Concentration

NOEL = No Observed Effect Level

OECD = Organization for Economic Co-operation and Development



Revision Date: 2018-01-16 Version 2.06

OSHA = Occupational Safety and Health Administration

UVCB = Substance of unknown or Variable composition, Complex reaction products or Biological material

DNEL = Derived No Effect Level

PNEC = Predicted No Effect Concentration

dw = dry weight fw = fresh water mw = marine water or = occasional release

Legend Section 8

TWA: Time Weight Average STEL: Short Time Exposure Limit

M: Mutagen R: Toxic to reproduction

Revision Date: 2018-01-16

Revision Note *** Indicates updated section.

This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

This safety data sheet serves to complete but not to replace the technical product sheets. The information contained herein is given in good faith and is accurate to the best of knowledge at the date indicated above. It is understood by the user that any use of the product for purposes other than those for which it was designed entails potential risk. The information given herein in no way dispenses the user from knowing and applying all provisions regulating his activity. The user bears sole liability for the precautions required when using the product. The regulatory texts indicated herein are intended to aid the user to fulfil his obligations. This list is not to be considered complete and exhaustive. It is the user's responsibility to ensure that he is subject to no other obligations than those mentioned.

End of Safety Data Sheet