



Seamax Extra Range

Monograde diesel engine oil

Description

Seamax Extra 30 and 40 is a new range of 15 BN engine oils specifically developed for the arduous conditions of use experienced in today's fishing industry.

This range of high performance lubricants has been formulated using the highest quality base oils and a unique balance of additives to offer both economic and operational benefits.

Application

Seamax Extra is suitable for use in modern highly rated four-stroke engines operating on marine distillate fuels.

Features / Benefits

The diesel engine performance of the Seamax Extra range exceeds the API CF specification, offering enhanced detergency, excellent thermal and oxidative stability and enhanced performance at high temperatures. The range also exhibits high load carrying capabilities and superior gear performance, which enables it to be used as a common oil for both engine and transmission systems.

The superior performance of Seamax Extra leads to reduced cost of use through:

- reduced maintenance and wear.
- excellent engine cleanliness
- extended time between overhauls.
- cleaner piston ring belts.
- improved resistance to liner lacquering.

Technical Data

| Name | Method | Units | Seamax Extra 30 | Seamax Extra 40 |
|--|------------|--------------------|-----------------|-----------------|
| SAE Grade | | | 30 | 40 |
| Density @ 15°C, Relative | ASTM D1298 | g/ml | 0.890 | 0.895 |
| Viscosity, Kinematic @ 100°C | ASTM D445 | mm ² /s | 11.5 | 13.5 |
| Total Base Number, TBN | ASTM D2896 | mg KOH/g | 15.0 | 15.0 |
| Closed Flash Point | ASTM D93 | °C | >200 | >200 |
| Pour Point | ASTM D5985 | °C | -15 | -15 |
| Typical Load Carrying Capacity FZG Gear Test (A/8.3/90), FLS | DIN 51354 | - | 12 | 12 |

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

Packaging and Storage

Supplied in bulk and drums of approximately 210 litres. Ensure drums are tightly re-sealed after use.

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and the obliteration of drum markings.

Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Seamax Extra Range

08 May 2012

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Marine, Technology Centre, Whitchurch Hill, Pangbourne, Reading RG8 7QR, United Kingdom

www.castrolmarine.com