

Product Data

Seamax Standard 40

Monograde diesel engine oil

Description

Seamax Standard 40 is a monograde diesel engine oil specifically developed for the use in today's fishing industry.

Application

Seamax Standard 40 accomodates typical operating conditions found in many medium speed trunk-piston marine diesel

engine designs when running on distillate fuels. Seamax Standard 40 is suitable for use in engines where API CF-4 type performance is recommended.

Typical Characteristics

Name	Method	Units	Seamax Standard 40
Density @ 15C, Relative	ASTM D4052	g/ml	0.896
Viscosity, Kinematic 100C	ASTM D445	mm²/s	14.5
Total Base Number, TBN	ASTM D2896	mg KOH/g	9.5
Viscosity, Kinematic 40C	ASTM D445	mm²/s	145

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Seamax Standard 40 16 Jun 2017

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Marine, Technology Centre, Whitchurch Hill, Pangbourne, Reading RG8 7QR, United Kingdom

www.castrol.com/marine