



Product Data

Rustilo™ 181

Solvent based corrosion preventive

Description

Castrol Rustilo™ 181 is a dark brown solvent deposited corrosion preventive fluid which, after evaporation of the solvent, gives a hard waxy yet flexible film.

Application

Rustilo 181 is a long term protective for use in severe conditions where a high degree of protection is required. It is ideal for protection of to certain engine spares such as fuel injector nozzles, fin tubes and similar highly finished parts prior to long-term storage or transportation.

Rustilo 181 used to be applied by immersion, brush or spray.

Advantages

- Contains a powerful corrosion inhibitor package suitable for severe conditions - provides reliable protection of components
- Good mechanical film strength and finger print suppressing properties - highly finished work not damaged by hand improves product quality
- Long bath-lifetimes possible - increases changing intervals and hence reduces operational cost
- Easy to apply and short drying time - enables high level of productivity
- Free from heavy metals, such as Barium - improves environmental profile and helps reducing waste disposal cost
- If required protective films of Rustilo 181 can be removed by using a petroleum solvent or alkaline process cleaner, available from Castrol

Typical Characteristics

Description	Test Method	Unit	Value
Appearance	Visual	-	amber fluid
Density @ 15 °C	DIN 51 757	g/ml	0.86
Flash Point	DIN 51 755	°C	40
Viscosity @ 20 °C	DIN 51 562	mm ² /s	65
Film Type	Visual	-	Hard, waxy
Film Thickness	In-house	µm	20 - 40
Consumption	In-house	kg/100 m ²	7 - 10
Corrosion Protection	(*) Indoor Storage	Years	Up to 8 - 10
	(**) Outdoor Storage	Month	12 - 24
Drying time	-	min	105

Subject to usual manufacturing tolerances.

Additional Information

The claims on film thickness and consumption are average values. These are valid for smooth surfaces with good drain-off characteristics and simple geometries without holes or recesses.

Average drying time is the time until the majority of the solvent is evaporated at ambient temperature and a relative humidity of 60 – 70%. The full corrosion protection will just be provided when the solvent is completely evaporated.

(*) "Indoor storage" describes the storage of ferrous components in closed store-rooms having a relative humidity of 60%. Increased protection times could be achieved when treating finished surfaces or store the parts in a sealed pack.

(**) "Outdoor storage" describes open storage, which assumes primary protection from the elements by tarpaulin or other form of cover.

Storage

To avoid product deterioration always keep the container/drum tightly sealed. Store the product in a cool, dry place away from direct sunlight. Prevent exposure to frost and avoid water ingress. For optimum product stability, it is preferable to store the product indoors between 5°C and 30 °C / 41°F and 86°F.

Product must be used in a liquid form. Influence of temperature may cause some cloudiness, which is reversible and does not have an impact on product quality or corrosion protection performance in most instances.

For more details, please refer the product safety data sheet.

Rustilo™ 181

05 Aug 2015

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Australia Level 8 (QV1 Building), 250 St. Georges Terrace, Perth WA 6000, Australia. Customer Service Number +61 (0)8 9420 1825

Dubai City Tower 2, 6th Floor PO BOX 1699, Sheikh Zayed Road, Dubai, U.A.E. Customer Service Number +971 4 3079304

Norway Drammensveien 167, Box 153 Skoyen, 0212 Oslo, Norway. Customer Service Number +47 22 51 12 43 501

Singapore Keppel Bay Towers, 1 Harbourfront Avenue 02-01, Singapore 098632, Singapore. Customer Service Number +65 6371 8478

United Kingdom BlueSky Business Space, Westpoint House, Pavilion 2 Prospect Park, Prospect Road, Arnhall Business Park, Westhill. AB32 6FJ, UK.
Customer Service Number +44 (0)1224 270365

USA 501 Westlake Park Boulevard, Houston, Texas 77079, USA. Customer Service Number +1 800 339-7157., Brazil Avenida Itaoca, 2.400, Inhauma, Rio de Janeiro, Zip code 21061-020, customer service +55 11 4133 7835

www.castrol.com/globalbusiness