

Wetland Functional Design Report

North Sale – Area C South

Wellington Shire Council

January 2018





Document Status

Version	Doc type	Reviewed by	Approved by	Date issued
01	Report	ADV	CBD	13/10/2017
02	Report	TJC	TJC	23/01/2018

Project Details

Project Name	North Sale – Area C South
Client	Wellington Shire Council
Client Project Manager	Sam Pye
Water Technology Project Manager	Simon Hof
Water Technology Project Director	Luke Cunningham
Authors	Thomas Cousland
Document Number	4267-01_R03v01c_Area_C_SouthFD_report.docx



COPYRIGHT

Water Technology Pty Ltd has produced this document in accordance with instructions from Wellington Shire Council for their use only. The concepts and information contained in this document are the copyright of Water Technology Pty Ltd. Use or copying of this document in whole or in part without written permission of Water Technology Pty Ltd constitutes an infringement of copyright.

Water Technology Pty Ltd does not warrant this document is definitive nor free from error and does not accept liability for any loss caused, or arising from, reliance upon the information provided herein.

154 Macleod Street
 Bairnsdale VIC 3875
 Telephone (03) 5152 5833
 ACN 093 377 283
 ABN 60 093 377 283



4267-01_R03v01c_Area_C_SouthFD_report.docx



CONTENTS

1	INTRODUCTION	4
1.1	Design Flow Rates	4
1.2	Site Constraints	4
2	SEDIMENT BASIN	5
3	WETLAND MACROPHYTE ZONE	6
4	DRAINAGE RESERVE	8
4.1	Edge Treatments	8
4.2	Retarding Basin	9
4.2.1	Outlet Details	9
4.2.2	Storage Volume	9
4.3	Sediment Basin Sizing	12
4.4	Sediment Basin Outlet	12
4.5	Wetland Outlet	13
4.6	RB Outlet	14

APPENDICES

- Appendix A Design Calculations
- Appendix B Area C South Functional Design Plans
- Appendix C Area C South Cost Estimates

LIST OF FIGURES

Figure 3-1	Macrophyte Zone Inundation Frequency Curve	6
Figure 3-2	Macrophyte Zone Water Balance	7
Figure 4-1	Typical Edge Treatment for Sediment Basin and Wetland Macrophyte Zone	8

LIST OF TABLES

Table 1-1	Design Flow Rates	4
Table 3-1	Macrophyte Zonation Details	6
Table 4-1	Retarding Basin Height-Storage Details	9
Table 5-1	Cost Estimates Area C South	10



1 INTRODUCTION

The Area C South Wetland/Retarding Basin forms part of the North Sale Drainage Investigation located at the north- western corner of the intersection of Maffra-Sale Road and the Gippsland Railway Line.

Calculations used in the functional design are included in Appendix A.

1.1 Design Flow Rates

The design flow rates used in the design of the North Sale Area C South are shown in Table 1-1

Table 1-1 Design Flow Rates

Storm Event	Flow Rate (m ³ /s)
3 month ARI inflow	0.15
1 year ARI Inflow	0.80
100 year AR Inflow	4.75
Target 100 year ARI outflow from retarding basin	0.92

1.2 Site Constraints

Several river red gums are located within drainage reserve which have been largely avoided by the wetland design. The existing trees are still located within the retarding basin below the 100 year ARI flood level, however the infrequent inundation of the river red gums has been investigated as part of the design process with no impact on the health of the trees expected.



2 SEDIMENT BASIN

Sediment basins have been sized by the Fair and Geyer formula (Equation 10.3 in WSUD Engineering Procedures, 2004) to determine minimum surface area required to ensure the settling velocity criteria for sediments was satisfied. The 1 year AR flow rate of 0.76 m³/s was used to determine the required basin, which was sized to a cleanout frequency of 5 years or longer. It was found that the settling criteria was the critical factor in sizing of the sediment basins, not sediment storage volume.

An Extended Detention Depth of 350 mm has been incorporated into the sediment basin.

A 375 mm diameter pipe has been sized to convey the 3 month ARI flow from the sediment basin to the wetland macrophyte zone. The sediment basin outlet pit has been sized large enough to ensure that the pipe outlet forms the hydraulic control.

The 100 year velocity in the sediment basin has been calculated as 0.30 m/s based on the cross sectional area between NWL and the 10 year level in the basin. This 100 year velocity is within the requirement of 0.5 m/s to prevent re-suspension of deposited sediment during a major storm event.

The cleanout frequency of the sediment basin was determined to equal once every 5.9 years, with the cleanout volume determined to be 337 m³, with a sediment drying area located north of the sediment basin within the drainage reserve.



3 WETLAND MACROPHYTE ZONE

Table 3-1 shows a summary of the macrophyte zonation areas within the Area C North wetland.

An Extended Detention Depth of 350 mm has been incorporated into the macrophyte zone. The maximum 3 month velocities within the macrophyte zone has been calculated to equal 0.01 m/s which is less than the 3 month velocity criteria of <0.05 m/s which is the threshold to prevent biofilm from being stripped within the marsh areas.

Table 3-1 Macrophyte Zonation Details

	Macrophyte Zone (m ²)	Percentage of Macrophyte Zone
Open Water	1,093	19%
Submerged Marsh	239	4%
Deep Marsh	3,516	61%
Shallow Marsh	896	16%
TOTAL	5,744	100%

A 125 mm weir has been sized as the wetland outlets to control Extended Detention Depths within the macrophyte zones. The residence time of the wetland has been calculated to equal 3 days (for the 90th percentile of events), which represents the time taken for a particle of water to travel through the wetland system for all storm events. The wetland Inundation Frequency Curve is shown below in Figure 3-1 which shows the expected distribution of expected water levels within the macrophyte zone. A water balance analysis for the wetland system has been extracted from the MUSIC model (10 years of rainfall data) and is shown in Figure 3-2. The water balance modelling further illustrates that water levels within the wetland will be sit within an acceptable range at or near NWL for the vast majority of events.




Figure 3-1 Macrophyte Zone Inundation Frequency Curve

4267-01_R03v01c_Area_C_SouthFD_report.docx




Figure 3-2 Macrophyte Zone Water Balance

4267-01_R03v01c_Area_C_SouthFD_report.docx



4 DRAINAGE RESERVE

4.1 Edge Treatments

A 1 in 8 safety bench has been incorporated into the bathymetry below NWL to a depth of 350 mm. Minimum batter slopes of 1 in 6 are incorporated above NWL with the typical edge treatment shown in Figure 4-1 which are applicable for both the sediment basin and macrophyte zone.




Figure 4-1 Typical Edge Treatment for Sediment Basin and Wetland Macrophyte Zone



4.2 Retarding Basin

4.2.1 Outlet Details

Twin 600 mm diameter pipelines have been sized to control flows leaving the retarding basin to desired flow rates. The outlet pit has been sized large enough to ensure that the twin 600 mm pipes form the hydraulic control for the system. An outlet weir at the 100 year ARI level has been sized to convey the total design outflow should blockage occur within the outlet structures.

4.2.2 Storage Volume

Table 4-1 shows the Height Storage relationship for the Area C South Retarding Basin.

Table 4-1 Retarding Basin Height-Storage Details

Height (m AHD)	Storage (m ³)	Outflow (m ³ /s)
9.5	0	0
9.6	1	0.01
9.7	2	0.02
9.8	965	0.03
9.9	2,179	0.06
10	3,625	0.1
10.1	5,420	0.8
10.2	7,510	1.05
10.3	9,902	1.37
10.4	12,470	1.85
10.5	15,397	2.39
10.6	18,672	3.1
10.7	22,030	3.83
10.8	25,394	4.62



5 COSTINGS

5.1 Cost Overview

Detailed cost estimates have been provided to Water Technology by Crossco Consulting. As per Council specification these estimates include a cut and fill rate of \$10.00 / m³ and a contingency of 20%. An overview of these costs can be seen below in table 5.1. A detailed breakdown of cost estimates is included in Appendix C.

Table 5-1 Cost Estimates Area C South

	Total (ex GST)	Incl 20% contingency (ex GST)	Incl GST	TOTAL (incl GST and contingency)
Totals	\$ 496,669	\$ 596,003	\$ 59,600	\$ 655,604
Total Including 20% Contingency and GST				\$ 655,604



APPENDIX A DESIGN CALCULATIONS





5.2 Sediment Basin Sizing

$V_s =$	0.011 m/s	Catchment Area =	33.8 ha
$d_e =$	0.35 m	Sediment load =	1.6 m ³ /ha/yr
$d_p =$	1.0 m	Gross Pollutant Load =	0.4 m ³ /ha/yr (Alison et al 1998)
$d^* =$	1.0 m	Actual basin depth =	1.0 m
$(d_e+d_p) =$	1.0	Actual Basin area =	800.0 m ²
(d_e+d^*)		Basin sediment accumulation fraction	0.17 per year
$Q =$	0.76 m ³ /s	Clean out every	5.9 years
$A =$	800 m ²		
$V_s =$	11.58		
Q/A			
$\lambda =$	0.26		
$n =$	1.35		
Fraction of Initial Solids Removed			
$R =$	95%		

5.3 Sediment Basin Outlet

Ignore the pit?? Yes/No					Are you Assuming INLET CONTROL???					No		
PIT					PIPE		INLET CONTROL		OUTLET CONTROL			
Pit Sill Level				9.7 m AHD	Invert Level				8.5 m AHD	Ke		0.5 Square edge
Width				0.6 m	Dia				0.375 m	Kex		1.0
Length				0.6 m	barrels				1	Length		22.0 m
Area				0.36 m ²	Area				0.110446617 m ²	Tailwater Level		9.7 m AHD
Grill blockage factor				50 %						wetted perim		1.18 m
weir blockage				0 %						Hyd Radius		0.09 m
Height	Head	Orifice Flow	Weir Flow	total flow into pit	Head	Orifice Flow		head loss	flow	TOTAL FLOW RATE		
9.7	0	0.000	0.000	0.000	1.013	0.325		0.000	0.000	0.000	m ³ /s	
9.75	0.05	0.118	0.046	0.046	1.063	0.333		0.050	0.061	0.046	m ³ /s	
9.8	0.1	0.166	0.129	0.129	1.113	0.341		0.100	0.086	0.086	m ³ /s	
9.85	0.15	0.204	0.237	0.204	1.163	0.348		0.150	0.106	0.106	m ³ /s	
9.9	0.2	0.235	0.365	0.235	1.213	0.356		0.200	0.122	0.122	m ³ /s	
9.95	0.25	0.263	0.510	0.263	1.263	0.363		0.250	0.136	0.136	m ³ /s	
10	0.3	0.288	0.670	0.288	1.313	0.370		0.300	0.149	0.149	m ³ /s	
10.05	0.35	0.311	0.845	0.311	1.363	0.377		0.350	0.161	0.161	m ³ /s	

Broad Crested Weir		SED BASIN WEIR	
Formula	$Q = CbH^{3/2}$		
Inputs	C	1.60	Weir Coefficient (1.4-2.1, typically 1.6)
	b	3.00 m	Breadth of Weir
	H	0.300 m	Head Of Water Above Crest
Output	Q	0.79	m ³ /s

4267-01_R03v01c_Area_C_SouthFD_report.docx



5.4 Wetland Outlet

Wetland EDD	0.35 m	Starting Water Depth	Detention Time
Wetland Area at TED	8299 m ²	100mm	40 hrs
Wetland Area at NWL	6930 m ²	200mm	44 hrs
Volume at EDD	2665.075 m ³	300mm	48 hrs
		400mm	49 hrs
		500mm	51 hrs
		Average Detention Depth	46.4 hrs

Orifice configuration
Weir Coefficient **1.7**

Depth (m)	Weir Width (mm)
1 0	125
2 0.2	0
3 0.3	0

Assumed fully drained volume **133.25375**

Height	Weir 1	Weir 2	Weir 3	TOTAL FLOW
0	0	0	0	0.000 m ³ /s
0.1	0.019843	0	0	0.020 m ³ /s
0.2	0.056126	0	0	0.056 m ³ /s
0.3	0.10311	0	0	0.103 m ³ /s
0.4	0.158748	0	0	0.159 m ³ /s
0.5	0.221857	0	0	0.222 m ³ /s
0.6	0.291638	0	0	0.292 m ³ /s
0.7	0.367506	0	0	0.368 m ³ /s
0.8	0.449006	0	0	0.449 m ³ /s

Orifice Equation WETLAND OUTLET C_d recommended by Tony Wong for design of Wetland Drains 0.67
 $Q = C_d A (2gH)^{1/2}$ C_d recommended by Keith Boniface 0.61-0.66, 0.61 for 0 velocity

Inputs	C_d	0.62	Coefficient of Discharge
	A	0.16 m ²	Cross Sectional Area
	H	0.350 m	Head above centreline of Orifice
			Pipe Dia (m) Area (m ²)
			0.45 0.16
Output	Q	0.26 m ³ /s	

4267-01_R03v01c_Area_C_SouthFD_report.docx



5.5 RB Outlet

Ignore the pit?? Yes/No				Are you Assuming INLET CONTROL???				Are you Assuming INLET CONTROL???			
No				No				No			
PIT				PIPE				OUTLET CONTROL			
Pit Sill Level				Invert Level				Ke			
10.05 m AHD				9.5 m AHD				0.5 Square edge			
Width				Dia				Kex			
2.4 m				0.6 m				1.0			
Length				barrels				Length			
2.4 m				2				140.0 m			
Area				Area				Tailwater Level			
5.76 m ²				0.565486678 m ²				9.1 m AHD			
Grill blockage factor								wetted perim			
0 %								1.88 m			
								Hyd Radius			
								0.30 m			
Height	Head	Orifice Flow	Weir Flow	total flow into pit	Head	Orifice Flow	head loss	flow	TOTAL FLOW RATE (wetland connection NOT included)		
9.5	-0.55	0.000	0.000	0.000	-0.300	0.000	0.400	0.811	0.00 m ³ /s		
9.6	-0.45	0.000	0.000	0.000	-0.200	0.000	0.500	0.907	0.00 m ³ /s		
9.7	-0.35	0.000	0.000	0.000	-0.100	0.000	0.600	0.994	0.00 m ³ /s		
9.8	-0.25	0.000	0.000	0.000	0.000	0.000	0.700	1.073	0.00 m ³ /s		
9.9	-0.15	0.000	0.000	0.000	0.100	0.523	0.800	1.148	0.00 m ³ /s		
10	-0.05	0.000	0.000	0.000	0.200	0.739	0.900	1.217	0.00 m ³ /s		
10.1	0.05	3.765	0.193	0.193	0.300	0.802	1.000	1.283	0.80 m ³ /s		
10.2	0.15	6.522	1.004	1.004	0.400	1.046	1.100	1.346	1.00 m ³ /s		
10.3	0.25	8.419	2.160	2.160	0.500	1.169	1.200	1.405	1.17 m ³ /s		
10.4	0.35	9.962	3.578	3.578	0.600	1.281	1.300	1.463	1.28 m ³ /s		
10.5	0.45	11.296	5.216	5.216	0.700	1.383	1.400	1.518	1.38 m ³ /s		
10.6	0.55	12.488	7.048	7.048	0.800	1.479	1.500	1.571	1.48 m ³ /s		
10.7	0.65	13.576	9.056	9.056	0.900	1.568	1.600	1.623	1.57 m ³ /s		
10.8	0.75	14.583	10.600	10.600	1.000	1.653	1.700	1.673	1.65 m ³ /s		
10.9	0.85	15.525	12.789	12.789	1.100	1.734	1.800	1.721	1.72 m ³ /s		
11	0.95	16.413	15.111	15.111	1.200	1.811	1.900	1.768	1.77 m ³ /s		


Broad Crested Weir		RB WEIR	
Formula	$Q = CbH^{3/2}$		
Inputs			
C	1.60	Weir Coefficient (1.4-2.1, typically 1.6)	
b	4.00 m	Breadth of Weir	
H	0.300 m	Head Of Water Above Crest	
Output			
Q	1.05	m ³ /s	



APPENDIX B

AREA C SOUTH FUNCTIONAL DESIGN PLANS





NOT FOR CONSTRUCTION

REVISIONS			
REV.	DESCRIPTION	DATE	INIT.
V01	ISSUED FOR COMMENT	2/02/2017	TJC

CLIENT:
WELLINGTON SHIRE COUNCIL



WELLINGTON
SHIRE COUNCIL

CONSULTANT:
Water Technology Pty Ltd
ABN: 60 093 377 283
Melbourne T +61 3 8526 0800



WATER TECHNOLOGY
WATER, COASTAL & ENVIRONMENTAL CONSULTANTS

Water Technology Pty Ltd

DRAWN	RJD
CHECKED	TJC
DESIGN	RJD
CHECKED	TJC
APPROVED	SMH




NORTH SALE AREA C SOUTH WETLAND
FUNCTIONAL DESIGN
PLAN VIEW

JOB NO. J4276-01
SHEET 1 of 5

Drawing No. 4276-01_D02V01_001 SCALE: 1:1250
Rev No. V01

A3



LONG SECTION A-A
HORIZONTAL SCALE 1:1250 VERTICAL SCALE 1:50

NOT FOR CONSTRUCTION

REVISIONS			
REV.	DESCRIPTION	DATE	INIT.
V01	ISSUED FOR COMMENT	2/02/2017	TJC

CLIENT:
WELLINGTON SHIRE COUNCIL



CONSULTANT:
Water Technology Pty Ltd
ABN: 60 093 377 283
Melbourne T +61 3 8526 0800




DRAWN RJD
CHECKED TJC
DESIGN RJD
CHECKED TJC
APPROVED SMH


NORTH SALE AREA C SOUTH WETLAND
FUNCTIONAL DESIGN
LONG SECTION
JOB NO. J4276-01
SHEET 2 of 5

Drawing No. 4276-01_D02V01_001
Rev No. V01


SCALE: AS NOTED




CROSS SECTION D-D
HORIZONTAL SCALE 1:1000 VERTICAL SCALE 1:250



CROSS SECTION C-C
HORIZONTAL SCALE 1:1000 VERTICAL SCALE 1:250



CROSS SECTION B-B
HORIZONTAL SCALE 1:1000 VERTICAL SCALE 1:250



CROSS SECTION A-A
HORIZONTAL SCALE 1:1000 VERTICAL SCALE 1:250

NOT FOR CONSTRUCTION

REVISIONS			
REV.	DESCRIPTION	DATE	INIT.
V01	ISSUED FOR COMMENT	2/02/2017	TJC

CLIENT:
WELLINGTON SHIRE COUNCIL



WELLINGTON SHIRE COUNCIL

CONSULTANT:
Water Technology Pty Ltd
ABN: 60 093 377 283
Melbourne T +61 3 8526 0800



WATER TECHNOLOGY
WATER, COASTAL & ENVIRONMENTAL CONSULTANTS


DRAWN	RJD
CHECKED	TJC
DESIGN	RJD
CHECKED	TJC
APPROVED	SMH

NORTH SALE AREA C SOUTH WETLAND
FUNCTIONAL DESIGN
CROSS SECTIONS
JOB NO. J4276-01
SHEET 3 of 5

Drawing No. 4276-01_D02V01_001
Rev No. V01


SCALE: AS NOTED

A3



TWIN CHAMBER OUTFALL / HIGH FLOW BYPASS PIT - REFER MWC 7251/12/4009

RETARDING BASIN SPILLWAY



WETLAND CROSS SECTION

NOT TO SCALE

NOT FOR CONSTRUCTION

REVISIONS			
REV.	DESCRIPTION	DATE	INIT.
V01	ISSUED FOR COMMENT	2/02/2017	TJC

CLIENT:
WELLINGTON SHIRE COUNCIL



CONSULTANT:
Water Technology Pty Ltd
ABN: 60 093 377 283
Melbourne T +61 3 8526 0800



DRAWN RJD
CHECKED TJC
DESIGN RJD
CHECKED TJC
APPROVED SMH








© Water Technology Pty Ltd

NORTH SALE AREA C NORTH WETLAND
FUNCTIONAL DESIGN
DETAIL 1

JOB NO. J4276-01
SHEET 4 of 5

Drawing No. 4276-01_D02V01_001
Rev No. V01

SCALE: NOT TO SCALE



NOT FOR CONSTRUCTION

REVISIONS			
REV.	DESCRIPTION	DATE	INIT.
V01	ISSUED FOR COMMENT	2/02/2017	TJC

CLIENT:
WELLINGTON SHIRE COUNCIL

WELLINGTON
SHIRE COUNCIL

CONSULTANT:
Water Technology Pty Ltd
ABN: 60 093 377 283
Melbourne T +61 3 8526 0800

WATER TECHNOLOGY
WATER, COASTAL & ENVIRONMENTAL CONSULTANTS

DRAWN	RJD
CHECKED	TJC
DESIGN	RJD
CHECKED	TJC
APPROVED	SMH

NORTH SALE AREA C NORTH WETLAND
FUNCTIONAL DESIGN
DETAIL 2
JOB NO. J4276-01
SHEET 5 of 5

Drawing No. 4276-01_D02V01_001
Rev No. V01

SCALE: NOT TO SCALE

A3



APPENDIX C AREA C SOUTH COST ESTIMATES





North Sale - Area C South Wetland									
Item	Qty	Unit	Rate	Total (ex GST)	Incl 20% contingency (ex GST)	GST	TOTAL (incl GST and contingency)	Comments	
Establishment, contractor management and supervision									
Removal of vegetation	1	Item	3,000.00	3,000	3,600	360	3,960		
Earthworks									
Strip site (say 200mm depth)	22,425	sq.m	1.30	29,153	34,983	3,498	38,481	assumed all topsoil is stockpiled for reuse	
Excavate to line and level	8,335	cu.m	10.00	83,348	100,018	10,002	110,019	excavate 300 below finished and below NTWL to allow for clay and topsoil and 200 below finished and above NTWL to allow for topsoil	
Fill and compact to design levels	2,993	cu.m	20.00	59,860	71,832	7,183	79,015		
Construct Clay liner (300mm depth to NTWL)	2,096	cu.m	8.00	16,766	20,120	2,012	22,132	See provisional item if treatment required	
Place topsoil won from s'pile (200mm depth)	21,674	sq.m	2.20	47,683	57,219	5,722	62,941	assumed material won from site; excludes area 500mm below NTWL in SB	
Dispose of excess material from site	3,396	cu.m	15.00	50,943	61,132	6,113	67,245	allowance for approx. 1hr of travel and dozer time to spread	
Associated drainage infrastructure									
225mm dia RCP	95	lm	130.00	12,350	14,820	1,482	16,302		
375mm dia RCP	25	lm	180.00	4,500	5,400	540	5,940		
450mm dia RCP	12	lm	250.00	3,000	3,600	360	3,960		
600mm dia RCP	175	lm	320.00	56,000	67,200	6,720	73,920		
900x900 Sed Basin Transfer Pit with pipe grille	1	#	-	-	-	-	-		
Endwall to suit 375 Dia pipe incl rock beaching	1	#	2,500.00	2,500	3,000	300	3,300		
600x600 Offtake Pit	4	#	1,000.00	4,000	4,800	480	5,280		
900x900 Offtake Pit	1	#	1,200.00	1,200	1,440	144	1,584		
WLRB Outlet Control pit (2.4mx2.4m)	1	#	15,000.00	15,000	18,000	1,800	19,800		
Landscaping									
Ephemeral batters (1,383m2) @6 plants/m2	8,298	#	1.70	14,107	16,928	1,693	18,621	SB = 281m2, WLTB = 1,102m2	
Shallow Marsh (896m2) @2 plants/m2	1,792	#	1.70	3,046	3,656	366	4,021		
Deep Marsh (3,516m2) @2 plants/m2	7,032	#	1.70	11,954	14,345	1,435	15,780		
Submerged Marsh (239m2) @1 plant/m2	239	#	1.70	406	488	49	536		
Miscellaneous									
Construct Sed Basin hard base floor (400mm depth rock)	603	sq.m	15.00	9,045	10,854	1,085	11,939		
Construct drying areas with 100mm CL3 FCR	634	sq.m	12.00	7,608	9,130	913	10,043		
Construct Access Tracks / Ramps (200mm depth CR)	0	sq.m	20.00	-	-	-	-		
Construct Sed Basin bypass with concrete weir (b=3m)	1	Item	3,200.00	3,200	3,840	384	4,224	\$150/m for 500 deep concrete weir (say 7m long) + \$40/m2 for apron rock (say 52.5m2)	
As-constructed survey of basin/WLRB	1	Item	8,000.00	8,000	9,600	960	10,560	\$560,003.28	
Maintenance of landscaping - 2yrs									
Provisional Items	1	Item	30,000.00	30,000	36,000	3,600	39,600		
Excavate and disposal of unsuitable material		cu.m	35.00	-	-	-	-		
Supply, place and compact clay fill from s'pile		cu.m	40.00	-	-	-	-		
Treat clay with (3% lime / 1% gysum) to 200mm depth		sq.m	9.00	-	-	-	-		
Totals				496,669	596,003	59,600	655,604		
Professional fees									
Detailed design & documentation (8% x const cost)	1	Item	-	-	-	-	-	\$44,800.26	
Geotechnical	1	Item	-	-	-	-	-		
Survey	1	Item	-	-	-	-	-		
Totals				496,669	596,003	59,600	655,604		
Total including contingency and GST							\$ 655,603.61		
Note:									
1. Assumed 300mm depth for clay liner. TBC by Geotech investigation.									

4267-01_R03v01c_Area_C_SouthFD_report.docx



Melbourne

15 Business Park Drive
Notting Hill VIC 3168
Telephone (03) 8526 0800
Fax (03) 9558 9365

Wangaratta

First Floor, 40 Rowan Street
Wangaratta VIC 3677
Telephone (03) 5721 2650

Geelong

PO Box 436
Geelong VIC 3220
Telephone 0458 015 664

Wimmera

PO Box 584
Stawell VIC 3380
Telephone 0438 510 240

Brisbane

Level 3, 43 Peel Street
South Brisbane QLD 4101
Telephone (07) 3105 1460
Fax (07) 3846 5144

Perth

PO Box 362
Subiaco WA 6904
Telephone 0438 347 968

Gippsland

154 Macleod Street
Bairnsdale VIC 3875
Telephone (03) 5152 5833

www.watertech.com.au

info@watertech.com.au

