



# Hylío AG-230 Spec Sheet - Imperial

Aircraft	
Total Weight (without batteries)	61 lb.
Maximum Recommended Takeoff Weight	165 lb.
Maximum Thrust	270 lb.
Maximum Operating Speed	30 mph
Flight Time	<p>Full Payload: approx. 8 min.  Mixed: approx. 12-15 min. @ 25 lb./min. payload application rate  No Payload: approx. 20 min.</p> <p><i>Flight times are affected by numerous conditions such as weather conditions, altitude relative to MSL, temperature, battery age/health, and other factors.</i></p>
Spray System	
Maximum Payload (Weight)	85 lb.
Maximum Payload (Volume)	8 gal.
Nozzle Compatibility	<p>Compatible with any TeeJet or similar style nozzle tips.</p> <p>Optional rotary atomizer nozzles available.</p>
Pump System	2 x Diaphragm Pump, 65 PSI
Flow Rate (no nozzle)	0.4 – 4.0 gal./min.
Flow Rate (with TT 11003 nozzle tip)	3.0 gal./min.
Effective Swath Width	20 – 30 ft.
Productivity Rate	Up to 50 ac./hr. at 1 gal./ac.
Spreader System	
Maximum Payload (Weight)	85 lb.
Maximum Payload (Volume)	5 gal.
Weight of Device	3 lb.
Optimal Particle Size	0.02 – 0.4 in.
RPM Range	Up to 1621 RPM
Aperture Control	3 channels, allowing 0 – 170 deg. total opening
Effective Swath	Up to 45 ft.
Maximum Flow Rate	Up to 16 lb./min.
Device Dimensions	9 x 6 x 3 in.
Productivity Rate	Up to 60 ac./hr. at 20 lb./ac.



Propulsion	
Motor KV	100 rpm/V
Foldable Propeller	30 x 9 in.
Configuration	Octocopter
Operating Voltage	12S (44.4 V.)
Battery	
Battery System	2 x 12S 16 Ah (44.4 V) Intelligent LiPo Batteries
Battery Weight	9 lb. each; total = 18 lb.
Charger	
Type	Dual Channel
Input Voltage	100 – 240V
Output Power	AC220V: 3000W AC110V: 1200W
Compatibility	LiPo: 12S/14S; LiHV: 12S
Dimensions	11.5 in. x 5.5 in. x 11 in.
Weight	12 lb.
Charging Current	<b>AC220V</b>  Fast Charge: 60A Single Channel Max Standard Charge: 30A Single Channel Max; 60A Total Across Two Channels  <b>AC110V</b>  20A Single Channel Max; 60A Total Across All Channels
Weather	
Ingress Protection Rating	IP55
Maximum Sustained Wind	25 mph
Maximum Wind Gust	40 mph
Communication & Control (Hylío GroundLink)	
Standard Control Device	Hylío GroundLink Controller
Ground Station Control Software	Hylío AgroSol GCS; GroundLink Operating system: Windows 11
Available Flight Modes	Swarm up to 3 units, fully autonomous, position hold manual, fully manual
Operating Frequencies	2470 to 2477 MHz
Wireless Transmission Range	Max Unobstructed: 18.5 mi. Typical Rural Operation Setting: 3 mi. With 4G SIM: Unlimited (wherever cellular coverage is available)
Display	13.3" Sunlit Readable 1000 nits, 10-Point Touch Display
Environment	IP67
Battery	6-8 Hours, Rechargeable Li-ion Battery <i>Battery life dependent on factors such as screen brightness and level of activity</i>
Regulatory Compliance	FY2019 NDAA Sec. 889 Compliant; FY2020 NDAA Section 848 Compliant; FCC Part 15 Compliant