

## linelube Compressor Oils 32 - 150

### Product Description

A range of premium quality industrial compressor lubricants. The linelube Compressor Oil range is blended from special base oils which have low carbon forming tendencies and are fortified with additives to inhibit wear, corrosion, oxidation and foaming.

### Features & Benefits

- Prolonged service life due to good oxidation resistance, excellent anti-wear and anti-corrosion properties
- Low foaming tendency
- Good demulsifiability

### Applications

Suitable for use in rotary screw, vane, vacuum pumps and reciprocating compressors. These products can be used for extended drain intervals up to 4000 hours.

### Specifications

- DIN 51506 VB
- DIN 51506 VC
- DIN 51524 Part II and Part III (HLP, HVLP)
- DIN 51515 Part 11

### Typical Test Data

ISO Viscosity Grade	32	46	68	100	150
Specific Gravity @ 16°C	0.870	0.875	0.878	0.883	0.888
Kinematic Viscosity mm <sup>2</sup> /s @ 40°C	32	46	68	100	150
Kinematic Viscosity mm <sup>2</sup> /s @ 100°C	5.4	6.8	8.7	11.5	15.2
Viscosity Index (VI)	102	100	100	100	100
Pour Point (°C)	-20	-20	-20	-20	-20
Flash Point (°C)	220	230	235	245	255

### Health & Safety

For health and safety information please refer to the relevant health & safety data sheet on our website. The contents of this data sheet are given in good faith but without warranty.