

linelube Synthetic 75W-90 Gear Oil

Product Description

linelube Synthetic 75W-90 Gear Oil is a modern high-performance product manufactured from a blend of synthetic oil, sheer stable viscosity index improvers and a multipurpose extreme pressure additive system. It offers a high level of performance when compared to straight mineral oil whilst being compatible with mineral oils. This enables it to be used simply as a replacement product on a drain and fill basis.

Features & Benefits

- Very high levels of rust and corrosion resistance
- Long drain capability
- Excellent oxidation stability
- Very good thermal stability
- Outstanding low and high temperature performance

Applications

For use in high performance manual transmissions, spiral bevel axles, high load drive axles, hypoid axles and steering units. The use of this product will often smooth and improve manual gear changes in previously “notchy” gear boxes.

Specifications

- **API:** GL-4, GL-5, MT-1
- **SAE:** J2360 (PRI GL 0328)
- **MAN:** 3343 S (ex 3343 SL)
- **Mack:** GO-J Plus
- **Mercedes Benz:** MB235.8
- **Volvo:** 97312
- **Scania:** STO 1:0
- **Ford:** WSD- M2C200-C
- **Military:** MIL-PRF-2105E
- **ZF:** TE-ML 02B, 05B, 07A, 12B, 16F, 17B, 19C, 21B

Typical Test Data

Density @ 15°C	0.889
Kinematic Viscosity @ 40°C	103
Kinematic Viscosity @ 100°C	15.1
Viscosity Index	156
Pour Point (°C)	-41
Flash Point COC (°C)	216

Health & Safety

For health and safety information please refer to the relevant health & safety data sheet on our website. The contents of this data sheet is given in good faith but without warranty.