

linelube Transmission Oil TO4 - 30

Product Description

A quality single grade transmission fluid designed to meet the requirements of Caterpillar TO-4, GM Allison C-4 and Komatsu Dresser applications in off-highway construction and earthmoving equipment. Blended from quality base oils together with a specific additive system Transmission TO-4 Fluid ensures the advanced performance characteristics required to meet the test parameters of these up to date specifications. Improved frictional properties, Anti-wear performance oxidation stability and Wet Brake performance offer the essentials for longer equipment life.

Features & Benefits

- · Improved frictional properties
- Suitable for a wide range of highway equipment
- Oxidation stability

Applications

Transmission TO-4 Fluids will find application in a wide range of off highway equipment including Caterpillar transmissions and final drives GM Allison powershift transmissions and Komatsu, ZF, Torque converters, Eaton Dana manual transmissions and for all contractors plant where TO-4 or C-4 performance has been specified.

Specifications

Allison: C-4 (SAE 10, 30)

• Caterpillar: TO-4

Dresser

GM Detroit

Komatsu

• ZF: TE ML-03

ZF: TE ML-01

• Eaton and Dana (Spicer) Manual Transmissions (SAE 30, 50)

Typical Test Data

SAE Grade	30
Specific Gravity @ 15.6°C	0.888
Kinematic Viscosity @ 100°C	11.5
Viscosity Index	100
Pour Point (°C)	-30
Flash Point (°C)	210

Health & Safety

For health and safety information please refer to the relevant health & safety data sheet on our website. The contents of this data sheet is given in good faith but without warranty.

www.linelube.co.uk