

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Product name : COPAL OGL 2
Product code : 36601
Product description : Not available.
Product type : Solid.
Other means of identification : Not available.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses

☒ Lubricating grease
Formulation additives, lubricants and greases - Industrial
General use of lubricants and greases in vehicles or machinery - Industrial
General use of lubricants and greases in vehicles or machinery - Professional
Use of lubricants and greases in open systems - Industrial
Use of lubricants and greases in open systems - Professional

Uses advised against

Not applicable.

1.3 Details of the supplier of the safety data sheet

TotalEnergies Lubrifiants
562 Avenue du Parc de L'île
92029 Nanterre Cedex FRANCE
Tél: +33 (0)1 41 35 40 00
Fax: +33 (0)1 41 35 84 71
rm.msds-lubs@totalenergies.com

TotalEnergies Marketing UK Limited
10 Upper Bank Street (19th floor)
Canary Wharf,
London E14 5BF
UNITED KINGDOM
Tel: +44 (0)20 7339 8000
Fax: +44 (0)20 7339 8033
rm.gb-msds@totalenergies.com

H.S.E

1.4 Emergency telephone number

National advisory body/Poison Centre

Telephone number : National Poisons Information Service (NPIS): 111

Supplier

Telephone number : Emergency telephone: +44 1235 239670

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Eye Dam. 1, H318

Aquatic Chronic 3, H412

The product is classified as hazardous according to UK CLP Regulation SI 2019/720 as amended.

Ingredients of unknown ecotoxicity : Contains 13.6% of components with unknown hazards to the aquatic environment

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H318 - Causes serious eye damage.
H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention : P280 - Wear eye or face protection.
P273 - Avoid release to the environment.

Response : P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Storage : Not applicable.

Disposal : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

Contains : Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts

Supplemental label elements : Contains Naphthenic acids, zinc salts, basic. May produce an allergic reaction.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

This mixture does not contain any substances that are assessed to be a PBT or a vPvB in a concentration $\geq 0,1$ %.
This product does not contain any substance present at a concentration equal to or greater than 0.1% by mass, included in the list drawn up in accordance with article 59, paragraph 1 of the REACH Regulation, due to its endocrine disrupting properties, or a substance known to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation 2018/605.

SECTION 2: Hazards identification

Other hazards which do not result in classification : None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification	Type
(benzoato-O,O')hydroxy (octadecanoato-O,O')aluminium	REACH #: 01-2120127786-48 EC: 259-105-7 CAS: 54326-11-3	≥10 - ≤25	Not classified.	[2]
Synthetic graphite	EC: 231-955-3 CAS: 7782-42-5	≤10	Not classified.	[2]
Phosphorodithioic acid, mixed O, O-bis(iso-Bu and pentyl) esters, zinc salts	REACH #: 01-2119493628-22 EC: 270-608-0 CAS: 68457-79-4	≤10	Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Chronic 2, H411	[1]
mineral oil	-	≤3	Asp. Tox. 1, H304	[1]
Reaction products of diphosphorus pentaoxide and alcohol C7-9-iso, C8 rich, salted with 2-ethylhexylamine molybdenum disulphide	REACH #: 01-2120087237-50 EC: 942-466-6 EC: 215-263-9 CAS: 1317-33-5	≤3 ≤3	Eye Dam. 1, H318	[1]
Naphthenic acids, zinc salts, basic	EC: 215-263-9 CAS: 1317-33-5 REACH #: 01-2119988500-34 EC: 282-762-6 CAS: 84418-50-8	≤3 <1	Not classified. Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 3, H412 See Section 16 for the full text of the H statements declared above.	[2] [1]

Additional information : Mineral oil of petroleum origin Product containing mineral oil with less than 3% DMSO extract as measured by IP 346 The product is made from synthetic base oils

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type


[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact :  Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.

SECTION 4: First aid measures

- Inhalation** : Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Get medical attention immediately. Call a poison center or physician. Wash skin thoroughly with soap and water or use recognised skin cleanser. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain
watering
redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:
pain or irritation
redness
dryness
cracking
blistering may occur
- Ingestion** : Adverse symptoms may include the following:
stomach pains

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing media : Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture : This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous combustion products : carbon monoxide
carbon dioxide
nitrogen oxides
phosphorus oxides
sulfur oxides
Hydrogen sulfide
Mercaptans
Zinc oxides

5.3 Advice for firefighters

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : ☒ No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

6.3 Methods and material for containment and cleaning up

Small spill : ☒ Move containers from spill area. Avoid dust generation. Using a vacuum with HEPA filter will reduce dust dispersal. Place spilled material in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.

SECTION 6: Accidental release measures

- Large spill** : Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.
- 6.4 Reference to other sections** : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Do not get in eyes or on skin or clothing. Do not ingest. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

- Recommendations** : See exposure scenarios
- Industrial sector specific solutions** : Not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

SECTION 8: Exposure controls/personal protection

Product/substance	Exposure limit values
(benzoato-O,O')hydroxy(octadecanoato-O,O') aluminium	EH40/2005 WELs (United Kingdom (UK), 1/2020). [aluminium salts, soluble] TWA: 2 mg/m ³ 8 hours.
Synthetic graphite	EH40/2005 WELs (United Kingdom (UK), 1/2020). TWA: 4 mg/m ³ 8 hours. Form: respirable dust TWA: 10 mg/m ³ 8 hours. Form: inhalable dust
molybdenum disulphide	EH40/2005 WELs (United Kingdom (UK), 1/2020). [molybdenum insoluble compounds as Mo] STEL: 20 mg/m ³ , (as Mo) 15 minutes. TWA: 10 mg/m ³ , (as Mo) 8 hours.

Reportable hazardous constituent(s) contained in UVCB- and/or multi-constituent substance(s) complying with the classification criteria and/or with an exposure limit (OEL)

No exposure limit value known.

Biological Limit Values (BLV)

No exposure indices known.

Recommended monitoring procedures : Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Advisory OEL : Mineral oil mist: USA: OSHA (PEL) TWA 5 mg/m³, NIOSH (REL) TWA 5 mg/m³, STEL 10 mg/m³, ACGIH (TLV) TWA 5 mg/m³ (highly refined)

DNELs/DMELs

Product/substance	Type	Exposure	Value	Population	Effects
Synthetic graphite	DNEL	Long term Inhalation	1.2 mg/m ³	Workers	Systemic
	DNEL	Long term Inhalation	1.2 mg/m ³	Workers	Local
	DNEL	Long term Inhalation	1.2 mg/m ³	Workers	Systemic
	DNEL	Long term Inhalation	0.14 mg/m ³	Workers	Local
	DNEL	Short term Inhalation	0.26 mg/m ³	Workers	Local
	DNEL	Long term Inhalation	0.3 mg/m ³	General population	Local
	DNEL	Long term Oral	813 mg/kg bw/day	General population	Systemic
	DNEL	Long term Oral	0.24 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	2.06 mg/m ³	General population	Systemic
	DNEL	Long term Dermal	5.93 mg/kg bw/day	General population	Systemic
Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts	DNEL	Long term Inhalation	8.13 mg/m ³	Workers	Systemic
	DNEL	Long term Dermal	11.87 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	4.93 mg/m ³	Workers	Systemic
	DNEL	Long term Dermal	1.4 mg/m ³	Workers	Systemic
Naphthenic acids, zinc salts, basic	DNEL	Long term Inhalation			
	DNEL	Long term Dermal			

SECTION 8: Exposure controls/personal protection

	DNEL	Long term Inhalation	0.87 mg/m ³	General population	Systemic
	DNEL	Long term Dermal	0.5 mg/m ³	General population	Systemic
	DNEL	Long term Oral	0.5 mg/m ³	General population	Systemic

PNECs

Product/substance	Compartment Detail	Value	Method Detail
Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts Naphthenic acids, zinc salts, basic	Fresh water	1.9 mg/l	-
	Marine water	1.9 mg/l	-
	Sewage Treatment Plant	39 mg/l	-
	Fresh water sediment	33 mg/kg	-
	Marine water sediment	33 mg/kg	-
	Fresh water	5.62 to 20.6 µg/l	-
	Marine water	562 to 6100 ng/l	-
	Fresh water sediment	28.1 to 117.8 mg/kg dwt	-
	Marine water sediment	2.81 to 56.5 mg/kg dwt	-
	Soil	5.61 to 37.6 mg/kg dwt	-
	Sewage Treatment Plant	100 to 147.73 µg/l	-

8.2 Exposure controls

Appropriate engineering controls

- ☑ If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Individual protection measures

Hygiene measures

- : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

- ☑ Tightly-fitting goggles or face shield, EN 166.

Skin protection

Hand protection

- : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

SECTION 8: Exposure controls/personal protection

Hydrocarbon-proof gloves
nitrile rubber
Fluorinated rubber
Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.
In case of prolonged contact with the product, it is recommended to wear gloves complying with ISO 21420 and EN 374 standards, protecting at least for 480 minutes and having a thickness of 0,38 mm at least. These values are indicative only. The level of protection is provided by the material of the glove, its technical characteristics, its resistance to the chemicals to be handled, the appropriateness of its use and its replacement frequency

- Body protection** : Wear work clothing with long sleeves.
Protective shoes or boots.
- Respiratory protection** : Ensure adequate ventilation and check that a safe, breathable atmosphere is present before entry into confined spaces. In case of inadequate ventilation wear respiratory protection: Type A/P1. Warning ! filters have a limited use duration. The use of breathing apparatus must comply strictly with the manufacturer's instructions and the regulations governing their choices and uses.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature (20°C / 68°F) and pressure (1013 hPa) unless otherwise indicated

9.1 Information on basic physical and chemical properties

Appearance

- Physical state** : Solid. [smooth]
- Colour** : Black.
- Odour** : Characteristic.
- Melting point/freezing point** : >180°C
- Initial boiling point and boiling range** : Not applicable.
- Flammability (solid, gas)** : Not applicable.
- Upper/lower flammability or explosive limits** : Not applicable.
- Flash point** : Open cup: Not applicable.
- Auto-ignition temperature** : Not applicable.
- Decomposition temperature** : >180°C
- pH** : Not applicable. Product is non-soluble (in water).
- Viscosity** : Kinematic (40°C): Not applicable.
- Solubility(ies)** :

Media	Result
water	Not soluble

- Miscible with water** : No.

SECTION 9: Physical and chemical properties

Partition coefficient: n-octanol/ water	: >3.5
Vapour pressure	: Not applicable.
Relative density	: 0.9
Density	: 0.9 g/cm ³ [20°C (68°F)]
Vapour density	: Not applicable.
<u>Particle characteristics</u>	
Median particle size	: Not available.

9.2 Other information

No other relevant physical and chemical parameters for the safe use of the product

SECTION 10: Stability and reactivity

10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: Stable under recommended storage and handling conditions (see Section 7).
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: No specific data.
10.5 Incompatible materials	: Strong oxidising agents
10.6 Hazardous decomposition products	: carbon monoxide carbon dioxide nitrogen oxides phosphorus oxides sulfur oxides Hydrogen sulfide Mercaptans Zinc oxides

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/substance	Result	Species	Dose	Exposure	Test
(Benzoato-O,O')hydroxy (octadecanoato-O,O') aluminium	LD50 Dermal	Rat	>2000 mg/kg	-	402 Read across
	LD50 Oral	Rat	>2000 mg/kg	-	OECD 420 Read across
Synthetic graphite	LC50 Inhalation Dusts and mists	Rat - Male, Female	>2000 mg/m ³	4 hours	OECD 403
	LD50 Oral	Rat - Female	>2000 mg/kg	-	OECD 401
Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts	LD50 Dermal	Rabbit	>20 g/kg	-	OECD 402 Acute Dermal Toxicity

SECTION 11: Toxicological information

Reaction products of diphosphorus pentaoxide and alcohol C7-9-iso, C8 rich, salted with 2-ethylhexylamine	LD50 Oral	Rat	3.6 g/kg	-	-
	LD50 Oral	Rat	2500 mg/kg	-	OECD 401
	LD50 Dermal	Rabbit	>2000 mg/kg	-	-
	LD50 Oral	Rat	>2000 mg/kg	-	-
Naphthenic acids, zinc salts, basic	LC50 Inhalation Dusts and mists	Rat	>420 mg/m ³	4 hours	-
	LD50 Dermal	Rabbit	>2000 mg/kg	-	OECD 403 Acute Inhalation Toxicity
	LD50 Oral	Rat	>2000 mg/kg	-	OECD 402 Acute Dermal Toxicity
	LD50 Oral	Rat	>2000 mg/kg	-	OECD 423 Acute Oral toxicity - Acute Toxic Class Method

Acute toxicity estimates

Product/substance	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts	3600	N/A	N/A	N/A	N/A

Conclusion/Summary : Based on available data, the classification criteria are not met.

Irritation/Corrosion

Product/substance	Result	Species	Score	Exposure	Test
Synthetic graphite	Eyes - Iris lesion	Rabbit	0	-	OECD 405 404
	Skin - Oedema	Rabbit	0	-	

Conclusion/Summary

Skin : Based on available data, the classification criteria are not met.

Eyes : Based on available data, the classification criteria are met.

Respiratory : Based on available data, the classification criteria are not met.

Sensitisation

Product/substance	Route of exposure	Species	Result
Synthetic graphite	skin	Mouse	Not sensitizing

Conclusion/Summary

Skin : Based on available data, the classification criteria are not met. Contains sensitizer. May produce an allergic reaction.

Respiratory : Based on available data, the classification criteria are not met.

Mutagenicity

SECTION 11: Toxicological information

Product/substance	Test	Experiment	Result
Synthetic graphite	OECD 473	Experiment: In vitro Subject: Mammalian-Animal	Negative
	OECD 476	Experiment: In vitro Subject: Mammalian-Animal	Negative
	OECD 471	Experiment: In vitro Subject: Mammalian-Animal	Negative

Conclusion/Summary : Based on available data, the classification criteria are not met.

Carcinogenicity

Conclusion/Summary : Based on available data, the classification criteria are not met.

Reproductive toxicity

Product/substance	Maternal toxicity	Fertility	Developmental toxin	Species	Dose	Exposure
Synthetic graphite	Negative	Negative	Negative	Rat - Male, Female	Oral	-

Conclusion/Summary : Based on available data, the classification criteria are not met.

Teratogenicity

Conclusion/Summary : Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Not available.

Conclusion/Summary : Based on available data, the classification criteria are not met.

Specific target organ toxicity (repeated exposure)

Not available.

Conclusion/Summary : Based on available data, the classification criteria are not met.

Aspiration hazard

Product/substance	Result
mineral oil	ASPIRATION HAZARD - Category 1

Conclusion/Summary : Based on available data, the classification criteria are not met.

Information on likely routes of exposure : Not available.

Potential acute health effects

- Eye contact** : ☒ Causes serious eye damage.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : Defatting to the skin. May cause skin dryness and irritation.
- Ingestion** : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : ☒ Adverse symptoms may include the following:
pain
watering
redness
- Inhalation** : No specific data.

SECTION 11: Toxicological information

- Skin contact** : Adverse symptoms may include the following:
pain or irritation
redness
dryness
cracking
blistering may occur
- Ingestion** : Adverse symptoms may include the following:
stomach pains

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Long term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Potential chronic health effects

Product/substance	Result	Species	Dose	Exposure
Synthetic graphite	Sub-acute NOAEL Oral	Rat - Male, Female	813 mg/kg	-
	Sub-acute NOAEL Inhalation Dusts and mists	Rat - Male, Female	12 mg/m ³	4 weeks

- Conclusion/Summary** : Not available.
- General** : No known significant effects or critical hazards.
- Carcinogenicity** : No known significant effects or critical hazards.
- Mutagenicity** : No known significant effects or critical hazards.
- Reproductive toxicity** : No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

This product does not contain any substance present at a concentration equal to or greater than 0.1% by mass, included in the list drawn up in accordance with article 59, paragraph 1 of the REACH Regulation, due to its endocrine disrupting properties, or a substance known to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation 2018/605.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

Harmful to aquatic life with long lasting effects.

12.1 Toxicity

SECTION 12: Ecological information

Product/substance	Result	Species	Exposure	Test
Synthetic graphite	Acute EC50 101 mg/l	Algae - <i>Desmodesmus subspicatus</i>	72 hours	OECD 201
	Acute EC50 101 mg/l	Daphnia - <i>Daphnia magna</i>	48 hours	OECD 202
	Acute LC50 101 mg/l	Fish	96 hours	-
	Acute NOEC 101 mg/l	Algae - <i>Desmodesmus subspicatus</i>	72 hours	OECD 201
	Acute NOEC 101 mg/l	Daphnia - <i>Daphnia magna</i>	48 hours	OECD 202
	Acute NOEC >100 mg/l	Fish - <i>Danio rerio</i>	96 hours	OECD 203
	Acute EC50 10 mg/l	Daphnia - <i>Daphnia magna</i>	48 hours	OECD 202
Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts				
	Acute LC50 32 mg/l	Algae - <i>Scenedesmus subspicatus</i>	72 hours	OECD 201
	Acute LC50 5.3 mg/l	Fish - <i>Oncorhynchus mykiss</i>	96 hours	OECD 203
	Acute NOEC 0.8 mg/l	Daphnia - <i>Daphnia magna</i>	21 days	-
	Acute EC50 32 mg/l	Algae - <i>Pseudokirchneriella subcapitata</i>	72 hours	-
Reaction products of diphosphorus pentaoxide and alcohol C7-9-iso, C8 rich, salted with 2-ethylhexylamine				
	Acute EC50 16 mg/l	Daphnia - <i>Daphnia magna</i>	48 hours	-
	Acute LC50 75 mg/l	Fish	96 hours	-
	Chronic NOEC 1.6 mg/l	Daphnia - <i>Daphnia magna</i>	21 days	-

Conclusion/Summary : Not available.

12.2 Persistence and degradability

Conclusion/Summary : Not available.

Product/substance	Aquatic half-life	Photolysis	Biodegradability
Benzoato-O,O')hydroxy (octadecanoato-O,O') aluminium	-	-	Readily
Synthetic graphite	-	-	Readily
Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts	-	-	Not readily
molybdenum disulphide	-	-	Readily
Naphthenic acids, zinc salts, basic	-	-	Inherent

12.3 Bioaccumulative potential

Product/substance	LogP _{ow}	BCF	Potential
COPAL OGL 2	>3.5	-	Low
Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts	0.69	-	Low
Naphthenic acids, zinc salts, basic	-	60960	High

12.4 Mobility in soil

SECTION 12: Ecological information

- Soil/water partition coefficient (K_{oc})** : Not available.
- Mobility** : Not available.
- Mobility in soil** : Given its physical and chemical characteristics, the product has no soil mobility. The product is insoluble and floats on water. Loss by evaporation is limited

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB in a concentration $\geq 0,1$ %.

12.6 Endocrine disrupting properties

This product does not contain any substance present at a concentration equal to or greater than 0.1% by mass, included in the list drawn up in accordance with article 59, paragraph 1 of the REACH Regulation, due to its endocrine disrupting properties, or a substance known to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation 2018/605.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

- Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
- Hazardous waste** : ☒ Yes.
According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user based on the application for which the product was used. The following Waste Codes are only suggestions: 12 01 12*

Packaging

- Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
- Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	ICAO/IATA
14.1 UN number or ID number	Not regulated.	9005	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S., MOLTEN (Phosphorodithioic acid, mixed O,O-bis (iso-Bu and pentyl) esters, zinc salts)	-	-
14.3 Transport hazard class(es)	-	9	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.

Additional information

ADN

: The product is only regulated as a dangerous good when transported in tank vessels.

14.6 Special precautions for user

: **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments

: Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

UK (GB)/REACH

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Ozone depleting substances

Not listed.

Prior Informed Consent (PIC)

Not listed.

SECTION 15: Regulatory information

Persistent Organic Pollutants

Not listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Seveso Directive

This product is not controlled under the Seveso Directive.

EU regulations

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work.

DIRECTIVE 2008/68/EC related on the inland transport of dangerous goods

**Industrial emissions
(integrated pollution
prevention and control) -
Air** : Not listed

**Industrial emissions
(integrated pollution
prevention and control) -
Water** : Not listed

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Inventory list

Australia inventory (AIIC)	: All components are listed or exempted.
Canada inventory	: All components are listed or exempted.
China inventory (IECSC)	: All components are listed or exempted.
Europe inventory	: All components are listed or exempted.
Japan inventory	: Japan inventory (CSCL) : All components are listed or exempted. Japan inventory (ISHL) : All components are listed or exempted.
New Zealand Inventory of Chemicals (NZIoC)	: At least one component is not listed.
Philippines inventory (PICCS)	: Not determined.
Korea inventory (KECI)	: Not determined.
Taiwan Chemical Substances Inventory (TCSI)	: All components are listed or exempted.
Thailand inventory	: Not determined.

SECTION 15: Regulatory information

- Turkey inventory** : Not determined.
United States inventory (TSCA 8b) : All components are listed or exempted.
Vietnam inventory : Not determined.

The information stated in this section relates solely to the conformity of the chemical product with the countries Inventories. The information used to confirm the inventory status of this product may be based on additional data to the chemical composition shown in Section 3. Other regulations may apply for importation or marketing authorizations.

15.2 Chemical safety assessment : See exposure scenarios

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms : ATE = Acute Toxicity Estimate
 CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
 DNEL = Derived No Effect Level
 DMEL = Derived Minimal Effect Level
 EUH statement = CLP-specific Hazard statement
 N/A = Not available
 PBT = Persistent, Bioaccumulative and Toxic
 vPvB = Very Persistent and Very Bioaccumulative
 PNEC = Predicted No Effect Concentration
 LC50 = Median lethal concentration
 LD50 = Median lethal dose
 OEL = Occupational Exposure Limit
 VOC = Volatile Organic Compound
 UVCB Substance of unknown or Variable composition, Complex reaction products or Biological material
 NOEC No Observed Effect Concentration
 QSAR = Quantitative Structure–Activity Relationship

Procedure used to derive the classification

Classification	Justification
Eye Dam. 1, H318 Aquatic Chronic 3, H412	Calculation method Calculation method

Full text of abbreviated H statements

H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Full text of classifications

SECTION 16: Other information

Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Asp. Tox. 1	ASPIRATION HAZARD - Category 1
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITISATION - Category 1

Date of printing : 2023/09/28

Date of issue/ Date of revision : 2023/09/28

Date of previous issue : 2023/01/06

Version : 4

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Annex to the extended Safety Data Sheet (eSDS)

Industrial

Identification of the substance or mixture

Product definition : Mixture
Code : 36601
Product name : COPAL OGL 2

Section 1 - Title

Short title of the exposure scenario : Formulation additives, lubricants and greases - Industrial

List of use descriptors : **Identified use name:** Formulation additives, lubricants and greases - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC09, PROC15
Sector of end use: SU03, SU10
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC02

Health Contributing scenarios : **General measures applicable to all activities**
General exposures Use in contained systems Elevated temperature - PROC02
Mixing operations Closed systems Batch processes at elevated temperatures - PROC03
Mixing operations Open systems Batch processes at elevated temperatures - PROC04, PROC05
Mixing operations (open systems) - PROC04, PROC05
Process sampling - PROC04, PROC08b
Bulk transfers Dedicated facility - PROC08b
Drum/batch transfers Dedicated facility - PROC08b
Drum/batch transfers Non-dedicated facility - PROC08a
Equipment cleaning and maintenance - PROC08a, PROC08b
Drum and small package filling - PROC09
Laboratory activities - PROC15
Storage - PROC01, PROC02

Processes and activities covered by the exposure scenario : Industrial formulation of lubricant additives, lubricants and greases. Includes material transfers, mixing, large and small scale packing, sampling, maintenance.

Section 2 - Exposure controls

Contributing scenario controlling environmental exposure for 1:

ATIEL-ATC SPERC 2.Ai-I.v1

Amounts used : Volume manufactured/imported (tonnes/year) : 8.59E+03
Fraction of EU tonnage used in region : 0.1
Fraction of Regional tonnage used locally : 0.1

Frequency and duration of use : Emission days (days per year) : 300

Environment factors not influenced by risk management : Local freshwater dilution factor : 10
Local marine water dilution factor : 100

Other conditions affecting environmental exposure : Negligible wastewater emissions as process operates without water contact.
Release fraction to air from process (after typical onsite RMMs consistent with EU Solvent Emissions Directive requirements) : 5.00E-05
Release fraction to wastewater from process (after typical onsite RMMs and before (municipal) sewage treatment plant): 5.00E-11
Release fraction to soil from process (after typical onsite RMMs): 0

Technical conditions and measures at process level (source) to prevent release	: Common practices vary across sites thus conservative process release estimates used.
Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil	: Treat air emission to provide a typical removal efficiency of (%) : 70 Prevent discharge of undissolved substance to or recover from onsite wastewater. User sites are assumed to be provided with oil/water separators and for waste water to be discharged via public sewer system.
Organisational measures to prevent/limit release from site	: Do not apply industrial sludge to natural soils. Sewage sludge should be incinerated, contained or reclaimed.
Conditions and measures related to sewage treatment plant	: Estimated substance removal from wastewater via domestic sewage treatment (%): (%) : 0.31 Assumed domestic sewage treatment plant flow (m³/d) : 2.00E+03 Maximum allowable site tonnage (M _{safe}) based on release following total wastewater treatment removal (kg/day) : 480 210
Conditions and measures related to external treatment of waste for disposal	: External treatment and disposal of waste should comply with applicable local and/or national regulations.
Conditions and measures related to external recovery of waste	: External recovery and recycling of waste should comply with applicable local and/or national regulations.

Contributing scenario controlling worker exposure for 2: General measures applicable to all activities

Concentration of substance in mixture or article	: Covers percentage substance in the product up to 100 %. (unless stated differently)
Physical state	: Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure
Amounts used	: Not applicable.
Frequency and duration of use/exposure	: Covers daily exposures up to 8 hours (unless stated differently)
Human factors not influenced by risk management	: Not applicable.
Other conditions affecting workers exposure	: Covers percentage substance in the product up to 100% (unless stated differently)
Conditions and measures related to personal protection, hygiene and health evaluation	
Advice on general occupational hygiene	: Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN 374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent/minimise exposures and to report any skin problems that may develop. Avoid direct eye contact with product, also via contamination on hands.
Personal protection	: Use suitable eye protection.

**Contributing scenario controlling worker exposure for 3: General exposures Use in contained systems
Elevated temperature**

No other specific measures identified.

**Contributing scenario controlling worker exposure for 4: Mixing operations Closed systems Batch processes
at elevated temperatures**

Ventilation control measures	: Provide extract ventilation to points where emissions occur.
-------------------------------------	--

Contributing scenario controlling worker exposure for 5: Mixing operations Open systems Batch processes at elevated temperatures

Frequency and duration of use/exposure : Avoid carrying out activities involving exposure for more than 4 hours per day.

Ventilation control measures : Provide extract ventilation to points where emissions occur.

Contributing scenario controlling worker exposure for 6: Mixing operations (open systems)

Ventilation control measures : Provide extract ventilation to points where emissions occur.

Contributing scenario controlling worker exposure for 7: Process sampling

Frequency and duration of use/exposure : Avoid carrying out activities involving exposure for more than 1 hour per day.

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection : Wear chemical-resistant gloves (tested to EN374) in combination with specific activity training.

Contributing scenario controlling worker exposure for 8: Bulk transfers Dedicated facility

Frequency and duration of use/exposure : Avoid carrying out activities involving exposure for more than 4 hours per day.

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection : Wear chemical-resistant gloves (tested to EN374) in combination with intensive management supervision controls.

Contributing scenario controlling worker exposure for 9: Drum/batch transfers Dedicated facility

Ventilation control measures : Provide extract ventilation to points where emissions occur.

Contributing scenario controlling worker exposure for 10: Drum/batch transfers Non-dedicated facility

Frequency and duration of use/exposure : Avoid carrying out activities involving exposure for more than 1 hour per day.

Ventilation control measures : Provide a good standard of general or controlled ventilation (10 to 15 air changes per hour).

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection : Wear chemical-resistant gloves (tested to EN374) in combination with intensive management supervision controls.

Contributing scenario controlling worker exposure for 11: Equipment cleaning and maintenance

Technical conditions and measures to control dispersion from source towards the worker : Retain drain-downs in sealed storage pending disposal or for subsequent recycle.

Engineering controls : Drain down and flush system prior to equipment break-in or maintenance.

Conditions and measures related to personal protection, hygiene and health evaluation

Advice on general occupational hygiene : Clear spills immediately.

Personal protection : Wear chemical-resistant gloves (tested to EN374) in combination with intensive management supervision controls.

Contributing scenario controlling worker exposure for 12: Drum and small package filling

Ventilation control measures : Provide a good standard of general or controlled ventilation (10 to 15 air changes per hour).

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection : Wear chemical-resistant gloves (tested to EN374) in combination with specific activity training.

Contributing scenario controlling worker exposure for 13: Laboratory activities

Frequency and duration of use/exposure : Avoid carrying out activities involving exposure for more than 4 hours per day.

Contributing scenario controlling worker exposure for 14: Storage

Engineering controls : Store substance within a closed system.

Section 3 - Exposure estimation and reference to its source

Website: : Not applicable.

Exposure estimation and reference to its source - Environment: 1:

Exposure assessment (environment): : Used ECETOC TRA model.

Exposure estimation and reference to its source : Not available.

Exposure estimation and reference to its source - Workers: 2: General measures applicable to all activities

Exposure assessment (human): : The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.

Exposure estimation and reference to its source : Not available.

Exposure estimation and reference to its source - Workers: 3: General exposures Use in contained systems Elevated temperature

Exposure assessment (human): : The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.

Exposure estimation and reference to its source : Not available.

Exposure estimation and reference to its source - Workers: 4: Mixing operations Closed systems Batch processes at elevated temperatures

Exposure assessment (human): : The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.

Exposure estimation and reference to its source : Not available.

Exposure estimation and reference to its source - Workers: 5: Mixing operations Open systems Batch processes at elevated temperatures

Exposure assessment (human): : The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.

Exposure estimation and reference to its source : Not available.

Exposure estimation and reference to its source - Workers: 6: Mixing operations (open systems)

Exposure assessment (human): : The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.

Exposure estimation and reference to its source : Not available.

Exposure estimation and reference to its source - Workers: 7: Process sampling

Exposure assessment (human): : The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.

Exposure estimation and reference to its source : Not available.

Exposure estimation and reference to its source - Workers: 8: Bulk transfers Dedicated facility

- Exposure assessment (human):** : The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
- Exposure estimation and reference to its source** : Not available.

Exposure estimation and reference to its source - Workers: 9: Drum/batch transfers Dedicated facility

- Exposure assessment (human):** : The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
- Exposure estimation and reference to its source** : Not available.

Exposure estimation and reference to its source - Workers: 10: Drum/batch transfers Non-dedicated facility

- Exposure assessment (human):** : The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
- Exposure estimation and reference to its source** : Not available.

Exposure estimation and reference to its source - Workers: 11: Equipment cleaning and maintenance

- Exposure assessment (human):** : The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
- Exposure estimation and reference to its source** : Not available.

Exposure estimation and reference to its source - Workers: 12: Drum and small package filling

- Exposure assessment (human):** : The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
- Exposure estimation and reference to its source** : Not available.

Exposure estimation and reference to its source - Workers: 13: Laboratory activities

- Exposure assessment (human):** : The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
- Exposure estimation and reference to its source** : Not available.

Exposure estimation and reference to its source - Workers: 14: Storage

- Exposure assessment (human):** : The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
- Exposure estimation and reference to its source** : Not available.

Section 4 - Guidance to DU to evaluate whether he works inside the boundaries set by the ES

- Environment** : Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Further details on scaling and control technologies are provided in SPERC factsheet. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required. For further information see www.atiel.org/reach/introduction.
- Health** : Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. For further information see www.atiel.org/reach/introduction.

Additional good practice advice beyond the REACH CSA

Environment : Not available.**Health** : Not available.

Annex to the extended Safety Data Sheet (eSDS)

Industrial

Identification of the substance or mixture

Product definition : Mixture
Code : 36601
Product name : COPAL OGL 2

Section 1 - Title

Short title of the exposure scenario : General use of lubricants and greases in vehicles or machinery - Industrial

List of use descriptors : **Identified use name:** General use of lubricants and greases in vehicles or machinery - Industrial
Process Category: PROC01, PROC02, PROC08b, PROC09
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC04, ERC07

Health Contributing scenarios : **General measures applicable to all activities**
General exposures (closed systems) - PROC01
Initial factory fill of equipment Use in contained systems - PROC02, PROC09
Initial factory fill of equipment Open systems - PROC08b
Operation of equipment containing engine oils and similar Use in contained systems - PROC01
Equipment cleaning and maintenance - PROC08b
Equipment cleaning and maintenance Operation is carried out at elevated temperature (> 20°C above ambient temperature) - PROC08b
Storage - PROC01, PROC02

Processes and activities covered by the exposure scenario : Covers general use of lubricants and greases in vehicles or machinery in closed systems. Includes filling and draining of containers and operation of enclosed machinery (including engines) and associated maintenance and storage activities.

Section 2 - Exposure controls

Contributing scenario controlling environmental exposure for 1:

ATIEL-ATC SPERC 4.Bi.v1

Amounts used : Volume manufactured/imported (tonnes/year) : 2.26E+03
Fraction of EU tonnage used in region : 0.1
Fraction of Regional tonnage used locally : 0.1

Frequency and duration of use : Emission days (days per year) : 300

Environment factors not influenced by risk management : Local freshwater dilution factor : 10
Local marine water dilution factor : 100

Other conditions affecting environmental exposure : Negligible wastewater emissions as process operates without water contact.
Release fraction to air from process (after typical onsite RMMs consistent with EU Solvent Emissions Directive requirements) : 5.00E-05
Release fraction to wastewater from process (after typical onsite RMMs and before (municipal) sewage treatment plant): 5.00E-11
Release fraction to soil from process (after typical onsite RMMs): 0

Technical conditions and measures at process level (source) to prevent release : Common practices vary across sites thus conservative process release estimates used.

Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil	: Prevent discharge of undissolved substance to or recover from onsite wastewater. User sites are assumed to be provided with oil/water separators and for waste water to be discharged via public sewer system.
Organisational measures to prevent/limit release from site	: Do not apply industrial sludge to natural soils. Sewage sludge should be incinerated, contained or reclaimed.
Conditions and measures related to sewage treatment plant	: Estimated substance removal from wastewater via domestic sewage treatment (%): (%) : 0.31 Assumed domestic sewage treatment plant flow (m ³ /d) : 2.00E+03 Maximum allowable site tonnage (M _{Safe}) based on release following total wastewater treatment removal (kg/day) : 192 513
Conditions and measures related to external treatment of waste for disposal	: External treatment and disposal of waste should comply with applicable local and/or national regulations.
Conditions and measures related to external recovery of waste	: External recovery and recycling of waste should comply with applicable local and/or national regulations.

Contributing scenario controlling worker exposure for 2: General measures applicable to all activities

Concentration of substance in mixture or article	: Covers percentage substance in the product up to 100% (unless stated differently).
Physical state	: Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure.
Frequency and duration of use/exposure	: Covers daily exposures up to 8 hours (unless stated differently).
Other conditions affecting workers exposure	: Assumes use at not more than 20°C above ambient temperature. unless stated differently. Assumes a good basic standard of occupational hygiene has been implemented.
Conditions and measures related to personal protection, hygiene and health evaluation	
Advice on general occupational hygiene	: Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN 374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent/minimise exposures and to report any skin problems that may develop. Avoid direct eye contact with product, also via contamination on hands.
Personal protection	: Use suitable eye protection.

Contributing scenario controlling worker exposure for 3: General exposures (closed systems)

No other specific measures identified.

Contributing scenario controlling worker exposure for 4: Initial factory fill of equipment Use in contained systems

No other specific measures identified.

Contributing scenario controlling worker exposure for 5: Initial factory fill of equipment Open systems

Frequency and duration of use/exposure	: Avoid carrying out activities involving exposure for more than 4 hours per day.
Ventilation control measures	: Provide a good standard of general or controlled ventilation (10 to 15 air changes per hour)

Contributing scenario controlling worker exposure for 6: Operation of equipment containing engine oils and similar Use in contained systems

No other specific measures identified.

Contributing scenario controlling worker exposure for 7: Equipment cleaning and maintenance

Technical conditions and measures at process level (source) to prevent release : Retain drain-downs in sealed storage pending disposal or for subsequent recycle.

Engineering controls : Drain down system prior to equipment break-in or maintenance.

Ventilation control measures : Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection : Wear chemical-resistant gloves (tested to EN374) in combination with specific activity training.

Contributing scenario controlling worker exposure for 8: Equipment cleaning and maintenance Operation is carried out at elevated temperature (> 20°C above ambient temperature)

Technical conditions and measures to control dispersion from source towards the worker : Retain drain-downs in sealed storage pending disposal or for subsequent recycle.

Engineering controls : Drain down system prior to equipment break-in or maintenance.

Ventilation control measures : Provide extract ventilation to emission points when contact with warm (>50°C) lubricant is likely.

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection : Wear chemical-resistant gloves (tested to EN374) in combination with intensive management supervision controls.

Contributing scenario controlling worker exposure for 9: Storage

Engineering controls : Store substance within a closed system.

Section 3 - Exposure estimation and reference to its source

Website: : Not applicable.

Exposure estimation and reference to its source - Environment: 1:

Exposure assessment (environment): : Used ECETOC TRA model.

Exposure estimation and reference to its source : Not available.

Exposure estimation and reference to its source - Workers: 2: General measures applicable to all activities

Exposure assessment (human): : The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.

Exposure estimation and reference to its source : Not available.

Exposure estimation and reference to its source - Workers: 3: General exposures (closed systems)

Exposure assessment (human): : The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.

Exposure estimation and reference to its source : Not available.

Exposure estimation and reference to its source - Workers: 4: Initial factory fill of equipment Use in contained systems

Exposure assessment (human): : The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.

Exposure estimation and reference to its source : Not available.

Exposure estimation and reference to its source - Workers: 5: Initial factory fill of equipment Open systems

Exposure assessment (human):	: The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.

Exposure estimation and reference to its source - Workers: 6: Operation of equipment containing engine oils and similar Use in contained systems

Exposure assessment (human):	: The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.

Exposure estimation and reference to its source - Workers: 7: Equipment cleaning and maintenance

Exposure assessment (human):	: The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.

Exposure estimation and reference to its source - Workers: 8: Equipment cleaning and maintenance Operation is carried out at elevated temperature (> 20°C above ambient temperature)

Exposure assessment (human):	: The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.

Exposure estimation and reference to its source - Workers: 9: Storage

Exposure assessment (human):	: The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.

Section 4 - Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Environment	: Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Further details on scaling and control technologies are provided in SPERC factsheet. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required. For further information see www.atiel.org/reach/introduction .
Health	: Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. For further information see www.atiel.org/reach/introduction .

Additional good practice advice beyond the REACH CSA

Environment	: Not available.
Health	: Not available.

Annex to the extended Safety Data Sheet (eSDS)

Professional

Identification of the substance or mixture

Product definition : Mixture
Code : 36601
Product name : COPAL OGL 2

Section 1 - Title

Short title of the exposure scenario : General use of lubricants and greases in vehicles or machinery - Professional

List of use descriptors : **Identified use name:** General use of lubricants and greases in vehicles or machinery - Professional
Process Category: PROC01, PROC02, PROC08a, PROC08b, PROC20
Sector of end use: SU22
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC09a, ERC09b

Health Contributing scenarios : **General measures applicable to all activities**
Operation of equipment containing engine oils and similar Use in contained systems - PROC01
Material transfers Non-dedicated facility - PROC08a
Equipment cleaning and maintenance Dedicated facility - PROC08b, PROC20
Storage - PROC01, PROC02

Processes and activities covered by the exposure scenario : Covers general use of lubricants and greases in vehicles or machinery in closed systems. Includes filling and draining of containers and operation of enclosed machinery (including engines) and associated maintenance and storage activities.

Section 2 - Exposure controls

Contributing scenario controlling environmental exposure for 1:

ATIEL-ATC SPERC 9.Bp.v1

Amounts used : Volume manufactured/imported (tonnes/year) : 4.63E+03
Fraction of EU tonnage used in region : 0.1
Fraction of Regional tonnage used locally : 0.1

Frequency and duration of use : Emission days (days per year) : 365

Environment factors not influenced by risk management : Local freshwater dilution factor : 10
Local marine water dilution factor : 100

Other conditions affecting environmental exposure : Negligible wastewater emissions as process operates without water contact.
Release fraction to air from process (after typical onsite RMMs consistent with EU Solvent Emissions Directive requirements) : 1.00E-04
Release fraction to wastewater from process (after typical onsite RMMs and before (municipal) sewage treatment plant): 5.00E-04
Release fraction to soil from process (after typical onsite RMMs): 1.00E-03

Technical conditions and measures at process level (source) to prevent release : Common practices vary across sites thus conservative process release estimates used.

Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil : Prevent discharge of undissolved substance to or recover from onsite wastewater.

Organisational measures to prevent/limit release from site	: Do not apply industrial sludge to natural soils. Sewage sludge should be incinerated, contained or reclaimed.
Conditions and measures related to sewage treatment plant	: Estimated substance removal from wastewater via domestic sewage treatment (%): (%) : 0.31 Assumed domestic sewage treatment plant flow (m³/d) : 2.00E+03 Maximum allowable site tonnage (M _{Safe}) based on release following total wastewater treatment removal (kg/day) : 2 156
Conditions and measures related to external treatment of waste for disposal	: External treatment and disposal of waste should comply with applicable local and/or national regulations.
Conditions and measures related to external recovery of waste	: External recovery and recycling of waste should comply with applicable local and/or national regulations.

Contributing scenario controlling worker exposure for 2: General measures applicable to all activities

Concentration of substance in mixture or article	: Covers percentage substance in the product up to 100% (unless stated differently).
Physical state	: Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure.
Frequency and duration of use/exposure	: Covers daily exposures up to 8 hours (unless stated differently).
Other conditions affecting workers exposure	: Assumes use at not more than 20°C above ambient temperature. unless stated differently. Assumes a good basic standard of occupational hygiene has been implemented.
Conditions and measures related to personal protection, hygiene and health evaluation	
Advice on general occupational hygiene	: Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN 374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent/minimise exposures and to report any skin problems that may develop. Avoid direct eye contact with product, also via contamination on hands.
Personal protection	: Use suitable eye protection.

Contributing scenario controlling worker exposure for 3: Operation of equipment containing engine oils and similar Use in contained systems

No other specific measures identified.

Contributing scenario controlling worker exposure for 4: Material transfers Non-dedicated facility

Frequency and duration of use/exposure	: Avoid carrying out activities involving exposure for more than 4 hours per day.
Conditions and measures related to personal protection, hygiene and health evaluation	
Personal protection	: Wear chemical-resistant gloves (tested to EN374) in combination with specific activity training.

Contributing scenario controlling worker exposure for 5: Equipment cleaning and maintenance Dedicated facility

Technical conditions and measures at process level (source) to prevent release	: Retain drain-downs in sealed storage pending disposal or for subsequent recycle.
Engineering controls	: Drain down system prior to equipment break-in or maintenance.

Contributing scenario controlling worker exposure for 6: Storage

Engineering controls	: Store substance within a closed system.
-----------------------------	---

Section 3 - Exposure estimation and reference to its source

Website:	: Not applicable.
Exposure estimation and reference to its source - Environment: 1:	
Exposure assessment (environment):	: Used ECETOC TRA model.
Exposure estimation and reference to its source	: Not available.
Exposure estimation and reference to its source - Workers: 2: General measures applicable to all activities	
Exposure assessment (human):	: The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.
Exposure estimation and reference to its source - Workers: 3: Operation of equipment containing engine oils and similar Use in contained systems	
Exposure assessment (human):	: The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.
Exposure estimation and reference to its source - Workers: 4: Material transfers Non-dedicated facility	
Exposure assessment (human):	: The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.
Exposure estimation and reference to its source - Workers: 5: Equipment cleaning and maintenance Dedicated facility	
Exposure assessment (human):	: The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.
Exposure estimation and reference to its source - Workers: 6: Storage	
Exposure assessment (human):	: The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.

Section 4 - Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Environment	: Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Further details on scaling and control technologies are provided in SPERC factsheet. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required. For further information see www.atiel.org/reach/introduction .
Health	: Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. For further information see www.atiel.org/reach/introduction .

Additional good practice advice beyond the REACH CSA

Environment : Not available.**Health** : Not available.

Annex to the extended Safety Data Sheet (eSDS)

Industrial

Identification of the substance or mixture

Product definition : Mixture
Code : 36601
Product name : COPAL OGL 2

Section 1 - Title

Short title of the exposure scenario : Use of lubricants and greases in open systems - Industrial

List of use descriptors : **Identified use name:** Use of lubricants and greases in open systems - Industrial
Process Category: PROC01, PROC02, PROC07, PROC08b, PROC09, PROC10, PROC13
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC04

Health Contributing scenarios : **General measures applicable to all activities**
Material transfers Manual - PROC08b
Material transfers Automated process with (semi) closed systems - PROC08b, PROC09
Roller, spreader, flow application - PROC10
Spraying - PROC07
Treatment of articles by dipping and pouring - PROC13
Equipment cleaning and maintenance - PROC08b
Storage - PROC01, PROC02

Processes and activities covered by the exposure scenario : Covers use of lubricants and greases in open systems, including application of lubricant to work pieces or equipment by dipping, brushing or spraying (without exposure to heat), e.g. mold releases, corrosion protection, slideways. Includes associated product storage, material transfers, sampling and maintenance activities

Section 2 - Exposure controls

Contributing scenario controlling environmental exposure for 1:

ATIEL-ATC SPERC 4.Ci.v1

Amounts used : Volume manufactured/imported (tonnes/year) : 3.27E+02
Fraction of EU tonnage used in region : 0.1
Fraction of Regional tonnage used locally : 0.1

Frequency and duration of use : Emission days (days per year) : 300

Environment factors not influenced by risk management : Local freshwater dilution factor : 10
Local marine water dilution factor : 100

Other conditions affecting environmental exposure : Negligible wastewater emissions as process operates without water contact.
Release fraction to air from process (after typical onsite RMMs consistent with EU Solvent Emissions Directive requirements) : 5.0E-05
Release fraction to wastewater from process (after typical onsite RMMs and before (municipal) sewage treatment plant): 5.00E-11
Release fraction to soil from process (after typical onsite RMMs): 0

Technical conditions and measures at process level (source) to prevent release : Common practices vary across sites thus conservative process release estimates used.

Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil	: Treat air emission to provide a typical removal efficiency of (%) : 70 Prevent discharge of undissolved substance to or recover from onsite wastewater. User sites are assumed to be provided with oil/water separators and for waste water to be discharged via public sewer system.
Organisational measures to prevent/limit release from site	: Do not apply industrial sludge to natural soils. Sewage sludge should be incinerated, contained or reclaimed.
Conditions and measures related to sewage treatment plant	: Estimated substance removal from wastewater via domestic sewage treatment (%): (%) : 0.31 Assumed domestic sewage treatment plant flow (m ³ /d) : 2.00E+03 Maximum allowable site tonnage (M _{Safe}) based on release following total wastewater treatment removal (kg/day) : 28 448
Conditions and measures related to external treatment of waste for disposal	: External treatment and disposal of waste should comply with applicable local and/or national regulations.
Conditions and measures related to external recovery of waste	: External recovery and recycling of waste should comply with applicable local and/or national regulations.

Contributing scenario controlling worker exposure for 2: General measures applicable to all activities

Concentration of substance in mixture or article	: Covers percentage substance in the product up to 100% (unless stated differently).
Physical state	: Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure.
Frequency and duration of use/exposure	: Covers daily exposures up to 8 hours (unless stated differently).
Other conditions affecting workers exposure	: Assumes use at not more than 20°C above ambient temperature. unless stated differently. Assumes a good basic standard of occupational hygiene has been implemented.
Conditions and measures related to personal protection, hygiene and health evaluation	
Advice on general occupational hygiene	: Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN 374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent/minimise exposures and to report any skin problems that may develop. Other skin protection measures such as impervious suits and face shields may be required during high dispersion activities which are likely to lead to substantial aerosol release, e.g. spraying. Avoid direct eye contact with product, also via contamination on hands.
Personal protection	: Use suitable eye protection.

Contributing scenario controlling worker exposure for 3: Material transfers Manual

Frequency and duration of use/exposure	: Avoid carrying out activities involving exposure for more than 1 hour per day.
---	--

Contributing scenario controlling worker exposure for 4: Material transfers Automated process with (semi) closed systems

Ventilation control measures	: Ensure material transfers are under containment or extract ventilation.
-------------------------------------	---

Contributing scenario controlling worker exposure for 5: Roller, spreader, flow application

Ventilation control measures	: Provide extract ventilation to points where emissions occur.
-------------------------------------	--

Contributing scenario controlling worker exposure for 6: Spraying

Ventilation control measures : Carry out in a vented booth or extracted enclosure.

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection : Wear chemical-resistant gloves (tested to EN374) in combination with specific activity training.

Contributing scenario controlling worker exposure for 7: Treatment of articles by dipping and pouring

Ventilation control measures : Provide a good standard of general or controlled ventilation (10 to 15 air changes per hour)

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection : Wear chemical-resistant gloves (tested to EN374) in combination with intensive management supervision controls.

Contributing scenario controlling worker exposure for 8: Equipment cleaning and maintenance

Technical conditions and measures at process level (source) to prevent release : Retain drain-downs in sealed storage pending disposal or for subsequent recycle.

Engineering controls : Drain down system prior to equipment break-in or maintenance.

Ventilation control measures : Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection : Wear chemical-resistant gloves (tested to EN374) in combination with specific activity training.

Contributing scenario controlling worker exposure for 9: Storage

Engineering controls : Store substance within a closed system.

Section 3 - Exposure estimation and reference to its source

Website: : Not applicable.

Exposure estimation and reference to its source - Environment: 1:

Exposure assessment (environment): : Used ECETOC TRA model.

Exposure estimation and reference to its source : Not available.

Exposure estimation and reference to its source - Workers: 2: General measures applicable to all activities

Exposure assessment (human): : The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.

Exposure estimation and reference to its source : Not available.

Exposure estimation and reference to its source - Workers: 3: Material transfers Manual

Exposure assessment (human): : The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.

Exposure estimation and reference to its source : Not available.

Exposure estimation and reference to its source - Workers: 4: Material transfers Automated process with (semi) closed systems

Exposure assessment (human): : The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.

Exposure estimation and reference to its source : Not available.

Exposure estimation and reference to its source - Workers: 5: Roller, spreader, flow application

Exposure assessment (human):	: The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.

Exposure estimation and reference to its source - Workers: 6: Spraying

Exposure assessment (human):	: The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.

Exposure estimation and reference to its source - Workers: 7: Treatment of articles by dipping and pouring

Exposure assessment (human):	: The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.

Exposure estimation and reference to its source - Workers: 8: Equipment cleaning and maintenance

Exposure assessment (human):	: The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.

Exposure estimation and reference to its source - Workers: 9: Storage

Exposure assessment (human):	: The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.

Section 4 - Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Environment	: Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Further details on scaling and control technologies are provided in SPERC factsheet. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required. For further information see www.atiel.org/reach/introduction .
Health	: Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. For further information see www.atiel.org/reach/introduction .

Additional good practice advice beyond the REACH CSA

Environment	: Not available.
Health	: Not available.

Annex to the extended Safety Data Sheet (eSDS)

Professional

Identification of the substance or mixture

Product definition : Mixture
Code : 36601
Product name : COPAL OGL 2

Section 1 - Title

Short title of the exposure scenario : Use of lubricants and greases in open systems - Professional

List of use descriptors : **Identified use name:** Use of lubricants and greases in open systems - Professional
Process Category: PROC01, PROC02, PROC08a, PROC10, PROC11, PROC13
Sector of end use: SU22
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC08a, ERC08d

Health Contributing scenarios : **General measures applicable to all activities**
Material transfers Manual - PROC08a
Roller, spreader, flow application - PROC10
Spraying - PROC11
Treatment of articles by dipping and pouring - PROC13
Equipment cleaning and maintenance - PROC08a
Storage - PROC01, PROC02

Processes and activities covered by the exposure scenario : Covers use of lubricants and greases in open systems, including application of lubricant to work pieces or equipment by dipping, brushing or spraying (without exposure to heat), e.g. mold releases, corrosion protection, slideways. Includes associated product storage, material transfers, sampling and maintenance activities.

Section 2 - Exposure controls

Contributing scenario controlling environmental exposure for 1:

ATIEL-ATC SPERC 8.Cp.v1

Amounts used : Volume manufactured/imported (tonnes/year) : 1.92E+02
Fraction of EU tonnage used in region : 0.1
Fraction of Regional tonnage used locally : 0.1

Frequency and duration of use : Emission days (days per year) : 365

Environment factors not influenced by risk management : Local freshwater dilution factor : 10
Local marine water dilution factor : 100

Other conditions affecting environmental exposure : Negligible wastewater emissions as process operates without water contact.
Release fraction to air from process (after typical onsite RMMs consistent with EU Solvent Emissions Directive requirements) : 1.00E-04
Release fraction to wastewater from process (after typical onsite RMMs and before (municipal) sewage treatment plant): 5.00E-04
Release fraction to soil from process (after typical onsite RMMs): 1.00E-03

Technical conditions and measures at process level (source) to prevent release : Common practices vary across sites thus conservative process release estimates used.

Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil : Prevent discharge of undissolved substance to or recover from onsite wastewater.

Organisational measures to prevent/limit release from site	: Do not apply industrial sludge to natural soils. Sewage sludge should be incinerated, contained or reclaimed.
Conditions and measures related to sewage treatment plant	: Estimated substance removal from wastewater via domestic sewage treatment (%): (%) : 0.31 Assumed domestic sewage treatment plant flow (m³/d) : 2.00E+03 Maximum allowable site tonnage (M _{Safe}) based on release following total wastewater treatment removal (kg/day) : 253
Conditions and measures related to external treatment of waste for disposal	: External treatment and disposal of waste should comply with applicable local and/or national regulations.
Conditions and measures related to external recovery of waste	: External recovery and recycling of waste should comply with applicable local and/or national regulations.

Contributing scenario controlling worker exposure for 2: General measures applicable to all activities

Concentration of substance in mixture or article	: Covers percentage substance in the product up to 100% (unless stated differently).
Physical state	: Liquid, vapour pressure < 0.5 kPa at Standard Temperature and Pressure.
Frequency and duration of use/exposure	: Covers daily exposures up to 8 hours (unless stated differently).
Other conditions affecting workers exposure	: Assumes use at not more than 20°C above ambient temperature. unless stated differently. Assumes a good basic standard of occupational hygiene has been implemented.
Conditions and measures related to personal protection, hygiene and health evaluation	
Advice on general occupational hygiene	: Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN 374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent/minimise exposures and to report any skin problems that may develop. Other skin protection measures such as impervious suits and face shields may be required during high dispersion activities which are likely to lead to substantial aerosol release, e.g. spraying. Avoid direct eye contact with product, also via contamination on hands.
Personal protection	: Use suitable eye protection.

Contributing scenario controlling worker exposure for 3: Material transfers Manual

Frequency and duration of use/exposure	: Avoid carrying out activities involving exposure for more than 1 hour per day.
---	--

Contributing scenario controlling worker exposure for 4: Roller, spreader, flow application

Frequency and duration of use/exposure	: Avoid carrying out activities involving exposure for more than 4 hours per day.
Ventilation control measures	: Provide a good standard of general or controlled ventilation (5 to 15 air changes per hour) Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan.
Conditions and measures related to personal protection, hygiene and health evaluation	
Personal protection	: Wear chemical-resistant gloves (tested to EN374) in combination with specific activity training.

Contributing scenario controlling worker exposure for 5: Spraying

Frequency and duration of use/exposure	: Avoid carrying out activities involving exposure for more than 1 hour per day.
Ventilation control measures	: Provide a good standard of general or controlled ventilation (5 to 15 air changes per hour) Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan.
Conditions and measures related to personal protection, hygiene and health evaluation	
Personal protection	: Wear suitable coveralls to prevent exposure to the skin. Wear chemical-resistant gloves (tested to EN374) in combination with specific activity training.

Respiratory protection	: Wear a respirator conforming to EN140 with type A/P2 filter or better.
Contributing scenario controlling worker exposure for 6: Treatment of articles by dipping and pouring	
Ventilation control measures	: Provide a good standard of general or controlled ventilation (5 to 15 air changes per hour) Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan.
Contributing scenario controlling worker exposure for 7: Equipment cleaning and maintenance	
Frequency and duration of use/exposure	: Avoid carrying out activities involving exposure for more than 4 hours per day.
Technical conditions and measures at process level (source) to prevent release	: Retain drain-downs in sealed storage pending disposal or for subsequent recycle.
Engineering controls	: Drain down system prior to equipment break-in or maintenance.
Ventilation control measures	: Provide a good standard of general or controlled ventilation (5 to 15 air changes per hour) Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan.
Contributing scenario controlling worker exposure for 8: Storage	
Engineering controls	: Store substance within a closed system.

Section 3 - Exposure estimation and reference to its source

Website:	: Not applicable.
Exposure estimation and reference to its source - Environment: 1:	
Exposure assessment (environment):	: Used ECETOC TRA model.
Exposure estimation and reference to its source	: Not available.
Exposure estimation and reference to its source - Workers: 2: General measures applicable to all activities	
Exposure assessment (human):	: The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.
Exposure estimation and reference to its source - Workers: 3: Material transfers Manual	
Exposure assessment (human):	: The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.
Exposure estimation and reference to its source - Workers: 4: Roller, spreader, flow application	
Exposure assessment (human):	: The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.
Exposure estimation and reference to its source - Workers: 5: Spraying	
Exposure assessment (human):	: The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.

Exposure estimation and reference to its source - Workers: 6: Treatment of articles by dipping and pouring

Exposure assessment (human):	: The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.

Exposure estimation and reference to its source - Workers: 7: Equipment cleaning and maintenance

Exposure assessment (human):	: The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.

Exposure estimation and reference to its source - Workers: 8: Storage

Exposure assessment (human):	: The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.

Section 4 - Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Environment	: Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Further details on scaling and control technologies are provided in SPERC factsheet. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required. For further information see www.atiel.org/reach/introduction .
Health	: Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. For further information see www.atiel.org/reach/introduction .

Additional good practice advice beyond the REACH CSA

Environment	: Not available.
Health	: Not available.