

CIRKAN C



Lubrication



High quality oils for moving parts.

APPLICATIONS

Loss lubrication
Flushing

- **CIRKAN C** oils are pure mineral oils with appropriate viscosities for loss lubrication of:
 - moving parts
 - swivels
 - journals
 - chains
- **CIRKAN C** oils are suitable for use as a flushing fluid for maintenance of machine parts such as flushing of hydraulic circuits to remove contamination.

SPECIFICATIONS

- International specifications
- ISO 11158 Category HH
 - ISO 6743/4 Category HH

ADVANTAGES

- High natural viscosity index
- Compatible with seals
- High ignition point
- Benefits from advanced refining: almost transparent in appearance.

TYPICAL CHARACTERISTICS	METHODS	UNITS	CIRKAN C							
			32	46	68	100	150	220	320	460
Density at 15 °C	ISO 3675	kg/m ³	870	877	884	886	890	897	900	900
Viscosity at 40 °C	ISO 3104	mm ² /s	32	46	68	100	150	220	320	460
Viscosity at 100 °C	ISO 3104	mm ² /s	5.7	7.1	9.1	11.3	15.3	19.2	25	30.5
Viscosity index	ISO 2909		100	99	97	96	96	96	96	96
Open cup flash point	ISO 2592	°C	210	230	240	250	260	260	270	270
Pour point	ISO 3016	°C	- 12	- 12	- 6	- 6	- 6	- 6	- 6	- 6

Above characteristics are mean values given as an information. This lubricant used as recommended and for the application for which it has been designed does not present any particular risk. A material safety data sheet conforming to the regulations in use in the E.C. can be obtained from your local commercial adviser or downloaded from www.quick-fds.com.

TOTAL LUBRIFIANTS
Lubricants for Industry
24-11-2014
CIRKAN C 32-460 1/1

