



CHILLTAP CHILLED

Order Code CT1001-1

Zip ChillTap under-bench chilled filtered drinking water appliance.

Manufacturing Code	CT12XCXR2AU
--------------------	-------------

Capacity	Residential
----------	-------------



Tap	Carafe Tap single lever
-----	-------------------------

Water Pressure	150kPa- 700kPa
----------------	----------------

Water Connection	12.7mm BSP
------------------	------------

Water Valves	intergrated 500kPa pressure limiting valve and Dual Check valve
--------------	---

Power Rating	0.16kW
--------------	--------

Dimensions	335mm x 280mm x 475mm
------------	-----------------------

Warranty	12 months
----------	-----------

Installation Requirements

- '1. Installation and connection of your Zip ChillTap must be carried out by a qualified person, observing national and local regulations.
2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1.5 metres of the product.
3. ChillTap is air-cooled so discrete cabinetry cut-outs are required for ventilation.
4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service.
5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit.
6. Installation by Zip Professional Service can be arranged with a phone call or through www.zipwater.com'