

linelube Engine Oil Semi-Synthetic 5W-30

Product Description

Semi-Synthetic 5W-30 is manufactured from a balanced blend of top-quality mineral and synthetic base stocks, producing high quality engine oil with the properties of semisynthetic technology. Its naturally higher lubricity offers lower internal friction for reduced engine wear. Its low viscosity offers improved flow rates and hydraulic tappet performance during cold start and engine idling, a problem with many higher viscosity oils. It offers excellent stay in grade performance for today's modern multi-valve engines.

Features & Benefits

- Extended drain capability
- Excellent low temperature stability for improved flow rates
- Improved fuel efficiency
- Semi-synthetic formulation

Applications

Semi-Synthetic 5W-30 is suitable for normally aspirated and turbocharged, petrol and diesel vehicles particularly modern vehicles. It meets many of the latest Ford requirements. It is miscible with all synthetic and mineral based engine oils.

Specifications

- **ACEA:** A1, B1
- **API:** SL/SJ/CF
- **Ford:** WSS M2C 913-B
- **BMW:** LL-FE-01
- **Opel:** Pass
- **ILSAC:** GF-2

Typical Test Data

Specific Gravity @ 15.6°C	0.884
Kinematic Viscosity: @ 100°C (cSt)	11.04
Kinematic Viscosity: @ 40°C (cSt)	71.01
Viscosity Index	145
Pour Point °C	-44
Flash Point COC °C	212
Total Base Number (mg KOH/g)	9.20

Health & Safety

For health and safety information please refer to the relevant health & safety data sheet on our website. The contents of this data sheet is given in good faith but without warranty.