

linelube Super Universal Tractor Oil 15W-30

Product Description

linelube Super Universal Tractor Oil (SUTO) is designed to cover virtually all the lubrication requirements of agricultural machinery including farm tractors. It provides excellent high and low temperature stability, high standards of engine cleanliness and good oxidation resistance. Its natural high lubricity offers lower internal friction for reduced engine wear.

Features & Benefits

- Meets a range of OEM requirements
- Helps reduce wet brake noise or “squawk”
- Suitable for many agricultural machinery requirements
- API diesel & petrol engine specifications requirements

Applications

linelube Super Universal Tractor Oil is suitable for use in both normally aspirated and turbocharged diesel and petrol engines, transmission systems including those fitted with wet brakes, hydraulic systems, oil immersed clutches, gearboxes and final drives. It is suitable for agricultural, plant and off-road machinery.

Specifications

- **Massey Ferguson:** M1139, M1144, M1145
- **API:** CE/SF (Engine), GL-4 (Gears)
- **Ford:** M2C 86A, 134B/C, 159B
- **Mercedes Benz:** 227.1
- **CCMC:** D4/G2
- **John Deere:** J20A
- **ZF:** TE ML 06B, 06L, 07B, 07D
- **Caterpillar:** TO-2

Typical Test Data

Kinematic Viscosity @ 40°C	85.04
Kinematic Viscosity @ 100°C	11.49
Viscosity Index	125
Pour Point (°C)	-31
Flash Point (°C)	218
Total Base Number (mg KOH/g)	10.38

Health & Safety

For health and safety information please refer to the relevant health & safety data sheet on our website. The contents of this data sheet is given in good faith but without warranty.