

Enduris[™] Roof Coating



QUICK AND EASY TO USE:

1. Clean

E



2. Prep















Coat & Seal. Protect & Restore.

Extend building lifespan, improve performance and reduce maintenance costs, with advanced, 100% silicone sealants and coatings.

Advantages Of Enduris High Solids Roof Coating


- Easy, one coat application
- Primerless adhesion to most substrates
- Best-in-class elongation
- Superior UV resistance
- · Abrasion resistance
- Severe weather resistance
- · Unaffected by standing water
- Ultra-low VOC
- Versatile temperature application range: 0°-120° F (-17°C-49°C); call if substrate> 120° F (49°C)
- Environmentally responsible; solvent free

Warranty:

- 3rd party independent warranty inspection
- Efficient warranty administration
- Up to 20 years available



Silicone Roof Coating Colors:



Enduris 3500 series roof coating is currently available in nominal 5 gallon plastic pails and 55 gallon chimed steel drums.

Enduris Roof Coating Restores and Extends the Life of:

- TPO
 SBS Granulated
- EPDM
 APP
- Metal
 Modified Bitumen
- AsphaltHypalomTM
- PVC
 Concrete

Contact us for application to additional substrates

Use the practical alternative on your next project. **Contact us**















THE MATERIALS, PRODUCTS, AND SERVICES OF MOMENTIVE PERFORMANCE MATERIALS INC. AND ITS SUBSIDIARIES AND AFFILIATES (COLLECTIVELY "SUPPLIER"), ARE SOLD SUBJECT TO SUPPLIER'S STANDARD CONDITIONS OF SALE, WHICH ARE INCLUDED IN THE APPLICABLE DISTRIBUTOR OR OTHER SALES AGREEMENT, PRINTED ON THE BACK OF ORDER ACKNOWLEDGMENTS AND INVOICES, AND AVAILABLE UPON REQUEST. ALTHOUGH ANY INFORMATION, RECOMMENDATIONS, OR ADVICE CONTAINED HEREIN IS GIVEN IN GOOD FAITH, SUPPLIER MAKES NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, (i) THAT THE RESULTS DESCRIBED HEREIN WILL BE OBTAINED UNDER END-USE CONDITIONS, OR (ii) AS TO THE EFFECTIVENESS OR SAFETY OF ANY DESIGN INCORPORATING ITS PRODUCTS, MATERIALS, SERVICES, RECOMMENDATIONS, OR ADVICE. EXCEPT AS PROVIDED IN SUPPLIER'S STANDARD CONDITIONS OF SALE, SUPPLIER AND ITS REPRESENTATIVES SHALL IN NO EVENT BE RESPONSIBLE FOR ANY LOSS RESULTING FROM ANY USE OF ITS MATERIALS, PRODUCTS, OR SERVICES DESCRIBED HEREIN. Each user bears full responsibility for making its own determination as to the suitability of Supplier's materials, services, products, materials, or services will be safe and suitable for or waive any provision of Supplier's standard Conditions of Sale or this Disclaimer, unless any such modification is specifically agreed to in a writing signed by Supplier. No statement contained herein concerning a possible or suggested use of any material, product, service, or design is intended, or should be construed, to grant any license under any patent or other intellectual property right of Suppler's services will be a recommendation for the use of such material, product, service, or design in the infringement of any patent or other intellectual property right.

Hypalon is a trademark of DuPont USA. Item #: SEL-SCM3500PRO-EN

 ${\sf GE}\ is\ a\ registered\ trademark\ of\ General\ Electric\ Company\ and\ is\ used\ under\ license\ by\ Momentive\ Performance\ Materials\ Inc.$

*Enduris is a trademark of Momentive Performance Materials Inc. Copyright 2023 Momentive Performance Materials Inc. All rights reserved