



GE TOSSEAL 83 AMB
One Part Oxime Silicone Sealant
(Antimicrobial and antifungal grade)

ENSURES A CLEAN, LONG-LASTING SEAL IN KITCHEN AND BATH WITH GE TOSSEAL 83 AMB SEALANT

EASY TO APPLY, QUICK TO CURE,
AND REMAINS RESISTANT TO MOLD
AND MILDEW GROWTH



GE TOSSEAL 83 AMB sealant's 100% silicone formula offers excellent adhesion and long-term resistance to water intrusion and extreme temperatures. It is ideal for applications in bathrooms and kitchens, providing a silicone seal that won't crack, separate, or dry out, even after years of exposure.



- 100% waterproof seal
- Fast cure Oxime sealant, suitable for broader substrates
- Excellent adhesion and elasticity
- 12 times Mildew Resistance Performance @ GB/T 1741
- Low VOC (35g/L) @ GB 18583
- 18 months total shelf life
- JPN F4 Star Certificate
- Available in 7 colors

Decades of reliable performance.

WATERPROOF.

Quickly attains water-resistant properties and provides excellent longterm resistance to natural weathering, humidity and high & low temperatures.

EXCEPTIONAL DURABILITY.

High-performance 100% silicone formula expands and contracts for a long, resilient life—and won't crack or degrade. Fungicide in the cured sealant resists both mold and mildew. Once cured, remains elastic in temperatures from -55°F (-48°C) to 300°F (149°C), and withstands short-term, intermittent exposure up to 400°F (204°C).

OUTSTANDING ADHESION.

TOSSEAL 83 AMB is able to bond to many common substrates and finishes, including glass, ceramic tiles, porcelain, painted surfaces, some plastics, cultured marble, polished granites and marbles and many composite materials including fiberglass.

EASY TO USE.

The material can be easily gunned and tooled under hot or cold conditions. Removable cartridge nozzle that can be transferred from one cartridge to the next for a consistent bead size. Non-sag paste makes application possible on horizontal, vertical or overhead surfaces. Wide application temperature range from 40°F to 122°F. Product has a work life of five to 10 minutes, with a tack free time of 30 minutes and full cure time of 24 to 48 hours.

AVAILABLE IN SEVEN COLORS:



Ready to start your next project?

CONTACT US: siliconeforbuilding.com

THE MATERIALS, PRODUCTS, AND SERVICES OF MOMENTIVE PERFORMANCE MATERIALS INC. AND ITS SUBSIDIARIES AND AFFILIATES (COLLECTIVELY "SUPPLIER"), ARE SOLD SUBJECT TO SUPPLIER'S STANDARD CONDITIONS OF SALE, WHICH ARE INCLUDED IN THE APPLICABLE DISTRIBUTOR OR OTHER SALES AGREEMENT, PRINTED ON THE BACK OF ORDER ACKNOWLEDGMENTS AND INVOICES, AND AVAILABLE UPON REQUEST. ALTHOUGH ANY INFORMATION, RECOMMENDATIONS, OR ADVICE CONTAINED HEREIN IS GIVEN IN GOOD FAITH, SUPPLIER MAKES NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, (I) THAT THE RESULTS DESCRIBED HEREIN WILL BE OBTAINED UNDER END-USE CONDITIONS, OR (II) AS TO THE EFFECTIVENESS OR SAFETY OF ANY DESIGN INCORPORATING ITS PRODUCTS, MATERIALS, SERVICES, RECOMMENDATIONS, OR ADVICE, EXCEPT AS PROVIDED IN SUPPLIER'S STANDARD CONDITIONS OF SALE. SUPPLIER AND ITS REPRESENTATIVES SHALL IN NO EVENT BE RESPONSIBLE FOR ANY LOSS RESULTING FROM ANY USE OF ITS MATERIALS, PRODUCTS, OR SERVICES DESCRIBED HEREIN. Each user bears full responsibility for making its own determination as to the suitability of Supplier's materials, services, recommendations, or advice for its own particular use. Each user must identify and perform all tests and analyses necessary to assure that its finished parts incorporating Supplier's products, materials, or services will be safe and suitable for or waive any provision of Supplier's standard Conditions of Sale or this Disclaimer, unless any such modification is specifically agreed to in a writing signed by Supplier. No statement contained herein concerning a possible or suggested use of any material, product, service, or design is intended, or should be construed, to grant any license under any patent or other intellectual property right of Supplier covering such use or design, or as a recommendation for the use of such material, product, service, or design in the infringement of any patent or other intellectual property right.

GE is a registered trademark of General Electric Company and is used under license by Momentive Performance Materials Inc. Copyright 2012-2023 Momentive Performance Materials Inc. All rights reserved.