







VPL 150

The VPL 150 lift is a wheelchair lift also known as a low rise platform lift which provides internal or external vertical travel up to three meters. Our wheelchair lifts can accommodate changes in level from 600mm to 3000mm. In commercial and domestic environments, this lift is an ideal solution to a fully enclosed platform lift. This lift is available in a range of platform sizes.

- MODERN LIGHTWEIGHT DESIGN
- STAINLESS STEEL CONSTRUCTION
- LOW SPACE REQUIREMENTS
- HIGH LEVEL OF SECURITY
 - SIMPLE TO USE
- NO PIT REQUIRED
- SIMPLE TO INSTALL AND EASY TO SERVICE
- OVERALL LOW MAINTENANCE AND RUNNING COSTS





INDOORS OR OUTDOOR USAGE

This energy efficient wheelchair platform lift is perfectly suited to both indoor and outdoor usage, with robust and stylish finishes ensuring it is reliable, easy to clean and durable over time. Dual controls and a post mounted call station make this super simple to operate.

VLP 150 is specifically designed for projects with very little alterations to existing structures desired. As it has an open top design, it looks great. The brushed stainless steel finish is as standard. The lift provides a safe and easy way to access space where stairs would otherwise restrict the mobility of wheelchair users.

PAGE 6 PAGE 7



COMFORTABLE OPERATION

The smooth start and stop performance ensure that travel is a pleasant experience; our lifts are low-maintenance and their reliability has been proven in everyday life. The operation of the lift is completely battery-operated; the batteries are recharged at the final stations. The lift will automatically switch off after a period of time without use in order to prevent a deep discharge occurring if it has not been properly parked.

The modern touch sensitive membrane controls ensure that even people with reduced physical abilities and motor skills can operate our lifts.

SPECIFICATIONS

User group Ambulant and wheelchair users

Suitability For internal or external use(corrosion resistant)

Travel From 500 mm up to 3000 mm

Number of stops

Maximum capacity 400 kg

Platform size 1100 x 1400 (standard)

Travel speed 0.15 m/s

Cabin height 1100 mm

Gate 950 x 1100 mm

Drive type Bel

Power 220-240 V, 1 phase, 25A; 380-400 V, 3 phase, 20A, 50 Hz

Lighting Controls illuminated

Safety edge Safety edge-under platform proximity sensors

Handrail Integrated to lift cabin (on both sides)

Machine room Integral to guide rails

Floor Anti slip diamond plate

Finish Brushed stainless steel



OPTIONS

Platform Sizes 800 x 1400mm

900 x 1400mm 1000 x 1400mm

Gate Automatic upper gate

Automatic lower gate

Auto closers

Control Post mounted call station

Configurable control side
Dual control on the platform
Auto dialer on the platform

Full braille controls

Finish Painted in any RAL color



PSEMIES

BOOK A NO OBLIGATION CONSULTATION

Start a conversation with Premier today, we will asses your requirements, talk through our available options and ensure we meet your lift solution needs.



0203 355 0523 - London

0161 820 3716 - Manchester



info@premierliftgroup.co.uk



www.premierliftgroup.co.uk