



SUPER S

SUPER S				
ENGINE				
Manufacturer	Kawasaki FS, FT & FX series			
HP	36" deck: 15HP - FS541, 19HP - FX600			
	48" deck: 22HP - FX691			
	52" deck: 22HP - FT691			
	52", 60" deck: 27HP - FX850, 29.5HP - FX850 EFI (Per SAE J1995)			
Displacement	603cc - 852cc			
Cooling	Air cooled			
Air Cleaner	FX: Heavy duty air canister FS: Oval FT: Vortical			
Engine Warranty	3 year			
DRIVE SYSTEM				
Type	Dual hydrostatic			
Pumps	36" deck: Hydro-Gear 10cc 48", 52", 60" deck: Hydro-Gear 12cc			
Wheel Motors	36" deck: Parker TL 48", 52", 60" deck: Parker TL			
Speed	36": Up to 8 mph. 48", 52", 60": Up to 9 mph.			
Parking Brakes	Hand operated drum brakes			
DECKS				
Cutting Width	Side discharge: 36", 48", 52", 60"			
Cutting Heights	1.5"- 5.5"			
Deck Lift	Hand operated.			
Depth	5.5"			
Blades	36": 2 48", 52", 60": 3			
Blade Length	36" deck: 17.86" 48" deck: 16.50" 52" deck: 17.86" 60" deck: 20.50"			
Blade Tip Speed	36": 18,700 48": 18,500 52": 17,700 60": 18,400			
Spindles	Ductile cast iron with steel shafts and sealed ball bearings			
Drive	Electric PTO clutch			
Construction	7 ga. Fabricated w/ 7 ga. wrappers			
Spindle Mounts	36": 7ga. with 11 ga. doubler 48", 52", 60": 7 ga. with 7 ga. doubler			
Impact/Trim Areas	11 ga. formed channel with rolled edge			
CONSTRUCTION				
Frame	36": 1.5" x 2" steel tubing 48" 52" 60": 1.5" x 3" steel tubing			
Engine Plate	7 ga. with 11 ga. jackshaft doubler			
Operator Platform	7 ga. with embossed tread pattern			
Front Axle	Fabricated with tapered roller bearings			
Front Caster Wheels	Tapered wheel bearings and debris cap			
Front Caster Forks	Fabricated 3/8" steel			
Operator Pad	Bolstered operator pad			
GENERAL				
Fuel Capacity	36": 6.5 gallons 48", 52", 60": 7.3 gallons			
Front Tire	36" 11 x 4 - 5 48", 52": 13 x 5 - 6 60": 13 x 6.5 - 6			
Drive Tire	36": 20 x 8 - 10 48", 52": 24 x 9.5 - 12 60": 24 x 12 - 12			
DIMENSIONS				
Weight	36": 907 lbs 48": 1144 lbs 52": 1153 - 1182 lbs 60": 11207 - 1232 lbs			
Height	47"			
Length	36": 63.5" 48", 52": 68" 60": 70.75"			
Width w/Chute Up	36": 39" 48": 49.3" 52": 52.8" 60": 61.7"			
Tire Width	36": 36.3" 48", 52": 45.8" 60": 49"			
Trim Side	36": 0" 48": 1.5" 52": 3.5" 60": 5.6"			
PRODUCTIVITY*				
Acres Per Hour	36": 2.33 48": 3.49 52": 3.79 60": 4.36			



AVAILABLE DECK SIZES

36"- 60"

* Number based on 80% efficiency. This rating is to account for actual mowing conditions including overlapping, turning and terrain. ** Specifications are subject to change without notice.

SUPER S



ACCESSORIES

- ▶ Mulch kit
- ▶ Mesh side bagger (3 bushels)
- ▶ Metal side bagger (3.5 bushels)
- ▶ Light kit
- ▶ Stripe kit
- ▶ Trash basket
- ▶ Cup holder

THE SUPER S STAND-ON MOWER

SUPER S

- ✓ **Compact Stance**
Perfect for tight spaces and for trailering from job-to-job
- ✓ **Service Friendly Design**
Designed to make maintenance and service fast and easy.
- ✓ **SmoothTrak™ Steering**
Precision control to help trim and maneuver easily around obstacles.
- ✓ **VX Deck**
Fabricated 7 ga. steel engineered for extreme vacuum enhancing performance and cut quality.
- ✓ **Deck Options**
36", 48", 52" and 60"



LIMITED WARRANTY

5 YEAR | 1200 HOUR

FIRST 2 YEARS NO HOUR LIMIT