



# DIESEL Z



COMMERCIAL



# DIESEL Z

LIMITED WARRANTY  
**5 YEAR**  
**1200 HOURS**  
FIRST 2 YEARS NO HOUR LIMIT

## FABRICATED FRAME FOR DURABILITY

1.5" x 3.0" steel frame making it tough and durable.

## FOOT-OPERATED DECK LIFT

Easily adjust the deck height between 1"-5.5" with your foot.

## VX4™ DECK

Fabricated 7 GA steel deck engineered to move more grass at high speeds while maintaining cut-quality.

## PATENTED BELT DRIVE SYSTEM

Helps provide long life to this machine.

## SMOOTHTRAK STEERING

Precision control to help trim and maneuver easily around obstacles. Other brands have sensitive steering arms causing sudding and jerky movements.

## 13M SUSPENSION SEAT

High-back seat with adjustable armrests and 3-inch travel range.

## DUAL FUEL TANKS

14.4 gallon capacity with mechanical fuel gauges.

## COMMERCIAL-GRADE ENGINES

25 HP Perkins engines backed by 5-year limited warranties.

## COMMERCIAL-GRADE TORQUE

Driven by Tandem 21 cc Hydro-Gear® pumps



## DECK SIZE / ENGINE

60"	25 HP*	Perkins®
60" RD	25 HP*	Perkins®
72"	25 HP*	Perkins®
72" RD	25 HP*	Perkins®

# MORE FEATURES



## VX4® DECK

Fabricated 7 GA steel deck engineered to move more grass at high speeds while maintaining cut-quality.



## 13M SUSPENSION SEAT

High-back seat with adjustable armrests and 3-inch travel range.



## PATENTED BELT DRIVE SYSTEM

Helps provide long life to this machine.

## ACCESSORIES

(Each sold separately)

- Semi pneumatic front tires
- Steering lever extension kit
- Single/dual anti-scalp wheels
- Flex Forks®
- Mulch kit
- Light kit
- Stripe kit
- Sand kit
- Beacon kit
- Flasher kit
- Electric deck lift
- Hitch kit
- Michelin® X® Tweel® Turf



# DIESEL Z<sup>®</sup>

<b>ENGINE</b>	
Manufacturer	Perkins
HP	25 HP (Per SAE J1995)
Displacement	1,130 cc
Cooling	Liquid cooled, direct-drive, mechanical cooling fan
Air Cleaner	Heavy Duty Canister
Engine Warranty	3 year
<b>DRIVE SYSTEM</b>	
Type	Dual hydrostatic
Pumps	Tandem 21 cc Hydro-Gear pumps
Wheel Motors	Parker TG
Hydraulic Lines	Stanless steel Parker Seal-Lok technology
Hydraulic Capacity	Oil cooler with 8" fan
Reservoir Capacity	1.3 gallons
Speed	Up to 11.5 MPH
Parking Breaks	Integrated with steering levers
<b>DECKS</b>	
Cutting Width	Side discharge: 60", 72" • Rear-discharge: 60", 72"
Cutting Heights	1"-5.5"
Deck Lift	Foot operated
Depth	5.5"
Blades	3
Blade Length	60" deck: 20.50" • 72" deck: 24.5"
Blade Tip Speed	60" deck: 18,200 • 72" deck: 18,800
Spindles	Ductile cast iron with steel shaft and sealed ball bearings
Drive	Electric PTO clutch
Construction	7 ga welded steel
Spindle Mounts	Reinforced 7 GA stamped disc
Impact/Trim Areas	Front of deck: 11 GA formed bump bar • Side of deck: 1.5" x .375" steel bar
<b>CONSTRUCTION</b>	
Frame	1.5" x 3" steel tubing
Front Axle	Fabricated w/ sealed ball bearings
Front Caster Wheels	Tapered wheel bearings and debris cap
Front Caster Forks	Fabricated 1/2" steel
<b>GENERAL</b>	
Seat	I3M suspension seat
Fuel Capacity	14.4 gallons
Cupholder	Yes
Front Tire	13 x 6.5-6
Drive Tire	24 x 12-12
<b>DIMENSIONS</b>	
Weight	60": 1656 LBS • 60"RD: 1766 LBS • 72": 1711 LBS • 72": 1816 LBS
Height	51", 69" w/ROPs
Length	60", 60" RD: 86.8" • 72", 72" RD: 90.4"
Width w/Chute Up	60", 60" RD: 66" • 72", 72" RD: 78"
Tire Width	56"
Trim Side	60": 3.9" • 60"RD: 3.6" • 72": 10.9" • 72"RD: 8.6"
<b>PRODUCTIVITY*</b>	
Acres Per Hour	60": 5.57 • 72": 6.68"

Specifications are subject to change without notice.

\* Number based on 80% efficiency. This rating is to account for actual mowing conditions including overlapping, turning and terrain.

\*\* Specifications are subject to change without notice.