



SURFER PRO



COMMERCIAL

SURFER PRO

LIMITED WARRANTY	3 YEAR	300 HOURS
	RESIDENTIAL	
LIMITED WARRANTY	2 YEAR	300 HOURS
	COMMERCIAL	

SEMI PNEUMATIC FRONT TIRES

11" front tires.

KAWASAKI FS541 ENGINE

15 HP*

34" & 48" DECKS

Fabricated steel decks for durability.

SMALL FOOTPRINT

Just 59" in length for easy storage and trailering.

CUT HEIGHT ADJUSTMENT

Hand operated lever and pin to easily adjust deck/cutting height.

2 GALLON FUEL CAPACITY

HYDRO-GEAR ZT-1800 TRANSMISSIONS

PARK BRAKE

Hand operated lever to set the park brake.

18" DRIVE TIRES

Helps provide stability and traction.

DECK SIZES / ENGINE

36"	15 HP*	Kawasaki® FS541
48"	15 HP*	Kawasaki® FS541



MORE FEATURES



KAWASAKI® FS ENGINE

15HP Commercial FS541 V-Twin Engine.



FABRICATED DECK

Heavy duty construction.



IDEAL FOR COMMERCIAL CONTRACTORS AND HOMEOWNERS

For tight spaces and fenced backyards with gates.

ACCESSORIES

(Each sold separately)

- Mulch Kit
- Mesh side bagger (3 bushels)
- Light kit
- Stripe kit
- Weight kit



SURFER PRO

ENGINE	
Manufacturer	Kawasaki® FS series
HP	34"/48" deck: 15 HP* – FS541 (Per SAE J1995)
Displacement	603 cc
Cooling	Air cooled
Air Cleaner	Oval canister, dual element
Engine Warranty	3 year limited
DRIVE SYSTEM	
Type	Dual hydrostatic
Drive System	Hydro-Gear® ZT-1800*
Speed	Up to 6 MPH
Parking Brakes	Hand operated
DECKS	
Cutting Width	Side discharge: 34", 48"
Cutting Heights	2" - 4.75"
Deck Lift	Hand operated.
Depth Blades	4.10"
Blade Length	34" deck: 2 • 48" deck: 3
Blade Tip	34" deck: 16.75" • 48" deck: 16.50"
Speed	34" deck: 18,900 • 48" deck: 18,600
Spindles	Aluminum w/ 3/4" shaft and triple protection sealed ball bearings
Drive	Electric PTO clutch
Construction	34" deck: Fabricated 7 GA • 48" deck: Fabricated 11 GA
Spindle Mounts	14 GA
Impact/Trim Areas	3/8" x 1" steel bar
CONSTRUCTION	
Frame	1.5" x 1.5" steel tubing
Engine Plate	7 GA
Operator Platform	Suspension
Front Axle	Fabricated w/ sealed ball bearings
Front Caster Wheels	Commercial duty steel roller bearings
Front Caster Forks	Fabricated 1/4" steel
Operator Pad	Vinyl pad
GENERAL	
Fuel Capacity	2.0 gallons
Front Tire	11 x 4 semi pneumatic
Drive Tire	34" deck: 18 x 6.5 - 8 • 48" deck: 18 x 8.5 - 8
DIMENSIONS	
Weight	34" deck: 470 lbs • 48" deck: 490 lbs
Height	48.5"
Length	58.9"
Width w/ Chute Up	34" deck: 35" • 48" deck: 48.3"
Tire Width	34" deck: 6.5" • 48" deck: 9"
Trim Side	34" deck: 0.7" • 48" deck: 5.9"
PRODUCTIVITY**	
Acres Per Hour	34" deck: 1.65 • 48" deck: 2.33

Specifications are subject to change without notice.

* As rated by the engine manufacturer.

** Number based on 80% efficiency. This rating is to account for actual mowing conditions including overlapping, turning, and terrain.

Kawasaki is a registered trademark owned by KAWASAKI JUKŌGYŌ KABUSHIKI-KAISHA. Kohler and command Pro are registered trademarks owned by Kohler Co.

Vanguard is a registered trademark owned by Briggs & Stratton Corporation. Hydro-Gear and ZT-4400 are registered trademarks owned by Hydro-Gear Limited Partnership.

Michelin, X, and Tweel are registered trademarks owned by COMPAGNIE GENERALE DES ETABLISSEMENTS MICHELIN.