

Pioneer Flood Light Series



Overview

High efficiency - Improved integrated heat dissipation
- Wider distribution - Easier assembly
Ideal for Wall Light, Sports Lighting, Wall Washer,
Security Lighting



Product Information

Product Code	Luminaire Power	Operating Power	Lumens	Light Distribution	Dimensions	Weight
EST-PFW030B-5K	30W	220V-240V	3495	110°	200x167x40mm	1.2Kg
EST-PFW050B-5K	50W	220V-240V	5615	110°	265x220x47.5mm	2.3Kg
EST-PFW080B-5K	80W	220V-240V	9293	110°	300x245x49.5mm	4.0Kg
EST-PFW200B-5K	200W	220V-240V	24600	110°	400x360x53.5mm	7.1Kg

Technical Specification

Structure

Colours	Black
Material	Aluminum Housing
Lens	Toughened Glass
IP Rating	IP65
Tilt	270° adjustable




Performance


Light Source	CREE LED
Driver	220-240V, 50/60Hz PF>0.92
Colour Temperature	5000K
Efficacy	110-125 Lm/W
Colour Rendering Index	>75Ra
Warranty	5 Years in -20 to 50°C ambient

Dimensions


EST-PFW030B




EST-PFW050B



EST-PFW080B




EST-PFW200B




Photometry


EST-PFW030B-5K



EST-PFW050B-5K



EST-PFW080B-5K



EST-PFW200B-5K

