6W LED Inground Light



Overview

The XB2 commercial inground light has an adjustable beam direction. High efficiency light source. High quality aluminium lamp fixture. Beautiful appearance and reasonable waterproof structure. Tempered glass as cover. Heat resisting and impact resistance. Supplied with plastic installation container and 0.5 m of connecting cable.



Product Information							
Product Code	Luminaire Power	Operating Power	Lumens	Light Distribution	Dimensions	Weight	
EST-XB2BGRF-4K	6W	100V-240V	324	15°	D150 x H195mm	1,2Kg	










Please note the technical information and product images are subject to change due to product upgrades and feature changes,

Technical Specification


Structure	
Colours	Dark Grey
Material	Die-Cast Aluminium Housing with 316L Front Plate
Coating	Powder Coated
IP Rating	IP67
IK Rating	IKog
Glass Pressure Capacity	Full Area=783Kg

Performance					
Light Source	OSRAM				
Driver	100-240V, 50/60Hz				
Colour Temperature	4000K				
Efficacy	54 Lm/W (68 Lm/W without honeycomb)				
Operating Current	30 mA				
Warranty	2 Years in -20 to 40°C ambient				

Photometry Dimensions













Please note the technical information and product images are subject to change due to product upgrades and feature changes,