



# SUPER Z AND HYPERDRIVE



**SUPER Z**

**HYPERDRIVE**

AVAILABLE DECK SIZES  
**54"-72" 60"-72" RD**

AVAILABLE DECK SIZES  
**60"-72" 60"-72" RD**

	SUPER Z	HYPERDRIVE
<b>ENGINE</b>		
Manufacturer	Kawasaki FX series	Vanguard Big Block™, Kawasaki FX series
HP	54", 60", 60" RD, 72" RD deck: 27HP - FX850 60", 66" & 72" deck: 35HP - FX1000 60" & 72" deck: 38.5HP - FX1000 EFI (Per SAE J1995)	60", 72" deck: 36HP - BigBlock™ 60", 60RD", 66", 72" 72"RD deck: 37HP - BigBlock™ EFI 60" & 72" deck: 35HP - FX1000 60" & 72" deck: 37HP - BigBlock™ EFI w/ Oil Guard (Per SAE J1995)
Displacement	FX850: 852cc FX1000: 999cc FX1000 EFI: 999cc	Vanguard: 993cc FX1000: 999cc
Cooling		Air cooled
Air Cleaner		Heavy Duty Canister
Engine Warranty	3 year	Kawasaki: 3 year Vanguard: 5 year
<b>DRIVE SYSTEM</b>		
Type		Dual hydrostatic
Pumps	Hydro-Gear 21cc PY	Danfoss DDC-20
Wheel Motors	Parker TG310	Parker TG280
Hydraulic Lines		Stainless Parker Seal-Loc Technology
Reservoir Capacity		3 gallons
Speed	Up to 14 mph	Up to 16 mph
Parking Brakes		Patented automatic
<b>DECKS</b>		
Cutting Width	Side discharge: 54", 60", 66", 72" Rear-discharge: 60", 72"	Side discharge: 60", 66", 72" Rear-discharge: 60", 72"
Cutting Heights		1" - 5.5"
Deck Lift		Foot operated
Depth		5.5"
Blades		3
Blade Length	54" deck: 18.50" 60" deck: 20.50" 66" deck: 22.50" 72" deck: 24.50"	60" deck: 20.50" 66" deck: 22.50" 72" deck: 24.50"
Blade Tip Speed	54"& 60": 18,600 66": 18,200 72": 18,500	60": 18,600 66": 18,200 72": 18,500 72"RD: 18,000
Spindles		Ductile cast iron with steel shaft and sealed ball bearings
Drive		Electric PTO clutch
Construction		Fabricated 7 ga.
Spindle Mounts		Reinforced 7 ga. stamped disc
Impact/Trim Areas		Front of deck: 11 ga. formed bump bar Side of deck: 1.5" x .375" steel bar
<b>CONSTRUCTION</b>		
Frame		1.5" x 3" steel tubing
Front Axle		Fabricated with tapered roller bearings
Front Caster Wheels		Mounted with tapered wheel bearings and debris cap
Front Caster Forks		Fabricated 1/2" steel
<b>GENERAL</b>		
Seat		I3M suspension seat
Fuel Capacity		11.7 gallons
Cupholder		Yes
Front Tire		13 x 6.5 - 6
Drive Tire	54": 24 x 9.5 - 12 60", 66", 72": 24 x 12 - 12	26 x 12 - 12
<b>DIMENSIONS</b>		
Weight	54": 1420 lbs 60": 1451 lbs 60" RD: 1566 lbs 66": 1516 lbs 72": 1526 lbs 72"RD: 1626 lbs	60": 1536 lbs 60"RD: 1606 lbs 66": 1551 lbs 72": 1596 lbs 72"RD: 1676 lbs
Height	46.8" 72.5 w/ ROPs	47.8" 73.5 w/ ROPs
Length	54", 60": 89" 60"RD, 66": 91.5" 72", 72"RD: 93"	60": 89" 60"RD, 66": 91.5" 72", 72"RD: 93"
Width w/Chute Up	54": 60" 60": 66" 66"&72": 72" 72": 78" 72"RD: 73.23"	60": 66" 66"&72": 72" 72": 78"
Tire Width	54", 60", 60"RD: 57" 66", 72"RD, 72": 60"	60", 60"RD: 57" 66", 72"RD, 72": 60"
Trim Side	54": 2.7 60": 3.9 66": 5 72": 9.1	60": 3.4 66": 5.2 72": 9.1
<b>PRODUCTIVITY*</b>		
Acres Per Hour	54": 6.11 60": 6.78 66": 7.46 72": 8.14	60": 7.76 66": 8.54 72": 9.31

\* Number based on 80% efficiency. This rating is to account for actual mowing conditions including overlapping, turning and terrain.  
\*\* Specifications are subject to change without notice.

# SUPER Z

## VX4 Deck

Fabricated 7 ga. steel deck engineered to move more grass at high speeds while maintaining cut-quality.

## SmoothTrak™ Steering

Precision control to help trim and maneuver easily around obstacles. You will fully understand SmoothTrak steering when you drive ours and drive theirs.

## Commercial-grade Torque

Hydro-Gear 21cc PY pumps and Parker TG310 wheel motors.

## Foot Operated Deck Lift

Easily adjust the deck height between 1" - 5.5" with your foot.

## Easy to Service

Flip-up Seat Pan, Removable Floor Pan, Vented Pulley Covers

## I3M Suspension Seat

High-back seat with adjustable armrests and 3-inch travel range.

## Kawasaki® FX Engines

FX850, FX1000, and FX1000EFI engine options.



## UPGRADES FOUND ON THE HYPERDRIVE

# HYPERDRIVE

- ✓ HyperDrive® Hydro System
- ✓ Optional Vanguard® Big Block™ Engine w/ Oil Guard (500 hour oil change)
- ✓ Danfoss DDC-20 Pumps
- ✓ Larger 26" Drive Tire
- ✓ Up to 16 mph (compared to 14 mph)

LIMITED WARRANTY  
**3** YEAR  
NO HOUR LIMIT

OR

LIMITED WARRANTY  
**5** YEAR  
500 HOUR



## HYPERDRIVE SYSTEM

Increase the life and performance of your mower with Hustler's exclusive HyperDrive system, the largest, most durable drive system in the industry. With temperature regulation and heavy-duty components, HyperDrive will keep you operating at peak performance.



9" Fan & High Capacity Oil Cooler with Hot Oil Shuttle



Large Oil Reservoir



Heavy-Duty Parker TG280 Wheel Motors



Industrial-Grade Slipper Piston Pumps

## INDUSTRY'S BEST WARRANTY

**5** YEAR  
3000 HOUR

**PUMPS AND MOTORS**

LIMITED WARRANTY  
**2** YEAR  
NO HOUR LIMIT

OR

LIMITED WARRANTY  
**5** YEAR  
500 HOUR

## ACCESSORIES

- ▶ Steering extension kit
- ▶ Electric deck lift
- ▶ Rear hitch kit
- ▶ Anti-scalp deck rear wheels
- ▶ BacVac bagger
- ▶ Semi pneumatic front tire
- ▶ 3-bag powered bagger (12 bushels)
- ▶ Flex Forks®
- ▶ Mulch kit
- ▶ Light kit
- ▶ Sand kit
- ▶ Stripe kit
- ▶ Beacon kit
- ▶ Flasher kit
- ▶ Michelin® X® Tweel® Turf