



# FASTRAK SERIES



**FASTRAK**

AVAILABLE DECK SIZES  
48" - 60" 48" - 54" RD



**FASTRAK SDX**

AVAILABLE DECK SIZES  
48" - 60"

# FASTRAK

## Fabricated Frame for Durability

1.5" x 3.0" steel frame making it one of the toughest and most durable in its class.

## Welded Steel Deck

Durable 10 ga. welded fabricated steel.

## SmoothTrak™ Steering

Precision control to help trim and maneuver easily around obstacles. You will fully understand SmoothTrak steering when you drive ours and drive theirs.

## Serviceable Commercial Grade Transmission

Hydro-Gear® ZT-3200™

## Commercial-Grade Kawasaki® FT Engine

With Vortical Air Filtration assists with cleaning debris that extends engine life.

## Easy Serviceability

Flip-up seat pan and removable floor pan and toolless removable pulley covers makes maintenance easy and simple

## Foot Operated Deck Lift

Easily adjust the deck height between 1.5" -4.5" with your foot.

## BigBite™ Tires

For smooth ride and enhanced traction.

## Premium Seat

High-back seat with suspension to shield the operator from bumps and EVC cushion to take pressure off tail bone and lower back.

LIMITED  
WARRANTY

**4** YEAR | **750** HOUR



## UPGRADES FOUND ON THE FASTRAK SDX

### FASTRAK<sup>®</sup> SDX

- ✓ **Extra High-Back Suspension Seat**  
Higher backrest and more bolstered back cushion.
- ✓ **Kawasaki<sup>®</sup> FX Engine**  
(Full Commercial Remote Canister Air Cleaner)
- ✓ **Larger Transmissions**  
(Hydro-Gear<sup>®</sup> ZT-3400™)



### ACCESSORIES

- ▶ Mulch kit
- ▶ Flex Forks<sup>®</sup>
- ▶ 2-bag powered bagger (7.2 bushels)
- ▶ Steering lever extension kit
- ▶ Light kit
- ▶ Stripe kit



LIMITED  
WARRANTY

**4** YEAR | **1000**  
HOUR

FASTRAK		FASTRAK SDX
<b>ENGINE</b>		
Manufacturer	Kawasaki FT series, KOHLER 7500 EFI	Kawasaki FX series
HP	48", 48" RD, 54", 54" RD deck: 22HP - FT691 54", 60" deck: 27HP - 7500 EFI 60" deck: 24HP - FT730 (Per SAE J1995)	48", 54" deck: 22HP - FX691 60" deck: 23.5HP - FX730 (Per SAE J1995)
Displacement	48", 48" RD, 54": 726cc FT691 54", 60": 747cc 7500 EFI 60": 726cc FT730	726cc
Cooling	Air cooled	
Engine Warranty	3 year	
<b>DRIVE SYSTEM</b>		
Type	Dual hydrostatic	
Transmission	Hydro-Gear® ZT-3200™	Hydro-Gear® ZT-3400™
Speed	Up to 8 mph	Up to 9 mph
Parking Brakes	Patented automatic	
<b>DECKS</b>		
Cutting Width	Side discharge: 48", 54", 60" Rear-discharge: 48", 54"	Side discharge: 48", 54", 60"
Cutting Heights	1.5"- 4.5"	
Deck Lift	Foot operated	
Depth	5"	
Blades	3	
Blade Length	48", 48"RD: 16.50" 54", 54"RD : 18.50" 60" deck: 20.50"	48" deck: 16.50" 54" deck: 18.50" 60" deck: 20.50"
Blade Tip Speed	48", 48"RD: 18,600 54", 54"RD: 18,900 60": 18,400	48": 18,600 54": 18,900 60": 18,400
Spindles	Aluminum with 1.0" shafts and sealed ball bearings	Aluminum with 1.0" shafts and sealed ball bearings
Drive	Electric PTO clutch	
Construction	Fabricated 10 ga.	
Spindle Mounts	Reinforced 11 ga.	
Impact/Trim Areas	11ga. formed channel with rolled edge	
<b>CONSTRUCTION</b>		
Frame	1.5" x 3" steel tubing	
Front Axle	Fabricated with sealed ball bearings	
Front Caster Wheels	Heavy duty ball bearings, greasable	
Front Caster Forks	Fabricated 3/8" steel	
<b>GENERAL</b>		
Seat	High-back suspension seat	Extra High-back suspension seat
Fuel Capacity	5 gallons	
Cupholder	Yes	
Front Tire	48", 48" RD: 13 x 5 - 6 54", 54"RD, 60": 13 x 6.5 - 6	48": 13 x 5 - 6 54", 60": 13 x 6.5 - 6
Drive Tire	48", 48" RD: 23 x 9.5 - 10 BigBite™ 54", 54"RD, 60": 23 x 11 - 10 BigBite™	48": 23 x 9.5 - 10 BigBite™ 54", 60": 23 x 11 - 10 BigBite™
<b>DIMENSIONS</b>		
Weight	48": 835 lbs 48" RD: 840 lbs 54": 845 lbs 54" RD: 860 lbs 60": 865 lbs	48": 862 lbs 54": 891 lbs 60": 916 lbs
Height	45.5"	
Length	76"	
Width w/Chute	48": 49.1" 48" RD: 48.85" 54": 55.1" 54" RD: 54.85" 60": 61.1"	48": 49.1" 54": 55.1" 60": 61.1"
Tire Width	48": 47" 54" & 60": 52"	48": 47" 54" & 60": 52"
Trim Side	48": 1" 54": 3" 60": 6"	48": 1" 54": 3" 60": 6"
<b>PRODUCTIVITY*</b>		
Acres Per Hour	48" deck: 3.10, 54" deck: 3.48, 60" deck: 3.88	48" deck: 3.49, 54" deck: 3.93, 60" deck: 4.36

\* Number based on 80% efficiency. This rating is to account for actual mowing conditions including overlapping, turning and terrain.

\*\* Specifications are subject to change without notice.