

RESIDENTIAL

BIG DOG[®]
— MOWER CO. —

STOUT

— SERIES —



STOUT

AVAILABLE DECK SIZES

48" - 60"



STOUT ^{MP}

AVAILABLE DECK SIZES

48" - 60"

STOUT

7 YEAR
INDUSTRY LEADING
LIMITED
WARRANTY
OR
500
HOUR

Fully Welded Tubular Steel Frame

The 1.50" x 3" x .120 steel frame will give you a confident durable performance no matter the conditions.

Welded Steel Deck

Durable 10 ga. welded fabricated steel deck adds durability and extends mower's life.

Precision Steering

Precision control to help trim and maneuver easily around obstacles. Other brands have sensitive steering arms causing sudden and jerky movements.

Premium Seat

Mid-back suspension seat with armrests to relieve pressure off operator's lower-back and tailbone.

KOHLER 7000 Pro Engine
23, 24hp

Easy Serviceability

Flip-up seat pan, removable floor pan and toolless removable pulley covers make cleaning and maintenance simple.

23" BigBite™ Tires

For a smooth ride and enhanced traction.

Serviceable Commercial-Grade Transmission
Hydro-Gear ZT-3100® Transmissions

IDEAL FOR
UP TO

3+
ACRES

UPGRADES FOUND ON THE STOUT MP



STOUT ^{MP}

- **High-back Suspension Seat with Armrests**

Premium seat provides all day comfort for operator

- **Larger Transmissions**

Hydro-Gear ZT-3400® Transmissions

- **Additional Horsepower**

KOHLER Confidant

- **Warranty Upgrade**

Peace of mind with a 7 year,
1000 hour warranty

- **Speed up to 9 mph**

Make quick work of large areas



ACCESSORIES

- Mulch Kit
- Flex Forks
- 2-Bag Catcher
(7.2 bushels)
- Side Steel Catcher
(4.4 cu ft)
- Side Mesh Catcher
(3 bushels)
- Stripe Kit
- High Vacuum Deck Kit
- Light Kit
- Steering Extension Kit



STOUT				STOUT MP		
ENGINE						
Manufacturer	KOHLER 7000 Pro			KOHLER Confidant		
HP	48", 54": 23HP 60": 24HP (Per SAE J1995)			48", 54": 23HP 60": 25HP (Per SAE J1995)		
Displacement	725cc			747cc		
Cooling	Air cooled					
Engine Warranty	3 year					
DRIVE SYSTEM						
Type	Dual hydrostatic			Dual hydrostatic		
Transmission	Hydro-Gear ZT3100			Hydro-Gear ZT3400		
Speed	Up to 8 mph			Up to 9 mph		
Parking Brakes	Integrated with steering levers					
DECKS						
Cutting Width	48", 54", 60"			48", 54", 60"		
Cutting Heights	1.5"- 4.5"					
Deck Lift	Foot operated					
Depth	5"					
Blades	3					
Blade Length	48": 16.5" 54": 18.5" 60": 20.5"					
Blade Tip Speed	48": 18,600	54": 18,900	60": 18,400			
Spindles	Aluminum casting with steel shafts and sealed ball bearings					
Drive	Electric PTO Clutch					
Construction	10 ga. fabricated					
Spindle Mounts	Reinforced 11 ga.					
Impact/Trim Areas	11 ga formed channel with rolled edge					
CONSTRUCTION						
Frame	1.5" x 3" steel tubing			1.5" x 3" steel tubing		
Front Axle	Fabricated with sealed ball bearings					
Front Caster Wheels	Heavy duty ball bearings, greasable					
Front Caster Forks	Fabricated 3/8" steel					
GENERAL						
Seat	Mid-back suspension seat			High-back suspension seat		
Fuel Capacity	5 gallons			5 gallons		
Cupholder	Yes			Yes		
Front Tire	48": 13 x 5 - 6, Smooth tread 54", 60":13 x 6.5 - 6, Smooth tread			48": 13 x 5 - 6 54", 60":13 x 6.5 - 6		
Drive Tire	48": 23 x 9.5 - 10, BigBite 54", 60": 23 x 11 - 10, BigBite					
DIMENSIONS						
Weight	48": 855 lbs	54": 860 lbs	60": 880 lbs	48": 862 lbs	54": 891 lbs	60": 916 lbs
Height	45.5"			48.9"		
Length	76"			73.6"		
Width w/Chute	48": 49.1" 54": 55.1" 60": 61.1"					
Tire Width	48": 47.5" 54", 60": 51.5"					
Trim Side	48": 0.6" 54": 2.6" 60": 5.6"					
PRODUCTIVITY*						
Acres Per Hour	48": 3.10	54": 3.48	60": 3.88	48": 3.49	54": 3.93	60": 4.36

* Number based on 80% efficiency. This rating is to account for actual mowing conditions including overlapping, turning and terrain.

** Specifications are subject to change without notice.