











POWER-BAR STEERING SYSTEMThe easiest to learn, easiest to use walk-behind steering system.



WIDE STANCEFor increased stability.



COMPACT STANCEBetter maneuverability in tight spaces.





ENGINE

Manufacturer KOHLER®

HP 36": KOHLER Confidant – 19hp 48", 54": KOHLER Confidant – 23 hp

60": KOHLER Confidant - 25 hp

Displacement 36": 725cc 48", 54", 60": 747cc

Cooling Air Cooled, Fly-wheel fan

Engine Warranty 3 yrs

DRIVE SYSTEM

Type Dual hydrostatic
Transmission Hydro-Gear® ZT2800®

Speed Up to 6.3 mph

Parking Brakes Internal transmission mechanical brake

DECKS

Cutting Width 36", 48", 54", 60"

Cutting Heights 1.5"- 4.5"

Deck Lift Hand operated

Depth 5"

Blades 36": 2 48" 54" 60": 3 Blade Length 36": 17.86 48": 16.5"

54": 18.5" 40.10.5" 54": 20.5"

Blade Tip Speed 36": 18,400 48": 18,500 54": 18,800 60": 18,400

Spindles Aluminum with steel shaft and sealed ball bearings

Drive Electric PTO clutch

Construction 36": 7ga. + 11 ga. reinforced steel

48", 54", 60:" 10ga. + 11ga.reinforced steel

Spindle Mounts Reinforced 11 ga.

Impact/Trim Areas 11ga. formed channel rolled edge

CONSTRUCTION

Frame 1.5" x 2" tubular steel

Front Axle Fabricated with sealed ball bearings
Front Caster Wheels Tapered wheel bearings and debris cap

Front Caster Forks Fabricated 3/8" steel

GENERAL

Seat N/A
Fuel Capacity 3.4 Gal
Cup Holder N/A

Front Tire 11 x 4 Semi pneumatic

Drive Tire 36": 20 x 6.5 - 10 48": 20 x 8 - 10

54", 60": 20 x 10 - 10

DIMENSIONS

Weight	36": 560 lbs 54": 660 lbs	48": 635 lbs 60": 695 lbs
Height	36", 48", 54": 60": 42.55"	
Length	36": 76.7" 54": 75.3"	48": 75" 60": 77.5"
Width w/Chute Up	36": 37" 54": 55"	48": 49" 60": 61"
Tire Width	36": 35" 54": 46"	48": 44" 60": 46"
Trim Side	34": 0.9" 54": 5.4"	42": 2.4" 60": 8.4"

PRODUCTIVITY*

Acres Per Hour 36": 1.88 48": 2.44

54": 2.75 60": 3.06

OPTIONAL ACCESSORIES

Mulch Kit

Side Mesh Catcher

Stripe Kit

Side Steel Catcher (48", 54", 60" only) High Vacuum Kit (48", 54", 60" only)

 $[\]ensuremath{^{**}}$ Specifications are subject to change without notice.



^{*} Number based on 80% efficiency. This rating is to account for actual mowing conditions including overlapping, turning and terrain.