

# T2 ON-OFF ASSEMBLY



The Tier 1 T2 On-Off Assembly is a high pressure rated disconnect / re-connect tool commonly used in conjunction with down hole packers.

The T2 is typically configured to be left-hand release and auto-jay to the right to engage. The assembly consists of two primary components: the overshot and the slick joint.

The tubing string above the T2 may be recovered along with the overshot while leaving the slick joint in position down hole.

## CURRENT SIZES

Tubing:

- ⇒ 60.3mm
- ⇒ 73.0mm
- ⇒ 88.9mm

## STANDARD OFFERING

- ⇒ Left-hand set
- ⇒ P-110
- ⇒ EUE

## OPTIONS

- ⇒ Right-hand set
- ⇒ Premium / semi-premium connections
- ⇒ Sour Service
- ⇒ CRA materials
- ⇒ Shear release value
- ⇒ Coatings

## FEATURES & BENEFITS

- ⇒ Extensive run history proving reliability and longevity
- ⇒ Slim OD to ensure ease of installation
- ⇒ Large through-bore providing maximum flow area
- ⇒ Secondary shear release to ensure any retrieving operation is simple and successful
- ⇒ Easily and economically redressed to minimize workover expenses

## APPLICATIONS

- ⇒ Production
- ⇒ Vertical / Deviated
- ⇒ Injection
- ⇒ Stimulation

