TXT-II PACKER



The Tier 1 TXT-II is a high pressure rated service packer ideal for all types of operations requiring pressurized injection.

The TXT-II is a compression set packer with hydraulically activated upper slips that engage when tubing pressure exceeds the annular pressure above the packer. Once equalized the packer is simply unset with a straight pick up on the tubing string.

The TXT-II is utilized in applications such as hydraulic stimulation, cement squeezes, and high-pressure acidizing. The robust and field proven design combined with the three-element packing system ensure reliability and high-performance.

CURRENT SIZES

→ 114.3mm – 244.5mm (4.5" – 9.625")

STANDARD OFFERING

- → Right-hand set
- → Nitrile elastomers
- **⇒** P-110
- **⇒** EUE

OPTIONS

- → Left-hand set
- → Premium / semi-premium connections

FEATURES & BENEFITS

- Extensive run history proving reliability and longevity
- Large internal bypass area to maximize running and circulating rates
- Multiple hydraulic activated hold-down slips to ensure high-pressure injection performance
- Quarter-turn set/straight pick-up release providing ease of operation regardless of deviation

APPLICATIONS

- Service operations
- → Cement squeezing
- Fracturing
- Acidizing
- Pressure testing
- → Vertical / Deviated / Horizontal





