

Media Filters

HRV SIDE MOUNT SERIES MEDIA FILTERS

HRV-Series filters are heavy-duty, NSF-rated media filters engineered to withstand the high flows and pressures of semi-commercial and commercial applications up to 140 gpm. With reinforced neck ring and solid lid closure, this filter is the best fit for today's demanding projects.

- 8 lateral under-drain for optimal back-washing and filtering performance.
- 2" connections on all models
- Maximum operating pressure: 50 p.s.i.
- 3 Year Tank Warranty and 1 year warranty on all other components.



Model	Model Description	Sand Media (lbs.)	Surface Area (ft ²)	Height (in.)	Flow Rate (gpm) 15 - 20 gpm/ft ²	Shipping Weight
22207248	HRV 24" Filter (2" Connections)	300	3.14	38	47-63	19
22207308	HRV 30" Filter (2" Connections)	500	4.91	42	74-98	23
22207368	HRV 36" Filter (2" Connections)	800	7.07	46	106-141	32

MULTIPOINT VALVES

Multipoint valves are engineered to withstand a working pressure of up to 58psi with a test pressure of 87 psi.



Model	Model Description	Models Applied To	Shipping Weight
30B0045	1 1/2" Baker SM Multi. Valve	Baker HRV (Disc)	6
31B0084	1 1/2" Baker SM Multi. w/Piping	Baker HRV (Disc)	8
30B0047	2" Baker SM Multipoint Valve	HRV Series, Baker HRV (Disc)	8
31B0085	2" Baker SM Multi. w/Piping	HRV Series, Baker HRV (Disc)	10
31C0085	2" SM Multi. w/comm. Piping	Baker HRV (Disc)	11
31B0075	1 1/2" Piping Kit (Baker HRV)	HRV Series, Baker HRV (Disc)	2
31B0076	2" Piping Kit (Baker HRV)	HRV Series, Baker HRV (Disc)	2