


Gauges, Check Valves, Silencers, Enclosures

SS1708

Gauges




Gauges are important for monitoing the operating pressure or vacuum of the blower. Gauges should be positioned as close to the blower as possible.

Part number	Duty	Scale A		В	
VG25-60	Vacuum	0-60" H₂O		_	
VG25-200	Vacuum	0-200"H₂0		2.59	
VG25-300	Vacuum	0-300" H₂0	2.88		
PG25-60	Pressure	0-60" H ₂ 0			
PG25-200	Pressure	0-200" H ₂ 0			
PG25-300	Pressure	0-300" H ₂ 0			
PG25-15*	Pressure	0-15 psi	2.7	2.25	

Dimensions in inches. Tolerance on given values \pm 10% - unbinding and can be changed without prior notice.

Check Valves




Swing check valves allow air to flow in one direction. These valves prevent backflow into the blower and are supplied in bronze or brass.

and an experience and an exper					
Part Number	NPT	А	В	U	
CV075	0.75"	2.4			
CV10	1"	2.8	2.7	1.9	
CV125	1.25"	3.2	3.2	2.2	
CV15	1.5"	3.6	3.5	2.5	
CV20	2"	4.3	4.2	3.1	
CA30	3"	5.8	6.1	4.2	
CV40	4"	6.9	7.1	5.5	

Dimensions in inches. Tolerance on given values ± 10% - unbinding and can be changed without prior notice.

Silencers




Silencers provide additional sound attenuation.


TYPE	D	Α	В	С	E	F	lbs
SS 4	1″ 1/4	7.5	5.5	2.8	2	0.6	0.8
SS 5	1″ 1/2	7.9	6.7	3.1	1.2	0.8	1.1
SS 6	2″	9.1	7.9	3.5	1.2	0.8	1.3
SS 8	3″	19.1	15.7	6.0	3.3	0.8	4.8
SS 9	4"	18.3	16.9	6.7	1.1	0.8	9.9

Steel manufactured (apart from SI 9 / SS 9 - entirely in aluminium) with sound absorbing polyurethane element.

Dimensions in inches. Tolerance on given values $\pm\,10\%$ - unbinding and can be changed without prior notice.

Sound Enclosures





Part #	Used on models	Α	В	С
IH1	SCL KO3-MS	13.4	18.2	15.8
IH3	SCL KO4-MS	14.3	19.7	16.5
IH5	SCL K05-6 MS + 30-40DH	16.9	26.8	21.3
IH7	SCL K07-8 MS / MD	31.7	64.4	26
IH8	SCL KO7-8 TD	31.7	64.4	26
IH9	SCL K07-8 TS	31.7	64.4	26
IH10	SCL K09-12 MS/MD	31.7	67.2	30
IH11	SCL K09-10 TD	31.7	67.2	30
IH12	SCL K11-TD	31.7	67.2	30
IH13	SCL K09-11 TS	31.7	67.2	31.5

Dimensions in inches - unbinding and can be changed without prior notice.

^{*}PG25-15 is suitable for outdoor use