

# Equinox.



Aquarius



Aries



Capricorn



Leo



Pisces



Taurus

Equinox | Mixed

Equinox is a Stainproof SDX (Solution Dyed Nylon) tufted tile. The colours are based on earthy tones, which make Equinox perfect for commercial installations.

**BILL OF QUANTITIES:**

- Belgotex EQUINOX 50cm x 50cm NexBac tiles are manufactured from Stainproof SDX and Stainproof Eco SDX Blend (Solution Dyed Nylon).
- This product is to be laid in accordance with the SANS 10186 fitting code of practice.
- Belgotex EQUINOX can be installed in the following directions: tessellated, random and ashlar.
- Belgotex recommends the use of carpet protector mats where castor wheels are used.

\*\* Weighted Average \*\*\* Also available in 60 x 60cm, 1m x 50cm, 1m x 1m NexBac tiles, 25cm x 100cm and 30cm x 120cm NexBac plank tiles. EcoBac is standard for 50 x 50cm tiles in stock and available on request for 1m x 1m tiles. As these sizes and backings are not standard, minimum production quantities apply. Please contact your nearest Belgotex representative for more information.

## Extended Specifications

	<b>NexBac Tiles</b>
Construction	Tufted Multi Scroll Loop Pile
Product Description	Heavy Commercial, SDN, Tufted Loop Pile, Bitumen Tile
Yarn Type	Stainproof SDX (Solution Dyed Nylon)
Yarn Mass	575g/m <sup>2</sup>
Recycled Content	EcoBac/NexBac Eco (on request only) & Pile Yarn (certain colours only)
Use Classification	Heavy Commercial
Pile Height	2.5mm, 4.5mm, 5.5mm (±0.5mm)
Total Thickness	8mm (±0.5mm)
Total Mass	±4295g/m <sup>2</sup> **
Standard Tile Size	50 x 50cm***
Machine Gauge	1/10"
Stitches/10cm	45
Fire Index	2 (SANS 10177-IV)
Colour fastness to:	
(i) Light	7 (ISO 105-B02)
(ii) Rubbing	(a) Wet 4-5 (ISO 105-X12)
Rubbing	(b) Dry 4-5 (ISO 105-X12)
(iii) Water	4-5 (ISO 105-E01)
Electrostatic Propensity	Less than 2.0kV (ISO 6356 & EN1307)
Static Control	Permanent
VOC Tested	Passed

