B_

Rhythmic

Extended Specifications

Use Classification	Heavy Commercial 33 (EN 1307)
Construction	Pattern Colour Placement Loop Pile
Product Description	Heavy Commercial SDN Tufted Loop Pile Bitumen Tile - SCP
Recycled Content	Yarn - Stainproof SDX Eco (Certain Colours) Backing - EcoBac 300 & EcoBac 500
Yarn Type	Stainproof SDX (Solution Dyed Nylon-6)
Pile Height	± 2mm
Total Thickness	± 6mm (NexBac SX)
Total Mass	± 3900g/m² (NexBac SX)
Standard Size (tile)	50cm x 50cm / 25 x 100cm / 50 x 100cm / 100 x 100cm
Standard backing	NexBac SX
Custom Backing	EcoBac 300 & EcoBac 500
Machine Gauge	1/10”
Stitches / 10cm	50 (± 1)
Fire Index	2 (SANS 10177-4) Bfl-s1 (EN 13501) Class 1 (ASTM E648-08)
Colour Fastness To:	
i) Light	8 (AATCC 16/ISO 105 B02)
ii) Rubbing (change of colour)	4/5 (AATCC 165/ISO 105 x 12)
iii) Rubbing (staining)	5 (AATCC 165/ISO 105 x 12)
Electrostatic Propensity	≤ 2kV (ISO 6356/EN 1307)
Static Control	Permanent
Sound Absorption	aω 0.15 (EN ISO 354:2003)
Sound Insulation	ΔLw 18 dB (ISO 717-2)
Thermal Resistance	0.0638 m² K/W (ISO 8302)
VOC Tested	Pass (GBCSA/GBCA)
Castor Chair Suitability	A: Intense Use (NF EN 985)

B_

Beat


Drum


Even

Pace

Perfect


Pitch

Regular


Rock


Sound

Steady


Tone

Wave

Rhythmic

The Breakout Range.

BELGOTEX GUARANTEE 5 YEAR

LIMITED WEAR WARRANTY 15 YEAR

ANTI ALLERGENIC

REUSE REDUCE RECYCLE

COLOURFAST SDX BLEACH RESISTANT

COLOURFAST SDX ECO BLEACH RESISTANT

STAINPROOF SDN SOLUTION DYED NYLON

NEX BAC

ECO BAC

On Request

Eco-Friendly

Modular

Institution

Hospitality

Staircase Suitable

Underfloor Heating

Heavy Commercial

Medium/ General Commercial

MADE IN SOUTH AFRICA

Local & Imported Goods

greenstar 6 Existing Building Performance Custom Industrial v1 ★★★★★★ World Leadership GREEN BUILDING COUNCIL March 2017 – March 2020

GREEN BUILDING COUNCIL S.A. MEMBER ORGANISATION

SABS ISO 9001

SABS ISO 14001

GLOBAL GREEN TAG CERTIFIED GOLD STREAMLINED GBCSA | Level A SOUTH AFRICA trust brands

*Also available in 1m x 50cm, 1m x 1m NexBac tiles, and in 25cm x 100cm NexBac plank tiles. As these sizes are not standard, minimum production quantities apply. Please contact your nearest Belgotex Floors representative for more information.

Bill of Quantities

- Belgotex Rhythmic 50cm x 50cm tiles are manufactured from Stainproof SDX (Solution Dyed Nylon-6).
- This product is to be laid in accordance with the SANS 10186 fitting code of practice.
- Belgotex Rhythmic can be installed in the following directions: Ashlar, Random Ashlar, Brick, Random Brick, Colour Mix, Monolithic, Random and Tessellated (50 x 50cm/100 x 100cm tiles).
- Belgotex Rhythmic can be installed in the following directions: Ashlar, Random Ashlar, and Herringbone (25cm x 100cm / 50cm x 100cm planks).
- Belgotex recommends the use of carpet protector mats where castor wheels are used.

*All product names and logos are trademarks of BELGOTEX FLOORCOVERINGS® (Pty) Ltd.
© BELGOTEX FLOORCOVERINGS ® (Pty) Ltd. All rights reserved. Warranty and guarantee to limitations and conditions. For details contact BELGOTEX FLOORCOVERINGS®(Pty) Ltd.