


B...



Columbian Oak 649M



Columbian Oak 910M




Gambel Oak 119M



Laurel Oak 116L



Laurel Oak 669D




Nottingham 119M



Rockingham 790M



Tasmanian Oak 096L



Texas Oak 136L



Texas Oak 162L



Zinc 096L



Zinc 996D

Strut
Medium Commercial:
Cushion Vinyl

Extended Specifications

Type of Installation	Cushion Vinyl Sheetting
Use Classification	Heavy Residential/Medium Commercial
Application	Heavy Residential/Medium Commercial
Wear Layer Thickness	0.4mm
Overall Thickness	± 2.8mm
Product Width	± 4m
Backing	Black Tex Bac
Chemical Resistance	Resistant (ISO 26987/EN 423)
Fire Classification	Bfl-s1 (EN 13501-1)
Slip Resistance	R10 (DIN 51130)
Residual Indentation	≤ 0.20mm (EN ISO 24343-1/EN 433)
Thermal Resistance	0.018m²K/w (ISO 8302)
Thermal Conductivity	0.16 W/m.K (EN 12524)
Electrostatic Behaviour	≤ 2 kV (EN 1815)
Dimensional Stability	≤ 0.4% (EN ISO 23999/EN 434)
Colour Fastness	≥ 6 degree (EN ISO 105 B02)
Sound Absorption	Δ Lw 13dB (EN ISO 717/2)
Dynamic Coefficient of Friction	> 6 (EN 13893)
Underfloor Heating	Suitable (EN 12667)
Castor Chair	Note: Carpet Protector mats are necessary where castor wheels are used



Comfort Bac

Suitable for
Staircases

Underfloor
Heating

Heavy
Residential

Medium
Commercial

Natural
Look

Anti-
Bacterial

*All product names and logos are trademarks of BELGOTEX FLOORCOVERINGS® (Pty) Ltd.
© BELGOTEX FLOORCOVERINGS® (Pty) Ltd. All rights reserved. Warranty and guarantee
to limitations and conditions. For details contact BELGOTEX FLOORCOVERINGS® (Pty) Ltd.